

**PRODUCT INFORMATION**

Date of issue: 22.10.2020

**Diamant 5000 Super Cut****Application area:**

Silicone-free intensive rubbing compound for professionals.

**Product description:**

Diamant 5000 Super Cut is a silicone-free professional, intensive rubbing compound with a strong mix of abrasive grinding components. Thermally optimised aluminium oxide micro-particles ensure reliable defect correction with very simple machine guidance. After starting polishing, the cut immediately achieves, and leaves, a reduced hologram and homogeneously uniform gloss. Dust-free processing and effortless removal of polishing residues ("easy-off"). Removes grind sections up to 3,000 grit.

**Features:**

- extremely simple to apply
- with high-end abrasives
- free of silicone

**Application:**

Polytop Diamant rubbing compounds are applied best by a rotation polishing machine. Apply the Diamant 5000 evenly onto the Polytop polishing pad and process crosswise in sections on the paint surface. Polishing residues can be rubbed off by a microfiber cloth. Using a Polytop polishing fleece has a double or triple abrasiveness compared to a polishing sponge

**Additional information:**

Shake well before use! Protect against frost!  
Safety data sheet for professional users available under [www.polytop.de](http://www.polytop.de).

**Ingredients:**

EC 648/2004: aliphatic hydrocarbons 15-30%, anionic surfactants less than 5%, nonionic surfactants less than 5%, preservatives (PHENOXYETHANOL, LAURYLAMINE DIPROPYLENEDIAMINE, BUTYLBENZISOTHIAZOLINONE), additional information: paraffinum liquidum, abrasives, thickener

**Density:**

1,06

**Hazardous informations:**

Repeated exposure may cause skin dryness or cracking. Safety data sheet available on request

**Art. no.:**17200001  
17200250**Pack size:**1 Liter  
0,25 Liter