PRODUCT INFORMATION

Date of issue: 22.10.2020

POLYTOP®

Apex Seal

Application area:

Sealing with intensive deep gloss.

Product description:

Apex Seal is an extremely easy-to-process sealing with a combination of natural carnauba wax and synthetic waxes. The included polymers form a reactive connection with the paint surface and increase the service life. The result is an impressive wet look deep gloss and long-lasting repellent effect. 12 hours after application the maximum sealing level is reached.

Features:

- easy on / easy off-formula
- wet look Finish
- high water repelling effect

Application:

Put Apex Seal onto a soft application sponge or polishing fleece. Process in sections over the surface area in a uniform cross coat manner. For machine application we recommend an excentric polishing machine. Allow to dry a little bit, then wipe off with a microfiber cloth without pressure. Apex Seal does not dry completely before you polish off; therefore it is very easy in application.

Additional information:

Shake well before use! Protect against frost! Reserved for industrial and professional use. Keep out of reach of children. Safety data sheet available under www.polytop.de

Ingredients:

EC 648/2004: aliphatic hydrocarbons 15-30%, nonionic surfactants less than 5%, preservatives (PHENOXYETHANOL, LAURYLAMINE DIPROPYLENEDIAMINE, BUTYLBENZISOTHIAZOLINONE), fragrances, dye, additional information: silicone oil, waxes, synth. Polymers, thickeners

Density:

0,96

Art. no.:	Pack size:	
14900001	1	Liter
14900250	0,25	Liter
14900500	0,5	Liter

Hazardous informations:

Safety data sheet available on request