

**PRODUCT INFORMATION**

Date of issue: 22.10.2020

**Oxide Ultra Cut****Application area:**

Intensive rubbing compound for professionals.

**Product description:**

Oxide Ultra Cut is a silicone-free professional, intensive rubbing compound with an extremely strong mix of abrasive grinding components. Thermally optimised aluminium oxide micro-particles ensure reliable defect correction with very simple machine guidance. After starting polishing, the cut immediately achieves, and leaves, a reduced hologram and homogeneously uniform gloss. Dust-free processing and effortless removal of polishing residues („easy-off“). Removes grind sections up to 2,000 grit.

**Features:**

- extremely simple to apply
- with high-end abrasives
- free of silicone

**Application:**

Oxide Ultra Cut rubbing compound is applied best by a rotation polishing machine. Apply the Oxide Ultra Cut evenly onto the POLYTOP polishing pad RED and process crosswise in sections on the paint surface. Polishing residues can be rubbed off by a microfiber cloth. Using a POLYTOP polishing fleece has a double or triple abrasiveness compared to a polishing pad.

**Additional information:**

Shake well before use! Protect against frost!  
Safety data sheet for professional users available.

**Ingredients:**

EC 648/2004: aliphatic hydrocarbons 15-30%, anionic surfactants less than 5%, nonionic surfactants less than 5%, preservatives (PHENOXYETHANOL, LAURYLAMINE DIPROPYLENEDIAMINE, BUTYLBENZISOTHIAZOLINONE), additional information: paraffinum liquidum, abrasives, thickeners

**Density:**

1,10

**Hazardous informations:**

Safety data sheet available on request

**Art. no.:****Pack size:**

17350001	1	Liter
17350005	5	Liter
17350250	0,25	Liter