



TECNICAL DATA SHEET

10974 WOOD PUTTY

Product Description: Asboya Acrylic copolymer emulsion based, water-based colors, interior-exterior wood putty.

General Use: Internal and external fronts, especially all kinds of wooden surfaces and surface smoothing compound used as a filler, with high filling power, fast drying, easy sanding, applied to the surfaces silky inner and outer facade gives the appearance of wood putty. Builds on a solid foundation for the paint to be applied, reduces paint consumption. Water and moisture resistant.

Tecnical Specification

Density	: 1,75-185
Solid %	: Weight: 70-80
Viscosity	: > 140 Ku

Application Type: Application to solid surfaces, must be clean and dry. Swollen and old painted surfaces should be cleaned by scraping. After substrate preparation with a trowel or spatula inner and outer wall wood Paste 1 or 2 coats are applied. Ready for use, thinning is done. After the application should be sanded with fine sandpaper.

Coverage: 2- 2,5 m² / kg (depending on surface)

Drying Time: (25 ° C) Drying Time: 2-3 hours (23 ° C, 50% relative humidity)

Shelf life: 2 years in unopened package



STIR



CLEAN THE
SURFACE



STORE IN TIGHTLY
CLOSED PACKAGES



DRY
SANDING



APPLY WITH
A SPATULA



PROTECT FROM
FROST