

TIXE srl
Via Carlo Ferrari, 49
(Frazione Pratalborato)
15060 Capriata d'Orba (AL) IT
Phone +39 0143 46397



www.tixepaint.com
mail@tixepaint.com
Partita IVA IT 01779800992



Family: GOLD PAINT



Product: GOLD PAINT FOR INDOOR WATER BASED

DESCRIPTION:

Water-based paint, pigmented with bronze powder, in different shades.

MAIN FEATURES

Leafing effect
High brilliance
High decorative effect

USE

Ready to use. Ideal for the treatment of wooden rods for frames, stuccos, fillets and decorations of antique furniture, restoration of antique furniture, touch-ups of brassed and coppered objects.

APPLICATION

The surface to be painted with DORATURA ACQUA PER INTERNI must be prepared with a suitable treatment, namely:

ON NEW SUPPORTS:

for better anchoring and for a longer life, the surface must be carefully degreased with water and soap or washing diluent. Sand and apply a primer, then apply one coat of the product.

ON PAINTED SUPPORTS: if the pre-existing layer of paint does not recommend complete removal, degrease with water and detergent, rinse. If the existing paints are in the phase of detachment, brush and sand these parts thoroughly, or proceed with the paint stripping with paint stripper. Wash with a washing diluent, or with soap and water, then apply a primer and then apply one coat of the product.

Use suitable preparatory primers for surfaces in iron, wood, plastic, plaster.

During application by brush or roller do not cross the hand, and do not pull the product, but leave a rather abundant film, to facilitate the formation of the metal mirror.

Avoid the application of a second coat, which would remove the previous one, compromising the formation of the metal mirror, which is the typical prerogative of the ECOLINE DORATURA.

Recommended applications: brush, roller, immersion, spray, airless.

To dust the treated surface with INTERNAL WATER DORATURE, use a soft, gently used cloth.

The application of the product is ONLY and EXCLUSIVELY recommended for internal use.

IF IT DOES NOT EXCEED THE APPLICATION OUTSIDE, as it is subject to rapid oxidation and consequent darkening, when exposed to moisture and / or aggressive agents.

TIXE srl
Via Carlo Ferrari, 49
(Frazione Pratalborato)
15060 Capriata d'Orba (AL) IT
Phone +39 0143 46397



www.tixepaint.com
mail@tixepaint.com
Partita IVA IT 01779800992



Environmental and support conditions:

The substrate must be dry, free from dust, grease and any other pollutant

Room temperature: min. 10 ° C / max 35 ° C

Relative humidity of the environment: <75%

Support temperature: min. 10 ° C / max 35 ° C

DILUTION

The product is to be used as it is, whatever with water. Given the nature of the pigment, consisting of bronze micro scales, there is a marked tendency of the metallic pigment to settle.

It is therefore recommended a careful mixing of the PRIMA product and DURING the APPLICATION, in order to guarantee the constant homogeneity of the product.

STORAGE

In a cool and well-ventilated environment.

Keep the tin tightly closed, overturned and protected from frost and heat sources.

PHYSICAL CHARACTERISTICS

(at 20 ° C and 50% - 60% U.R.)

Specific weight 1.16 ± 0.02 Kg./l. For pale, rich, rich pale, copper, duchy

Yield (*) 8 - 10 m² / l

Draining time 13 "± 3" ISO cup 2

Drying 1 hour off impression
5 hours deep

Storage life At least 36 months

(*) The yield depends on the nature and porosity of the surface

SHADES '

PALLID, RICH, RICH PALLIDO, COPPER, DUCATO

VOC CLASSIFICATION

Interior / exterior finishing and cladding paints for wood, metal or plastic.

VOC expressed in g / liter of product ready for use:

Maximum limit: 150.00 (2007) - 130.00 (2010)

Product VOC: 11.99

PRECAUTIONS

In addition to the risk and precautionary signs that regulate INTERNAL WATER DORATURE in the form of production and which are shown on the container, it is recommended, before applying the product, to consult the relative SAFETY DATA SHEET.

However, it is good practice to use protective gloves and goggles, and to apply it in a well-ventilated area.