



HEAVY DUTY WALLPAPER ADHESIVE

1 – DESCRIPTION

HEAVY DUTY WALLPAPER ADHESIVE is a premium Wallpaper Adhesive which is based on cold water dispersible starch derivative.

2 – PROPERTIES

- Easy to apply.
- Thanks to quick dissolving adhesive, viscosity rise quickly.
- Allows time for positioning.
- Makes future removal quick and easy.
- Dissolves in water with ease.
- Can be cleaned with a sponge and water.
- Contains anti-fungal & bacterial protection.

3 - APPLICATIONS

Thoroughly clean walls and ceilings. Painted walls and highly glazed non-porous walls should be lightly sanded and washed down. Old wall coverings and paste must be removed with a Wallpaper Remover. Porous substrates should be sized. Allow thoroughly drying before hanging wallpapers / wall coverings.

4 - INSTRUCTIONS

Add the adhesive slowly, in preferably warm, water in accordance with the figures shown below. Stir the mixture and allow the adhesive dissolve in the water. Make sure that substrates are clean, dry and smooth. Roll the mixture to the back of wallpapers.

5- PACKAGING

<i>Product</i>	<i>Weight</i>	<i>Package</i>
HEAVY DUTY WALLPAPER ADHESIVE	250 gr	50
HEAVY DUTY WALLPAPER ADHESIVE	25 kg	1

6- STORAGE AND SHELF LIFE

24 months in unopened cartridge if stored under dry and cool conditions

7- SAFETY

- Must be used in well ventilated areas.
- Must be kept away from children.



- The product contains preservative.

8- TECHNICAL PROPERTIES

Basis	: Carboxymethylated
Appearance	: Flakes
Colour	: White to creamy
Viscosity at 3 min.	: 8000 cPs at 23°C (Brookfield RTV, 20 rpm, Sp.3)
pH	: 8
Temperature Resistance	: -20°C to +70°C
Application Temperature	: +5°C to +35°C

Application Ratios

For 250gr s of adhesive

Paper Type	Amount of Water	Roll	Surface
Light paper	8,5 Liter	9-10	45-50 m ²
Normal paper	6 Liter	9-7	38-45 m ²
Heavy paper	4 Liter	5-6	25-30 m ²