



ACRYLIC WATERPROOFING MEMBRANE

1 – DESCRIPTION

Acrylic Waterproofing Membrane is a one component, water based, acrylic copolymer based elastic waterproofing membrane.

2 – PROPERTIES

- Ready to use
- Can be easily applied with airless spray gun, roller or brush
- Low labor cost
- Does not contain solvent, can be diluted with water
- Water vapor permeable
- Resistant to UV
- Maintains elasticity even at low temperatures
- Over paintable
- High opacity
- Can be colored with water based color pastes
- Seamless application

3 - APPLICATION AREAS

Waterproofing of;

- Balconies, terraces and roofs
- Facades
- Wooden surfaces
- Asphalt and bitumen floorings
- Roofing details such as gutters, chimney edges etc.

4 – INSTRUCTIONS

Ensure that the surfaces to be waterproofed are clean, dry and free from grease. On porous surfaces such as concrete, cement and plaster a primer (mixture of 4-5 parts one part acrylic waterproofing membrane and 1-2 parts of water) can be applied. It is recommended to apply anti-corrosive primers for metal surfaces. Apply non-diluted Acrylic waterproofing membrane on the surface by using airless spray gun, roller or brush only in a single direction. Wait sufficient amount of time to allow the first layer to dry. Then apply next layer in the opposite direction. The optimum layer thickness is approx. 1 mm. Apply minimum 2 layers. It is recommended to use reinforcing textiles for connection lines or surfaces with cracks.

5- STORAGE AND SHELF LIFE



12 months if stored properly in its original package between +5 °C and 25 °C in a dry environment and protected from direct sunlight.

6- RESTRICTIONS

- It should not be applied in case of risk of rain or frost.
- Prevent applied waterproofing layer from rain or frost for at least 24 hours
- Not suitable for pressurized water
- Not recommended for pedestrian or vehicle traffic. In such a case, the surface of waterproofing layers should be covered with suitable elements such as tiles or protective surface covering materials.

7-SAFETY & DISPOSAL

Check MSDS guidelines for disposal and further information concerning safety.

8- TECHNICAL PROPERTIES

| | |
|--|--|
| Chemical Basis | : Acrylic copolymer |
| Solid Content | : %70-80 |
| Density | : 1,37 ± 0,03 g / ml |
| Consistency / Color | : Liquid / White |
| Viscosity | : 50.000 ±5000 (Spindle No:6, 12rpm, 20°C) |
| Dry Time for Next Layer Application | : 4-5 hours (23°C, %50 R.H.) |
| Service Time | : 48 hours (23°C, %50 R.H.) |
| Consumption | : Horizontally 1,0-1,5 kg/m², vertically 0,75 kg/m² |
| Elongation at Break | : ≥ 600% (DIN 53504) |
| Tensile Strength | : >1 N/mm² (DIN 53504) |
| Application Temperature | : +5°C to +35°C |
| Ambient Temperature | : +5 °C to +35°C |