

PROLOC HYBRID WATERPROOFING MEMBRANE

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 26.01.2021

Version: 00

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : PROLOC HYBRID WATERPROOFING MEMBRANE
Type of product : Coating

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

AKKİM YAPI KİMYASALLARI SANAYİ ve TİCARET A.Ş.
Yeşilbayır mahallesi Şimşir sokak No:22
34555 İSTANBUL - TURKEY
T +90 2127711371 - F + 90 2127713888
info@proloc.com.tr - www.proloc.com.tr
E-mail address of competent person responsible for the SDS : nilufer.ergin@akkim.net

1.4. Emergency telephone number

Emergency number : +90 2127711371 (9:00 am - 17:00 pm GMT+2)

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre, Wolfson Unit	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

May cause an allergic skin reaction. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) : Warning
Hazardous ingredients : N-(3-(trimethoxysilyl)propyl)ethylenediamine, trimethoxyvinylsilane
Hazard statements (CLP) : H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.

PROLOC HYBRID WATERPROOFING MEMBRANE

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 26.01.2021

Version: 00

Precautionary statements (CLP)	: P102 - Keep out of reach of children. P261 - Avoid breathing dust, fume, gas, mist, spray, vapours. P280 - Wear eye protection, face protection, protective gloves, protective clothing. P302+P352 - IF ON SKIN: Wash with plenty of water. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Child-resistant fastening	: Not applicable
Tactile warning	: Not applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Titanium Dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5	1 – 5	Not classified
N-(3-(trimethoxysilyl)propyl)ethylenediamine	(CAS-No.) 1760-24-3 (EC-No.) 217-164-6 (REACH-no) 01-2119970215-39	< 2	Acute Tox. 4 (Inhalation), H332 Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT RE 2, H373
trimethoxyvinylsilane	(CAS-No.) 2768-02-7 (EC-No.) 220-449-8 (REACH-no) 01-2119513215-52	1 – 1.5	Skin Sens. 1B, H317
dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)]stannane	(CAS-No.) 77-58-7 (EC-No.) 201-039-8 (EC Index-No.) 050-030-00-3 (REACH-no) 01-2119496068-27	< 0.05	Muta. 2, H341 Repr. 1B, H360FD STOT RE 1, H372

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

PROLOC HYBRID WATERPROOFING MEMBRANE

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 26.01.2021

Version: 00

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane (77-58-7)	
Austria - Occupational Exposure Limits	
Local name	Dibutylzinndilaurat
Remark (AT)	Fortpflanzungsgefährdend: F, D
Regulatory reference	BGBl. II Nr. 238/2018
Titanium Dioxide (13463-67-7)	
Austria - Occupational Exposure Limits	
Local name	Titandioxid (Alveolarstaub)
MAK (OEL TWA)	5 mg/m ³
MAK (OEL STEL)	10 mg/m ³

PROLOC HYBRID WATERPROOFING MEMBRANE

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 26.01.2021

Version: 00

Titanium Dioxide (13463-67-7)	
Regulatory reference	BGBl. II Nr. 186/2015
Belgium - Occupational Exposure Limits	
Local name	Titane (dioxyde de) # Titaandioxide
OEL TWA	10 mg/m ³
Regulatory reference	Koninklijk besluit/Arrêté royal 02/09/2018
Bulgaria - Occupational Exposure Limits	
Local name	Титанов диоксид
OEL TWA	10 mg/m ³ (респирабилен прах)
Croatia - Occupational Exposure Limits	
Local name	Titanov dioksid
GVI (OEL TWA) [1]	10 mg/m ³ U (ukupna prašina) 4 mg/m ³ R (respirabilna prašina)
Denmark - Occupational Exposure Limits	
Local name	Titandioxid
OEL TWA [1]	6 mg/m ³ beregnet som Ti
Regulatory reference	BEK nr 655 af 31/05/2018
Estonia - Occupational Exposure Limits	
Local name	Titaanoksiid
OEL TWA	5 mg/m ³
Regulatory reference	Vabariigi Valitsuse 18. septembri 2001. a määruse nr 293 (RT I, 30.11.2011, 5)
France - Occupational Exposure Limits	
Local name	Titane (dioxyde de), en Ti
VME (OEL TWA)	10 mg/m ³
Note (FR)	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Greece - Occupational Exposure Limits	
Local name	Τιτανίου διοξειδίο
OEL TWA	10 mg/m ³ εισπν. 5 mg/m ³ αναπν.
Regulatory reference	Π.Δ. 90/1999
Ireland - Occupational Exposure Limits	
Local name	Titanium dioxide
OEL TWA [1]	10 mg/m ³ total inhalable dust 4 mg/m ³ respirable dust
Regulatory reference	Code of Practice for the Chemical Agents Regulations 2018
Latvia - Occupational Exposure Limits	
Local name	Titāna dioksīds
OEL TWA	10 mg/m ³
Regulatory reference	Ministru kabineta 2007.gada 15.maija noteikumiem Nr.325 (Grozījumi Ministru kabineta 2011.gada 1.februārī noteikumiem Nr.92)

PROLOC HYBRID WATERPROOFING MEMBRANE

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 26.01.2021

Version: 00

Titanium Dioxide (13463-67-7)	
Lithuania - Occupational Exposure Limits	
Local name	Titano dioksidas
IPRV (OEL TWA)	5 mg/m ³
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Poland - Occupational Exposure Limits	
Local name	Ditlenek tytanu
NDS (OEL TWA)	10 mg/m ³ frakcja wdychalna
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
Local name	Dióxido de titânio
OEL TWA	10 mg/m ³
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Dioxid de titan
OEL TWA	10 mg/m ³
OEL STEL	15 mg/m ³
Regulatory reference	Hotărârea nr. 584/2018
Slovakia - Occupational Exposure Limits	
Local name	Oxid titaničitý
NPHV (OEL TWA) [1]	5 mg/m ³
Regulatory reference	Nariadenie vlády č. 33/2018 Z.z.
Spain - Occupational Exposure Limits	
Local name	Dióxido de titanio
VLA-ED (OEL TWA) [1]	10 mg/m ³
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT
Sweden - Occupational Exposure Limits	
Local name	Titandioxid
NGV (OEL TWA)	5 mg/m ³ totaldamm
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	Titanium dioxide
WEL TWA [1]	4 mg/m ³ respirable 10 mg/m ³ total inhalable
Regulatory reference	EH40/2005 (Third edition, 2018). HSE
Iceland - Occupational Exposure Limits	
Local name	Títandíoxíð, sem Ti
OEL TWA	6 mg/m ³
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)

PROLOC HYBRID WATERPROOFING MEMBRANE

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 26.01.2021

Version: 00

Titanium Dioxide (13463-67-7)	
Norway - Occupational Exposure Limits	
Local name	Titandioksid
Grønseverdi (OEL TWA) [1]	5 mg/m ³
Regulatory reference	FOR-2018-08-21-1255
Switzerland - Occupational Exposure Limits	
Local name	Dioxyde de titane / Titandioxid
MAK (OEL TWA) [1]	3 mg/m ³ (a) / (a)
Critical toxicity	VRI / UAW
Notation	SS _C / SS _C
Remark	NIOSH
Regulatory reference	www.suva.ch, 01.07.2019
USA - ACGIH - Occupational Exposure Limits	
Local name	Titanium dioxide
ACGIH OEL TWA	10 mg/m ³
Remark (ACGIH)	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2019

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

EN 374. Protective gloves

Skin and body protection:

Wear protective clothing

Eye protection:

EN 166. Safety glasses

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Flowable liquid.

PROLOC HYBRID WATERPROOFING MEMBRANE

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 26.01.2021

Version: 00

Colour	: White. Grey.
Odour	: Characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 60 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.44 g/ml
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 10000 – 20000 cP
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	1.49 – 2.44 mg/l air Animal: rat, Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity), Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

PROLOC HYBRID WATERPROOFING MEMBRANE

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 26.01.2021

Version: 00

dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane (77-58-7)	
LD50 oral rat	2071 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1207 - 5106
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))

Titanium Dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified

trimethoxyvinylsilane (2768-02-7)	
NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)
NOAEL (animal/female, F0/P)	250 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)

dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane (77-58-7)	
NOAEL (animal/male, F0/P)	1.9 – 2.3 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
NOAEL (animal/female, F0/P)	1.7 – 2.4 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure : Not classified
STOT-repeated exposure : Not classified

trimethoxyvinylsilane (2768-02-7)	
LOAEL (oral, rat, 90 days)	62.5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (oral, rat, 90 days)	< 62.5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	
NOAEL (oral, rat, 90 days)	≥ 500 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (dermal, rat/rabbit, 90 days)	≥ 1545 mg/kg bodyweight Animal: rat

Aspiration hazard : Not classified

PROLOC HYBRID WATERPROOFING MEMBRANE

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 26.01.2021

Version: 00

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

trimethoxyvinylsilane (2768-02-7)

LC50 - Fish [1]	> 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Daphnia [1]	168.7 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 957 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

LC50 - Fish [1]	597 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Daphnia [1]	81 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	126 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	352 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane (77-58-7)

EC50 - Daphnia [1]	1.7 – 3.4 mg/l Test organisms (species): Daphnia magna
EC50 - Daphnia [2]	< 463 µg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

Titanium Dioxide (13463-67-7)

LC50 - Fish [1]	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Daphnia [1]	19.3 mg/l Test organisms (species): Daphnia magna
EC50 - Daphnia [2]	27.8 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 2.92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

PROLOC HYBRID WATERPROOFING MEMBRANE

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 26.01.2021

Version: 00

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

Reference code	Applicable on	Entry title or description
30.	dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane	Substances which are classified as reproductive toxicant category 1A or 1B in Part 3 of Annex VI to Regulation (EC) No 1272/2008 and are listed in Appendix 5 or Appendix 6, respectively.

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

PROLOC HYBRID WATERPROOFING MEMBRANE

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 26.01.2021

Version: 00

15.1.2. National regulations

Germany

Regulatory reference : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1)
 Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)
 Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)
 Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed
 SZW-lijst van mutagene stoffen : None of the components are listed
 NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed
 NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane is listed
 NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane is listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed
 Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Switzerland

Storage class (LK) : LK 10/12 - Liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration

PROLOC HYBRID WATERPROOFING MEMBRANE

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 26.01.2021

Version: 00

NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 2	Germ cell mutagenicity, Category 2
Repr. 1B	Reproductive toxicity, Category 1B
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H226	Flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H341	Suspected of causing genetic defects.
H360FD	May damage fertility. May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

PROLOC HYBRID WATERPROOFING MEMBRANE

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 26.01.2021

Version: 00

SDS EU PROLOC

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable