

Banja Komerc Bekament DOO	TECHNICAL DATA SHEET	Edition 2	Date: December 12 2018
		Version 0	
BK-POL, BK-POL FRESH			RZ-TLP-010

## 1. PRODUCT AND COMPANY INFORMATION

**Commercial product name:** BK-Pol  
BK-Pol Fresh

**Manufacturer:** Banja Komerc Bekament DOO  
34304 Banja  
Arandelovac  
tel. 034-6777-500  
fax. 034-6777-505  
email: komercijala@bekament.com

**TDS contact:** email: laboratorija@bekament.com

## 2. DESCRIPTION, FIELD OF APPLICATION

BK-Pol and BK-Pol Fresh are high-quality acrylic emulsion-based dispersion paints. They are intended for interior use. They have great coverage vapor permeability. They are suitable for the decorative protection of interior walls and ceilings in residential and commercial objects, in places where there is no need for a high level of resistance and in places where there are no other specific requests. They are suitable for frequent painting of interior walls. Surfaces painted over are resistant to dry wiping; cleaning using wet cloth is not possible. It is considered an eco-product not harmful to human health or the environment. It does not contain organic solvents.

## 3. COMPOSITION

**Chemical composition:** Aqueous polymer emulsion, water, additives, pigments, and mineral fillers.

**Hazardous substances:** In accordance with the (EC) Regulation No. 1272/2008 on classification, labelling and packaging of substances and mixtures, through which the CLP/GHS classification and labeling system was introduced into law, this product is not classified as a hazardous product.

## 4. TECHNICAL CHARACTERISTICS

Density, g/dm <sup>3</sup> (EN ISO 2811-1)	1,600-1,700
Adhesion, MPa (EN ISO 4624)	≥ 1.0

Banja Komerc Bekament DOO	TECHNICAL DATA SHEET	Edition 2	Date: December 12 2018
		Version 0	
BK-POL, BK-POL FRESH			RZ-TLP-010

Wet wiping resistance, $\mu\text{m}$ (EN ISO 11998)	$\geq 70$ at 40 cycles (Class 5 according to EN 13300)
Particle size, $\mu\text{m}$ (EN 1524)	$< 100$ (fine according to EN 13300)

Shine, % (EN ISO 2813)	$< 5$ at an angle of $85^\circ$ (deep matte according to EN 13300)
Coverage (EN 6504-3)	Class 2 at $6 \text{ m}^2/\text{l}$ ( according to EN 13300)
Viscosity, mPas (EN ISO 2555)	45,000-55,000
Indicative consumption, $\text{g}/\text{m}^2$	$\sim 200-300$
Packaging, kg	1.5; 5; 8; 15; 25;

## 5. OTHER CHARACTERISTICS

**Physical appearance:** White or colored viscous liquid

**Odor:** PK-Pol - specific of polymeric binders

BK-Pol Fresh - lemon pH

**value (EN ISO 787-9):** 8-9

**Dry matter content (EN ISO 3251), %:**  $\sim 70$

**VOC\* content, g/l:**  $< 1$  (maximum value allowed A (a) 30 g/l)

\*VOC: Volatile Organic Compound;

Possibility of choosing over 500 shades according to Bekament's color charts with a limited selection of midtones and pastel colors. Pastel tones may also be made using the BK-Color and BK-Fas Color shading products. We do not guarantee a complete match according to the color charts of other manufacturers, nor do we guarantee absolute repeatability of shades.

## 6. SURFACE PREPARATION

The surface to which the paint is applied must be firm, clean, and dry, without poorly bound parts, greasy stains, etc. The following surfaces are appropriate: surfaces smoothed using smoothing masses, as well as surfaces where dispersion colors had taken solid hold. Before painting, the surface must be coated using the primer BK-Podloga. The primer must be left to dry before applying the paint for at least 12 hours. Surfaces smoothed out using BK-GletEx Universal and BK-Gletex Acryl do not need to be painted over with a base before applying paint.

Banja Komerc Bekament DOO	TECHNICAL DATA SHEET	Edition 2	Date: December 12 2018
		Version 0	
BK-POL, BK-POL FRESH			RZ-TLP-010

When the surfaces being repainted have wall mould, they should be disinfected with BK-Sanacid. When the surfaces in question have been previously treated with oil-based paints, varnishes, etc, a complete removal of all existing spreads must be performed.

## **7. PREPARATION AND APPLICATION**

Stir the mass before use and homogenise the materials from different batches and/or packages. After that, dilute the mass with about 15-20% of water. The paint is applied using a short-haired roller or brush, most often in two layers. Application of the second layer is done after the first layer is completely dry. In normal conditions (T=+23-25 °C, relative humidity=50-60 %), this takes 4-6 hours. Additional correction of paint during installation (additional dilution, adding pigments, etc.) are prohibited.

Work must be even and without interruptions in continuous wall surfaces so as to avoid any irregularities created due to the adhesion of surfaces, irregular drying, etc.

Air and surface temperature during installation should be in the +5 °C to +30 °C range.

## **8. CLEANING THE TOOLS**

All tools must be thoroughly washed using water immediately after use. If the tools are not washed immediately after use, remove the hardened residue mechanically. Removal may be easier if the tools are submerged in water over a period of several hours.

## **9. HANDLING AND STORAGE**

No special caution during use is needed when using the product properly. Keep out of reach of children.

Store at temperatures between +5 °C and +25 °C, protected from direct sunlight and frost. Shelf life: 18 months.

## **10. PERSONAL PROTECTION**

Respiratory tract protection: Not needed when the rooms are well aerated.

Hands and body protection: When the skin is repeatedly exposed to the mass, a preventative use of protection gloves is recommended. Use long-sleeve work overalls. Eye protection: Use safety goggles as a preventative measure.

## **11. ECOTOXICOLOGICAL INFORMATION**

Based on experiences and information currently available, no negative health effects are known when the product is used appropriately. Prevent uncontrolled discharge into sewage and waterways.

<b>Banja Komerc Bekament DOO</b>	<b>TECHNICAL DATA SHEET</b>	<b>Edition 2</b>	<b>Date: December 12 2018</b>
		<b>Version 0</b>	
<b>BK-POL, BK-POL FRESH</b>			<b>RZ-TLP-010</b>

## **12. STORAGE**

In accordance with local/regional/European/national regulations.

## **13. OTHER INFORMATION**

The color chart was printed on paper. While applying the product onto various surfaces, certain smaller deviations from the color chart may be expected. These deviations are not subject to claims. Certain deviations of the paint in relation to the appropriate shade in the color chart are possible due to the use of natural mineral fillers. The uneven color shading of a surface painted over may be the consequence of inappropriate conditions at installation, differences in absorption, and the roughness of the base. The appearances of stains on the wall are remediated by painting over the entire surface of the wall. Painting over just one section of the wall is not recommended.

Banja Komerc Bekament DOO does not guarantee a complete match of shades from various batches. Deviations in terms of tone are not subject to claims.

If the contractor notices an aesthetic or application deficiency while using the material, he is obliged to cease the works and notify the manufacturer of this. The manufacturer will consider the claim in the shortest possible time frame. Complaints to the manufacturer upon using a significant portion or the entire amount of the materials are not subject to claims.

## **14. NOTE**

Banja Komerc Bekament DOO performs product quality checks using its own laboratories. It also regularly tests its products in certified laboratories. The Data Sheet is the product of our knowledge and previous practical experience. The purpose of the Data Sheet is to serve as a recommendation in order to achieve the best possible results. If weather and other conditions are different than those described in our instructions, our instructions need to be taken as general guidelines, without an installation warranty.

Banja Komerc Bekament DOO assumes no liability for damages resulting from the improper use or incorrect product selection, as well as for poorly executed work. It is assumed that the contractor has mastered the techniques of installing and use of various products.

Matters written herein bind us in no way.

This document replaces all previous versions. All previous versions, starting with the listed date the document was compiled, are void.

Date: November 21 2011

Previous version: Version 1.5 - June 18 2015

Amended chapters: 4,6,7.