

DECOSTUCCO is an acrylic emulsion based; containing various types of quartz, limestone and pigments; at the paste consistency; given texture and form with trowel or spatula; glossy interior wall coating material.

FEATURES

- Gives the appearance of marble effect to the surface applied
- Provide high brightness due to the vibrant and luminous colors
- Due its high vapor permeability, it allows surface to discharge the steam and breathe
- As it is water-based, it is harmless to human health and environment
- It provides a pleasant odour in the application environments with its perfumed feature.

APPLICATION AREA

Used after surface preparation with the appropriate primer on wall, plaster coating, concrete and wood surfaces.

SURFACE PREPARATION

After removing all kinds of dirt, grease, bloated paint and dust from the application surface, the surface defects should be corrected with **SAN DECO Acrylic Putty Interior** and undercoated with **SAN DECO Decoprimer**.

APPLICATION INSTRUCTIONS

- **DECOSTUCCO** should well mixed before application
- One layer **DECOSTUCCO** is applied to the surface with a stainless steel trowel, the second coat is applied if the desired smoothness and coverage is not obtained.
- Once the product is dried after 24 hours, the surface is sanded with fine sandpaper and the desired effect is applied by trowel or spatula. To make the surface more glossy, steel trowel work can be done over again.
- The environment of application must be kept between +5 °C to +35 °C within 24 hours during and after the application.

TECHNICAL DATA

DENSITY (g/cm³)	1,73±0.02
VISCOSITY (Krebs Unit)	Viscous
FLASH POINT	Water Based
PH	8-9
SOLID CONTENT % wt	74±2
VOC (g/ltr) (EU Directive 2004/42/EC) Calculated theoretically.	80
DILUTION	No
COLOR	Decostucco Color Chart-It can be colored with "tinting system."
THEORETICAL CONSUMPTION * (g/m²) (For one coat)	400-600
COVERING CAPACITY (m²/Kg)	1,65 - 2,50
DRYING TIME (at 23°C)	Touch dry time 2-3 hours, Complete dry time 24 hours
SHELF LIFE**	1 Year
PACKAGING	5 Kg / 10 Kg / 20 Kg

* Theoretical Consumption Values are calculated for total consumption with the condition of the surface smoothness, its porosity and application methods.

** Shelf life is valid when the product is stored in its sealed package at cool and dry place, protected from direct sunlight and at storage temperature + 5°C and + 35°C conditions.

WARNINGS/ PRECAUTIONS

- **P 102** Keep out of reach of children.
- **P 301+ P 310 IF SWALLOWED:** Immediately call a **POISON CENTRE** or doctor/physician.
- Don't use the containers for food preservation.