



TECHNICAL DATA SHEET

GRAFIT ENAMEL Product code: 11110

Description: Developed for metal and wood surfaces and effects that look texture, rough surfaces, decorative enamel paint hides imperfections. Get high lighted floor and preferred for high corrosion resistance.

General Use: Interior and exterior surfaces of wood, masonry and metal surfaces, painting and sign type used in studies.

Density: 0.90-1,20 g/ml

Viscosity: 70-80 KU

Gloss Grade: Gloss

Drying Time: Touch dry within 1 hours and Hard dry after 24 hours

Coverage/ Spreading Minimum 10-14 m² surface can be painted with one liter at recommended film thickness

Method of use : Before starting the painting process, the surface should be cleaned from dirt, dust, oil and layers. Stir well before use. Thinning 10-20% with industrial thinner, two or three coats should be applied for rusty surfaces .. Wait a minimum of three hours between coats. Spray, brush or roller and the two layers are applied. Application temperature should be between +5 and +30 oC. Thinner should be used for cleaning equipment.

Shelf life 2 years in unopened package



CLEAN THE
SURFACE



STIR



APPLY WITH
SPRAY



APPLY WITH
BRUSH



APPLY WITH
ROLLER



STORE IN TIGHTLY
CLOSED PACKAGES



Xn: Harmful



F: Flammable