

according to 1907/2006/EC, Article 31

Printing date 27.01.2015

Revision: 27.01.2015

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: BETEK PLUS
- · Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation Water Based interior paint
- Details of the supplier of the safety data sheet

Manufacturer/Supplier: Betek Boya ve Kimya Sanayi A.S.
G.O.S.B. Tembelova Alani 3200 Sokak No:3206 41400 Gebze/ Kocaeli/ Türkiye Tel: 00 90 262 678 30 00 Fax: 00 90 262 641 21 68

· Further information obtainable from: R&D Department

· Emergency telephone number: 00 90 262 678 3000

2 Hazards identification

· Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



Skin Sens. 1 H317 May cause an allergic skin reaction.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xi; Sensitising

- *R43:* May cause sensitisation by skin contact.
- · Information concerning particular hazards for human and environment:
- The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- · Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- *Labelling according to Regulation (EC) No 1272/2008* The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labelling:

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one [EC no. 220-239-6] (3:1) mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1)

• Hazard statements

H317 May cause an allergic skin reaction.

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Printing date 27.01.2015

Revision: 27.01.2015

Trade name: BETEK PLUS

(Contd. of page 1)

· Precautionary statements

- *P101* If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

- *P280 Wear protective gloves/protective clothing/eye protection/face protection.*
- *P321* Specific treatment (see on this label).
- *P363 Wash contaminated clothing before reuse.*
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- *P501* Dispose of contents/container in accordance with local/regional/national/international regulations.
- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

1332-58-7 Kaolin 10-25% 55965-84-9 mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl- 2Hisothiazol-3-one [EC no. 220-239-6] (3:1) mixture of: 5-chloro-2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1) $\leq 2.5\%$ \Rightarrow one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1) $\leq 2.5\%$ \Rightarrow one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1) $\leq 2.5\%$ \Rightarrow one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1) $\leq 2.5\%$ \Rightarrow one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1) $\leq 2.5\%$ \Rightarrow one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1) $\leq 2.5\%$ \Rightarrow one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1) $\leq 2.5\%$ \Rightarrow one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1) $\leq 2.5\%$ \Rightarrow one [EC no. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; \Leftrightarrow Skin Corr. 1B, H314; \Leftrightarrow Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	· Dangerous components:			
2Hisothiazol-3-one [EC no. 220-239-6] (3:1) mixture of: 5-chloro-2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1) ☐ T R23/24/25; ☐ C R34; Xi R43; NR50/53 Acute Tox 3 H301: Acute Tox 3 H311: Acute Tox 3 H331: Skin Corr 18	1332-58-7	Kaolin	10-25%	
		2Hisothiazol-3-one [EC no. 220-239-6] (3:1) mixture of: 5-chloro-2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1) T R23/24/25; C R34; Xi R43; N R50/53	<i>≤ 2.5%</i>	

• Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- Description of first aid measures
- After inhalation:
- Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- *After eye contact:* Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

5 Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 3)

GB

according to 1907/2006/EC, Article 31

Printing date 27.01.2015

Revision: 27.01.2015

Trade name: BETEK PLUS

(Contd. of page 2)

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.*
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

· Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.

8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:
- 1332-58-7 Kaolin
- WEL Long-term value: 2 mg/m³
- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- · Respiratory protection:
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 4)

according to 1907/2006/EC, Article 31

Printing date 27.01.2015

Trade name: BETEK PLUS

(Contd. of page 3) *Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.*

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling

Information on basic physical	and chemical properties	
General Information	1 1	
Appearance:		
Form:	Liquid	
Colour:	According to product specification	
Odour:	Characteristic	
pH-value at 20°C:	7-9	
Change in condition		
Melting point/Melting range:		
Boiling point/Boiling range:	100°C	
Flash point:	Not applicable.	
Self-igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Vapour pressure at 20°C:	23 hPa	
Density at 20°C:	$1.57 - 1.63 \ g/cm^3$	
Solubility in / Miscibility with		
water at 20°C:	- g/l	
Solvent content:		
VOC (EC)	20 g/l	
Solids content:	67 %	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 5)

GB

according to 1907/2006/EC, Article 31

Printing date 27.01.2015

Revision: 27.01.2015

Trade name: BETEK PLUS

(Contd. of page 4)

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- \cdot Sensitization: Sensitization possible through skin contact.
- Additional toxicological information: The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

• Sensitisation May cause sensitisation by skin contact.

12 Ecological information

- · Toxicity
- · Acquatic toxicity: No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

13 Disposal considerations

- Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- *Recommendation: Disposal must be made according to official regulations.*

14 Transport information

- · Land transport ADR/RID (cross-border) · ADR/RID class: -
- · Maritime transport IMDG:
- · IMDG Class:
- Marine pollutant: No
- Air transport ICAO-TI and IATA-DGR: • ICAO/IATA Class: -
- · UN "Model Regulation": -
- · Special precautions for user Not applicable.

(Contd. on page 6)

GB

according to 1907/2006/EC, Article 31

Printing date 27.01.2015

Revision: 27.01.2015

Trade name: BETEK PLUS

(Contd. of page 5)

GR

15 Regulatory information

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H301 Toxic if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H331 Toxic if inhaled.
- *H400 Very toxic to aquatic life.*
- *H410 Very toxic to aquatic life with long lasting effects.*

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

- R34 Causes burns.
- *R43 May cause sensitisation by skin contact.*
- *R50/53* Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

• Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

VOC: Volatile Organic Compounds (USA, EU)