

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Epomax 102 FUN, Epomax 203 PRO, Epomax 304 FACE

Version 2.0 SDB_GB

Revision Date 06.09.2020

Print Date 08.09.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Epomax 102 FUN, Epomax 203 PRO, Epomax 304 FACE

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/ Mixture : Casting Resin

1.3 Details of the supplier of the safety data sheet

Company : EPOKSIMAX Kısıklı Mahallesi, Reşatbey, No:30-A Üsküdar/İstanbul

Telephone : +90 216 599 11 85

Telefax : +90 216 599 11 85

E-mail address : info@epoksimax.com

1.4 Emergency telephone number

+90 533 597 19 90 (8-17 h)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Chronic aquatic toxicity, Category 2 H411: Toxic to aquatic life with long lasting effects.

Classification (67/548/EEC, 1999/45/EC)

Sensitising R43: May cause sensitisation by skin contact. Irritant R36/38: Irritating to eyes and skin.

Dangerous for the environment R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Epoksimax

Kısıklı Mh. Reşatbey, No: 30-A Üsküdar – İstanbul/TURKEY

Tel: +90216 599 11 85 Mail: info@epoksimax.com

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Epomax 102 FUN, Epomax 203 PRO, Epomax 304 FACE

Version 2.0 SDB_GB

Revision Date 06.09.2020

Print Date 08.09.2020

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Signal word	:	Warning	
Hazard statements	:	H315	Causes skin irritation.
		H317	May cause an allergic skin reaction.
		H319	Causes serious eye irritation.
		H411	Toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention:	
		P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
		P273	Avoid release to the environment.
		P280	Wear eye protection/ face protection.
		P280	Wear protective gloves.
		Response:	
		P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
	P337 + P313	If eye irritation persists: Get medical advice/ attention.	

Hazardous components which must be listed on the label:

reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight ≤ 700)

Epichlorohydrin-formaldehyde-phenol polymer number average molecular weight # 700

1,6-bis(2,3-epoxypropoxy)hexane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Modified epoxy resin

Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
reaction product: bisphenol-A- (epichlorhydrin) and epoxy resin (number	25068-38-6 01- 2119456619-26	Xi; R36/38 R43 N; R51-R53	Eye Irrit. 2; H319 Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2;	$\geq 30 - < 50$

Epoksimax

Kısıklı Mh. Reşatbey, No: 30-A Üsküdar – İstanbul/TURKEY

Tel: +90216 599 11 85 Mail: info@epoksimax.com

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Epomax 102 FUN, Epomax 203 PRO, Epomax 304 FACE

Version 2.0 SDB_GB

Revision Date 06.09.2020

Print Date 08.09.2020

average molecular weight <= 700)			H411	
Epichlorohydrin-formaldehyde-phenol polymer number average molecular weight # 700	9003-36-5	Xi; R36/38 R43 N; R51/53	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 30 - < 50
1,6-bis(2,3-epoxypropoxy)hexane	16096-31-4 240-260-4 01- 2119463471-41	Xi; R36/38 Xi; R43 N; R52/53	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 20 - < 25
propylene carbonate	108-32-7 203-572-1 01- 2119537232-48	Xi; R36	Eye Irrit. 2; H319	>= 1 - < 3

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Keep warm and in a quiet place.
Show this safety data sheet to the doctor in attendance.
Take off all contaminated clothing immediately.
- If inhaled : Move to fresh air.
Keep patient warm and at rest.
If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Wash off immediately with soap and plenty of water.
Do NOT use solvents or thinners.
If on clothes, remove clothes.
If skin irritation persists, call a physician.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If eye irritation persists, consult a specialist.
If easy to do, remove contact lens, if worn.
- If swallowed : Keep at rest.
Do not induce vomiting without medical advice.
Keep respiratory tract clear.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : irritant effects
Redness

Epoksimax

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Epomax 102 FUN, Epomax 203 PRO, Epomax 304 FACE

Version 2.0 SDB_GB

Revision Date 06.09.2020

Print Date 08.09.2020

sensitising effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam
Sand
Carbon dioxide (CO₂)
Water mist

Unsuitable extinguishing media : Water spray jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : The pressure in sealed containers can increase under the influence of heat.
Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Further information : In the event of fire and/or explosion do not breathe fumes.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Immediately evacuate personnel to safe areas.
Prevent fire extinguishing water from contaminating surface water or the ground water system.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.
Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Inform the responsible authorities in case of gas leakage, or of entry into waterways, soil or drains.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Epoksimax

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Epomax 102 FUN, Epomax 203 PRO, Epomax 304 FACE

Version 2.0 SDB_GB

Revision Date 06.09.2020

Print Date 08.09.2020

Try to prevent the material from entering drains or water courses.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Pick up and transfer to properly labelled containers.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms.
Avoid inhalation, ingestion and contact with skin and eyes.
Wear personal protective equipment.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Provide adequate ventilation. Wash hands and face before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labelled containers.

Advice on common storage : Keep away from oxidising agents, strongly acid or alkaline materials and amines.
Keep product and empty container away from heat and sources of ignition.
Keep away from food and drink.

Other data : Stable at normal ambient temperature and pressure.

7.3 Specific end use(s)

Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

Epoksimax

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Epomax 102 FUN, Epomax 203 PRO, Epomax 304 FACE

Version 2.0 SDB_GB

Revision Date 06.09.2020

Print Date 08.09.2020

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

reaction product: bisphenol-A- (epichlorhydrin) and epoxy resin (number average mo- lecular weight <= 700)	:	End Use: Workers Exposure routes: Skin contact Potential health effects: Acute systemic effects, Long-term sys- temic effects Value: 8,33 mg/kg End Use: Workers Exposure routes: Inhalation Potential health effects: Acute systemic effects, Long-term local effects Value: 12,25 mg/m3 End Use: Consumers Exposure routes: Skin contact Potential health effects: Acute systemic effects, Long-term sys- temic effects Value: 3,571 mg/kg End Use: Consumers Exposure routes: Ingestion Potential health effects: Acute systemic effects, Long-term sys- temic effects Value: 0,75 mg/kg
1,6-bis(2,3- epoxypropoxy)hexane	:	End Use: Workers Exposure routes: Skin contact Potential health effects: Long-term systemic effects Value: 2,8 mg/kg End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 4,9 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

reaction product: bisphenol-A- (epichlorhydrin) and epoxy resin (number average mo- lecular weight <= 700)	:	Fresh water Value: 0,006 mg/l Marine water Value: 0,0006 mg/l Intermittent releases Value: 0,018 mg/l Sewage treatment plant Value: 10 mg/l Fresh water sediment Value: 0,996 mg/kg Marine sediment Value: 0,0996 mg/kg Soil Value: 0,196 mg/kg
1,6-bis(2,3- epoxypropoxy)hexane	:	Sewage treatment plant Value: 10 mg/l

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Epomax 102 FUN, Epomax 203 PRO, Epomax 304 FACE

Version 2.0 SDB_GB

Revision Date 06.09.2020

Print Date 08.09.2020

Fresh water
Value: 0,0115 mg/l
Fresh water sediment
Value: 0,283 mg/kg
Marine water
Value: 0,00115 mg/l
Marine sediment
Value: 0,0283 mg/kg
Soil
Value: 0,223 mg/kg

8.2 Exposure controls

Engineering measures

Effective exhaust ventilation system
effective ventilation in all processing areas

Personal protective equipment

- Eye protection : Do not wear contact lenses.
Safety glasses with side-shields conforming to EN166
Ensure that eyewash stations and safety showers are close to the workstation location.
- Hand protection
Material : Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.
- Skin and body protection : Protective suit
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
In the case of vapour formation use a respirator with an approved filter.
Respirator with a vapour filter (EN 141)
Apply technical measures to comply with the occupational exposure limits.
This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation.
- Protective measures : Avoid contact with skin.
Wear suitable protective equipment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : light yellow
- Odour : slight
- Odour Threshold : not determined

Epoksimax

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Epomax 102 FUN, Epomax 203 PRO, Epomax 304 FACE

Version 2.0 SDB_GB

Revision Date 06.09.2020

Print Date 08.09.2020

pH	: not determined
Melting point/freezing point	: Not applicable
Boiling point/boiling range	: > 200 °C
Flash point	: 140 °C
Evaporation rate	: not determined
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Vapour pressure	: Not applicable
Relative vapour density	: not determined
Density	: 1,15 g/cm ³ (25 °C)
Bulk density	: not determined
Solubility(ies)	
Solubility in other solvents	: not determined
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: Not applicable
Thermal decomposition	: Method: No data available
Viscosity	
Viscosity, dynamic	: 500 - 600 mPa.s (25 °C)
Viscosity, kinematic	: not determined
Explosive properties	: Not applicable
Oxidizing properties	: Not applicable

Epoksimax

Kısıklı Mh. Reşatbey, No: 30-A Üsküdar – İstanbul/TURKEY

9.2 Other information

Tel: +90216 599 11 85 Mail: info@epoksimax.com

Surface tension : not determined

Sublimation point : Not applicable

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Epomax 102 FUN, Epomax 203 PRO, Epomax 304 FACE

Version 2.0 SDB_GB

Revision Date 06.09.2020

Print Date 08.09.2020

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with the following substances:
Bases
Strong oxidizing agents
Avoid amines.

10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

10.5 Incompatible materials

Materials to avoid : Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

Hazardous decomposition products : This product may release the following:
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Remarks: No data available

Components:

reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight \leq 700):

Acute oral toxicity : LD50 (Rat, female): > 2.000 mg/kg
Method: OECD Test Guideline 420
GLP: yes

Acute dermal toxicity : LD50 (Rat, male and female): > 2.000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

Skin corrosion/irritation

Product:

Remarks: No data available

Epoksimax

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Epomax 102 FUN, Epomax 203 PRO, Epomax 304 FACE

Version 2.0 SDB_GB

Revision Date 06.09.2020

Print Date 08.09.2020

Components:

reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight ≤ 700):

Species: Rabbit

Exposure time: 4 h

Method: OECD Test Guideline 404

Result: Skin irritation

GLP: yes

Serious eye damage/eye irritation

Product:

Remarks: No data available

Respiratory or skin sensitisation

Product:

Remarks: No data available

Components:

reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight ≤ 700):

Test Type: Mouse Local Lymph Node assay (LLNA)

Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

GLP: yes

Germ cell mutagenicity

Carcinogenicity

Reproductive toxicity

STOT - single exposure

Product:

Remarks: Not applicable

STOT - repeated exposure

Repeated dose toxicity

Product:

Remarks: No data available

Aspiration toxicity

Components:

reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight ≤ 700):

Epoksimax

Kısıklı Mh. Reşatbey, No: 30-A Üsküdar – İstanbul/TURKEY

Tel: +90216 599 11 85 Mail: info@epoksimax.com

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Epomax 102 FUN, Epomax 203 PRO, Epomax 304 FACE

Version 2.0 SDB_GB

Revision Date 06.09.2020

Print Date 08.09.2020

No aspiration toxicity classification

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Components:

reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight \leq 700):

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 1,7 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,3 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Method: OECD Test Guideline 211
GLP: yes

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight \leq 700):

Biodegradability : Result: Not readily biodegradable.
Method: OECD Test Guideline 301F
GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Epoksimax

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Epomax 102 FUN, Epomax 203 PRO, Epomax 304 FACE

Version 2.0 SDB_GB

Revision Date 06.09.2020

Print Date 08.09.2020

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : Remarks: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : In accordance with local and national regulations.
Container hazardous when empty.
Do not dispose of with domestic refuse.
Do not mix waste streams during collection.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14: Transport information

14.1 UN number

ADR/RID : UN 3082

IMDG : UN 3082

IATA : UN 3082

14.2 UN proper shipping name

ADR/RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(Epoxy resin)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(Epoxy resin)

IATA : Environmentally hazardous substance, liquid, n.o.s.
(Epoxy resin)

14.3 Transport hazard class(es)

ADR/RID : 9

Epoksimax

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Epomax 102 FUN, Epomax 203 PRO, Epomax 304 FACE

Version 2.0 SDB_GB

Revision Date 06.09.2020

Print Date 08.09.2020

IMDG : 9

IATA : 9

14.4 Packing group

ADR/RID

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : E

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA

Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964
Packing group : III
Labels : 9

14.5 Environmental hazards

ADR/RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso II - Directive 2003/105/EC amending Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances

Epoksimax

Quantity 1

Quantity 2

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Epomax 102 FUN, Epomax 203 PRO, Epomax 304 FACE

Version 2.0 SDB_GB

Revision Date 06.09.2020

Print Date 08.09.2020

9b	Dangerous for the environment	200 t	500 t
----	-------------------------------	-------	-------

15.2 Chemical Safety Assessment

Not applicable

SECTION 16: Other information**Full text of R-Phrases**

R36	: Irritating to eyes.
R36/38	: Irritating to eyes and skin.
R43	: May cause sensitisation by skin contact.
R51	: Toxic to aquatic organisms.
R51/53	: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53	: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R53	: May cause long-term adverse effects in the aquatic environment.

Full text of H-Statements

H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic	: Chronic aquatic toxicity
Eye Irrit.	: Eye irritation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Epoksimax

Kısıklı Mh. Reşatbey, No: 30-A Üsküdar – İstanbul/TURKEY

Tel: +90216 599 11 85 Mail: info@epoksimax.com