

Drywall Screw

Technogips Pro Drywall Screw, corrosion resistant, designed for fixing plasterboards to metal profiles with metal thickness up to 1mm.

The black coloured, phosphate coating guarantees the vast corrosion resistance of the element.

Available Sizes: 3.5 x 25, 35, 45, 55 mm; 4.2 x 70 mm



Standard Classification:

In compliance with EN 14566:2008 Type TN

Advantages:



✓ PH 2 screw bit included in every box




- ✓ The countersunk head of the screw fastens to the plasterboards with greater ease.
- ✓ Sharpened point and special thread ease the puncture of the metal profile

Technical Data:

Parameters:	Specification:
Reaction to fire	A 1
Corrosion resistance classification	48 hrs
Drilling time requirement	< 2 sec

Product	d _w x L _w	Вох	Boxes in a carton
Drywall Screw 3.5 x 25	3.5 x 25 mm	1000 pcs	16
Drywall Screw 3.5 x 35	3.5 x 35 mm	1000 pcs	12
Drywall Screw 3.5 x 45	3.5 x 45 mm	500 pcs	16
Drywall Screw 3.5 x 55	3.5 x 55 mm	500 pcs	12
Drywall Screw 4.2 x 70	4.2 x 70 mm	250 pcs	12

- Packaged in distinctive green Technogips Pro boxes with included PH2 screw bit
- ✓ Store in a dry, covered and ventilated area



Safety recommendations:

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.

Technogips Pro reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification.

June 2019©