



Interior Products Range

Acrylic Putty Interior

DESCRIPTION

ACRYLIC PUTTY INTERIOR is an acrylic emulsion based thin, surface smoothing putty used for background preparation of water based paints in interior walls.

APPLICATION AREA

Used as lower layer material in smoothing concrete and mineral plastered rough surfaces and cleaning the blistered portions and removing defects in old paint surfaces.

FEATURES

- High adherence and aspiration ability,
- Good spreading feature and easy to apply,
- Decreases paint consumption / wastage,
- Not much chalking during sanding process,
- Smooths the surface with maximum 2 coats,
- As it is water-based, it is harmless to human health and environment.

SURFACE PREPARATION

Clean all dirt, oil, blistered paint and dust off the application surface.

APPLICATION INSTRUCTIONS

- ACRYLIC PUTTY INTERIOR must be mixed thoroughly prior to application,
- ACRYLIC PUTTY INTERIOR must be applied with steel trowel, in one or two coats depending on the surface roughness,
- 24 hours after the application of the putty, the defects on the surface and trowel marks must be smoothed with sandpaper,
- The environment of application must be kept between +5°C to +35°C within 24 hours during and after the application.

DRYING TIME

Allow 4-6 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on surface smoothness, porosity and application methods, for a single coat application;

-1 lt covers 3,0 – 5,8 m² of surface,

-1 kg covers 1,7 – 3,3 m² of surface,

-The paint consumption for 1 m² area is 170-340 ml and 300-600 gr.

STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight; during and at a temperature between +5°C and +35°C.

DEKA BOYA SANAYİ ve TİC. A.Ş.



Interior Products Range

Acrylic Putty Interior

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)

May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

Product Technical Data Sheet No. IP.010.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standards of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88