

1.PRODUCT DESCRIPTION

SAN DECO ART PEARL is a pearl-textured, acrylic emulsion and water-based decorative paint designed for interior use.

2.APPLICATION AREA

After appropriate surface preparation, it can be used on walls, plaster, raw concrete, wood surfaces, and old painted surfaces in the interiors of spaces, along with decoprimer.

3.PRODUCT FEATURES

- SANDECO ART PEARL is designed for interior surfaces.
- SANDECO ART PEARL creates a pearl-textured appearance on the applied surface.
- SANDECO ART PEARL is easy to apply. It has a strong adherence feature and doesn't peel off from the wall.
- Thanks to its high vapor permeability, moisture on the surface disappears easily and the drying of the product is accelerated.
- It is water-based and does not harm human health or the environment.
- It gives a pleasant smell thanks to its special components.

4.SURFACE PREPARATION

After cleaning the surfaces to be painted from any dirt, oil, peeling paints, and dust, surface imperfections should be corrected using San Deco Acrylic Putty Interior, followed by priming with San Deco Decoprimer.

5.APPLICATION INSTRUCTIONS

5.1.Environment and Surface Conditions

- During and for 24 hours after the application, it should be ensured that the ambient temperature remains between +5°C minimum and +35°C maximum.
- During the application, it should be ensured that the ambient humidity is below 75%.
- Make sure the humidity value of the application surface is lower than 10%.

5.2.Application:

- The product is applied to the surface in a single layer using a wooden brush, without diluting. While the wall is wet, create the desired patterns using circular or straight motions.
- In cases where more than one batch is used in the same project, it is recommended that the batches be mixed in equal proportions to prevent batch-based differences.

6.DRYING TIME

At 23°C, the touch-drying time is 2-3 hours, and the complete drying time is 24-48 hours.

7.THEORETICAL CONSUMPTION

For single-layer applications depending on surface smoothness, absorbency, and application techniques;

- 1 liter covers an area of 2.1 – 2.7 m².
- 1 kilogram covers an area of 2.0 – 2.5 m².
- Paint consumption per 1 m² is 375 – 450 ml and 400 – 500 gr.

8.STORAGE AND SHELF LIFE

The product can be stored in the original sealed package between +5°C - +35°C temperature for 2 years. Make sure that the product is protected from direct sunlight.

9. HAZARD STATEMENTS AND EXPLANATIONS

Limit value EU (Directive 2004/42/EC)

Category A/I: Decorative effect coatings (water-based): 200 g/l (2010)

Maximum contained in SANDECO ART PEARL: 36 g/l VOC

H317 It can cause allergic skin reactions.

Precautionary Statements and Explanations

- P 261: Avoid breathing dust / fume / gas / mist / vapours / spray.
P 333 +P 313: If skin irritation or rash occurs: Get medical advice / attention.
P 362 +P 364: Take off contaminated clothing and wash it before reuse.
P 280: Wear protective gloves/protective clothing/eye protection/face protection.
P 321: Specific treatment (see on this label).
P 272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, please check the Safety Data Sheet (SDS) of the product.