

1. PRODUCT DESCRIPTION

ALFROYA is a decorative paint designed for interior use. It has a soft and silky matte texture that allows you to create both a classic and a modern atmosphere.

ALFROYA's effortless application not only simplifies the process but also empowers you to create distinctively enchanting spaces, making your walls truly exceptional.

2. APPLICATION AREA

After appropriate surface preparation, it can be used on walls, plaster, raw concrete, wood surfaces, and old painted surfaces in the interiors of spaces, along with Decoprimer.

3. PRODUCT FEATURES

ALFROYA creates a bright matte appearance thanks to its pure acrylic emulsion content and special reflective pearl pigments.

- Since the product is easy to apply, patterns and textures can be easily created.
- It provides high vapor permeability, allowing the release of water vapor and surface breathability.
- It is water-based and has no harm human health or the environment.
- It gives a pleasant smell thanks to its special components.

4. SURFACE PREPARATION

After cleaning the surfaces to be painted from any dirt, oil, peeling paints, and dust, surface imperfections should be corrected using SAN DECO ACRYLIC PUTTY INTERIOR, followed by priming with SAN DECO DECOPRIMER.

5. APPLICATION INSTRUCTIONS

5.1. Environment and Surface Conditions

- During and for 24 hours after the application, it should be ensured that the ambient temperature remains between +5°C minimum and +35°C maximum.
- During the application, it should be ensured that the ambient humidity is below 75%.
- Make sure the humidity value of the application surface is lower than 10%.

5.2. Application:

- ALFROYA is applied in two coats.
- It should be mixed homogeneously without diluting.
- In the first coat application, apply ALFROYA using a trowel.
- After the appropriate drying time, apply the second coat with a trowel again, and use the trowel to create patterns according to the desired effect.
- Different kinds of brushes can also be used to create different textures and patterns.
- Wait a minimum of 5-6 hours between coats.
- In cases where more than one batch is used in the same project, it is recommended that the batches be mixed in equal proportions to prevent batch-based differences.

6. DRYING TIME

At 23°C and 50% humidity, the touch-drying time is 5-6 hours, and the complete drying time is 24 hours.

7. THEORETICAL CONSUMPTION

For single-layer applications depending on surface smoothness, absorbency, and application techniques;

- 1 liter covers an area of 8.5 – 13 m².
- 1 kilogram covers an area of 7 – 11.0 m².
- Paint consumption per 1 m² is 75 – 115 ml and 90 – 140 gr.

8. STORAGE AND SHELF LIFE

The product can be stored in the original sealed package between +5°C - +35°C temperature for 2 years. Make sure that the product is protected from direct sunlight.

9. HAZARD STATEMENTS AND EXPLANATIONS

Limit value EU (Directive 2004/42/EC)

Category A/l: Decorative effect coatings (water-based): 200 g/l (2010)

Maximum contained in ALFROYA: 48 g/l VOC

H317 It can cause allergic skin reactions.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Precautionary Statements and Explanations

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P321: Specific treatment (see...on this label).

P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, please check the Safety Data Sheet (SDS) of the product.