

1.PRODUCT DESCRIPTION

DUCSIA is a decorative paint designed for interior use, aiming to create prestigious surfaces with its sparkling fine metallic effect, offering captivating classic and modern atmospheres.

Its structure enriched with special pigments adds aesthetics to spaces by providing strong brightness contrasts that change with the angle of incident light.

Its easy application allows for achieving various aesthetic effects, light plays and creating captivating reflections.

2.APPLICATION AREA

After appropriate surface preparation, it can be used on walls, plaster, raw concrete, wood surfaces, and old painted surfaces in the interiors of spaces, along decoprimer.

3.PRODUCT FEATURES

- DUCSIA creates a sparkling appearance thanks to its special pigments and fillers.
- Since the product is easy to apply, patterns and textures can be easily created.
- Both classic and modern designs can be created with DUCSIA.
- It provides high vapor permeability, allowing the release of water vapor and surface breathability.
- It is water-based and has no harm human health or the environment.
- It gives a pleasant smell thanks to its special components.

4.SURFACE PREPARATION

After cleaning the surfaces to be painted from any dirt, oil, peeling paints, and dust, surface imperfections should be corrected using SAN DECO ACRYLIC PUTTY INTERIOR, followed by priming with SAN DECO DECOPRIMER.

5.APPLICATION INSTRUCTIONS

5.1.Environment and Surface Conditions

- During and for 24 hours after the application, it should be ensured that the ambient temperature remains between +5°C minimum and +35°C maximum.
- During the application, it should be ensured that the ambient humidity is below 75%.
- Make sure the humidity value of the application surface is lower than 10%.

5.2.Application:

- DUCSIA is applied in a single coat.
- It should be mixed homogeneously without diluting.
- It should be applied using a brush
- DUCSIA is applied unequally to the surface using a brush, and the fine particles in the product are dispersed on the surface to create fine patterned textures. After partial drying, the fine particles on the surface are unequally spreaded according to the desired appearance using a brush. You can create your own application methods that suit your taste.
- In cases where more than one batch is used in the same project, it is recommended that the batches be mixed in equal proportions to prevent batch-based differences.

6.DRYING TIME

At 23°C and 50% humidity, the touch-drying time is 4-6 hours, and the complete drying time is 24 hours.

7. THEORETICAL CONSUMPTION

For single-layer applications depending on surface smoothness, absorbency, and application techniques;

- 1 liter covers an area of 9.5 – 14.5 m².
- 1 kilogram covers an area of 10 – 15 m².
- Paint consumption per 1 m² is 95 – 145 ml and 100 – 150 gr.

8.STORAGE AND SHELF LIFE

The product can be stored in the original sealed package between +5°C - +35°C temperature for 2 years. Make sure that the product is protected from direct sunlight.

9. HAZARD STATEMENTS AND EXPLANATIONS

Limit value EU (Directive 2004/42/EC).

Category A/l: Decorative effect coatings (water-based): 200 g/l (2010).

DUCSIA contains a maximum of 52 g/l VOC.

H317 It can cause allergic skin reactions.

Precautionary Statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment (see...on this label).

P272 Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, please check the Safety Data Sheet (SDS) of the product.