

## 1. PRODUCT DESCRIPTION

PATINALUSSO is developed to be applied on the acrylic and lime-based products. It has a semi-pearlescent effect and creates a shiny appearance on the applied surface.

PATINALUSSO, which gives the surfaces a decorative touch, has an easy application and is suitable for manual or mechanical polishing.

## 2. APPLICATION AREA

It is applied to the surfaces of acrylic and lime-based decorative coatings on the interior spaces.

## 3. PRODUCT FEATURES

- PATINALUSSO, increases the brightness of the applied surfaces.
- It creates an extra soft texture on surfaces thanks to its special wax structure in its content.
- It is easy to apply.
- It creates shiny surfaces with silver and gold finishes.
- It can be easily polished with a dry and clean cloth or a polishing machine.
- It is water-based and has no harm human health or the environment.
- It gives a pleasant smell thanks to its special components.

## 4. SURFACE PREPARATION

After cleaning all kinds of dirt, grease, oil, and dust, from the surface, you can start the application.

## 5. APPLICATION INSTRUCTIONS

### 5.1. Environment and surface conditions.

During and for 24 hours after the application, it should be ensured that the ambient temperature remains between +5°C minimum and +35°C maximum.

During the application, it should be ensured that the ambient humidity is below 75%.

Make sure the humidity value of the application surface is lower than 10%.

### 5.2. Application:

PATINALUSSO is applied as a thin layer with a steel trowel, in a single coat.

It should be mixed homogeneously without diluting.

After drying, PATINALUSSO is polished with a clean dry cloth or a polishing machine.

After the appropriate drying time, the second coat is applied with a trowel, and the desired pattern is created using a trowel.

If desired, application can also be made using a brush for different textures and patterns.

## 6. DRYING TIME

At 23°C and 50% humidity, the touch-drying time is 1-2 hours, and the complete drying time is 24 hours.

## 7. THEORETICAL CONSUMPTION

For single-layer applications depending on surface smoothness, absorbency, and application techniques;

- 1 lt covers an area of 16 – 20 m<sup>2</sup>,
- 1 kg covers an area of 15 – 19 m<sup>2</sup>.
- Paint consumption per 1 m<sup>2</sup> is 50 - 60 ml and 52- 62 gr.

## 8. STORAGE AND SHELF LIFE

The product can be stored in the original sealed package between +5°C - +35°C temperature for 2 years.

## 9. HAZARD STATEMENTS

PATINALUSSO is not covered by EU Directive 2004/42/EC.

PATINALUSSO content maximum: 70 g/l VOC

**H317** May cause an allergic skin reaction.

### Precautionary Statements

**P261:** Avoid breathing dust/fume/gas/mist/vapours/spray.

**P333+P313:** If skin irritation or rash occurs: Get medical advice/attention.

**P362+P364:** Take off contaminated clothing and wash it before reuse.

**P280:** Wear protective gloves/protective clothing/eye protection/face protection.

**P321:** Specific treatment (see...on this label).

**P272:** Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, please check the Safety Data Sheet (SDS) of the product.

### DEKA BOYA SANAYİ ve TİC. A.Ş.