

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **BN100.10.1000**
Product name: **CELLULOSIC PAINT MATT WHITE**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Wood coatings**

1.3. Details of the supplier of the safety data sheet

Name: **KAYALAR KIMYA SAN.VE TIC.A.S.**
Full address: **Tepeören Kimya Sanayicileri O.S.B, Tem Yanyol F1 Blok**
District and Country: **34956 Istanbul (Tuzla) TURKEY**
Tel.: **+90 216-5930727**
Fax: **+90 216-5931850**

e-mail address of the competent person responsible for the Safety Data Sheet: **help@kayalarkimya.com.tr**

Supplier: **Kayalar Kimya San. Ve Tic. A.S.**

1.4. Emergency telephone number

For urgent inquiries refer to: **HEADQUARTERS: KAYALAR KIMYA SAN.VE TIC. A.Ş. TURKEY TEL: +90 216-5930727**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Reproductive toxicity, category 2	H361d	Suspected of damaging the unborn child.
Acute toxicity, category 4	H302	Harmful if swallowed.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, category 2	H371	May cause damage to organs.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



SECTION 2. Hazards identification ... / >>

Signal words: Danger

Hazard statements:

H225 Highly flammable liquid and vapour.
H361d Suspected of damaging the unborn child.
H302 Harmful if swallowed.
H373 May cause damage to organs through prolonged or repeated exposure.
H319 Causes serious eye irritation.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H371 May cause damage to organs.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P370+P378 In case of fire: use foam, fire-extinguishing powder, carbonsioxide to extinguish.
P261 Avoid breathing dust / fume / gas / mist / vapours / spray.
P201 Obtain special instructions before use.
P233 Keep container tightly closed.

Contains: TOLUENE
METHANOL
ACETONE
N-BUTYL ACETATE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients
3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
TOLUENE		
INDEX 601-021-00-3	$15 \leq x < 25$	Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 3 H412
EC 203-625-9		
CAS 108-88-3		
REACH Reg. 01-2119471310-51-XXXX		
TITANIUM DIOXIDE [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 μm]		
INDEX 022-006-00-2	$10 \leq x < 20$	Carc. 2 H351, Classification note according to Annex VI to the CLP Regulation: 10, V, W
EC 236-675-5		
CAS 13463-67-7		
REACH Reg. 01-2119489379-17-XXXX		
ACETONE		
INDEX 606-001-00-8	$10 \leq x < 20$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC 200-662-2		
CAS 67-64-1		
REACH Reg. 01-2119471330-49-XXXX		
NITROCELLULOSE		
INDEX	$5 \leq x < 10$	Flam. Liq. 2 H225
EC		
CAS 9004-70-0		
METHANOL		
INDEX 603-001-00-X	$5 \leq x < 10$	Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT SE 1 H370

SECTION 3. Composition/information on ingredients ... / >>EC 200-659-6
CAS 67-56-1**STOT SE 2 H371: ≥ 3%**
STA Oral: 100 mg/kg, STA Dermal: 300 mg/kg, STA Inhalation vapours: 3 mg/l**PROPAN-2-OL**INDEX 603-117-00-0 3 ≤ x < 5
EC 200-661-7
CAS 67-63-0
REACH Reg. 01-2119457558-25-XXXX**Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336****N-BUTYL ACETATE**INDEX 607-025-00-1 3 ≤ x < 5
EC 204-658-1
CAS 123-86-4
REACH Reg. 01-2119485493-29-XXXX**Flam. Liq. 3 H226, STOT SE 3 H336, EUH066****ISO-BUTANOL**INDEX 603-108-00-1 1 ≤ x < 3
EC 201-148-0
CAS 78-83-1
REACH Reg. 01-2119484609-23-XXXX**Flam. Liq. 3 H226, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, STOT SE 3 H336****2-BUTOXYETHANOL**INDEX 603-014-00-0 0,5 ≤ x < 1
EC 203-905-0
CAS 111-76-2
REACH Reg. 01-2119475108-36-XXXX**Acute Tox. 3 H331, Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315**
LD50 Oral: 1200 mg/kg, LC50 Inhalation vapours: 3 mg/l/4h

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
ESP EST	España Eesti	Límites de exposición profesional para agentes químicos en España 2021 Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskonna keemiliste ohutegurite piirnormid [RT I, 17.10.2019, 1 - jõust. 17.01.2020]
ITA PRT	Italia Portugal	Decreto Legislativo 9 Aprile 2008, n.81 Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy

SECTION 8. Exposure controls/personal protection ... / >>

ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022

ISO-BUTANOL
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	154	50			
TLV	EST	150	50			
NDS/NDSch	POL	100		200		SKIN
TLV	ROU	100	33	200	66	
WEL	GBR	154	50	231	75	
TLV-ACGIH		152	50			

TOLUENE
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	192	50	384	100	SKIN
VLA	ESP	192	50	384	100	SKIN
TLV	EST	192	50	384	100	SKIN
VLEP	ITA	192	50			SKIN
VLE	PRT	192	50	384	100	SKIN
NDS/NDSch	POL	100		200		SKIN
TLV	ROU	192	50	384	100	SKIN
ESD	TUR	192	50	384	100	SKIN
WEL	GBR	191	50	384	100	SKIN
OEL	EU	192	50	384	100	SKIN
TLV-ACGIH			20			

METHANOL
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	260	200			SKIN
VLA	ESP	266	200			SKIN
TLV	EST	250	200	350	250	SKIN
VLEP	ITA	260	200			SKIN
VLE	PRT	260	200			SKIN
NDS/NDSch	POL	100		300		SKIN
TLV	ROU	260	200			SKIN
ESD	TUR	260	200			SKIN
WEL	GBR	266	200	333	250	SKIN
OEL	EU	260	200			
TLV-ACGIH		262	200	328	250	SKIN

SECTION 8. Exposure controls/personal protection ... / >>
2-BUTOXYETHANOL
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	98	20	246	50	SKIN
VLA	ESP	98	20	245	50	SKIN
TLV	EST	98	20	246	50	
VLEP	ITA	98	20	246	50	SKIN
VLE	PRT	98	20	246	50	SKIN
NDS/NDSch	POL	98		200		SKIN
TLV	ROU	98	20	246	50	SKIN
ESD	TUR	98	20	246	50	SKIN
WEL	GBR	123	25	246	50	SKIN
OEL	EU	98	20	246	50	SKIN
TLV-ACGIH		97	20			

PROPAN-2-OL
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	980		1225		
VLA	ESP	500	200	1000	400	
TLV	EST	350	150	600	250	
NDS/NDSch	POL	900		1200		SKIN
TLV	ROU	200	81	500	203	
WEL	GBR	999	400	1250	500	
TLV-ACGIH		492	200	983	400	

ACETONE
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	600		1400		
VLA	ESP	1210	500			
TLV	EST	1210	500			
VLEP	ITA	1210	500			
VLE	PRT	1210	500			
NDS/NDSch	POL	600		1800		
TLV	ROU	1210	500			
ESD	TUR	1210	500			
WEL	GBR	1210	500	3620	1500	
OEL	EU	1210	500			
TLV-ACGIH			250		500	

N-BUTYL ACETATE
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	710		950		
VLA	ESP	241	50	724	150	
TLV	EST	500	100	700	150	
VLEP	ITA	241	50	723	150	
VLE	PRT	241	50	723	150	
NDS/NDSch	POL	240		720		
TLV	ROU	241	50	723	150	
WEL	GBR	724	150	966	200	
OEL	EU	241	50	723	150	
TLV-ACGIH			50		150	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

SECTION 8. Exposure controls/personal protection ... / >>

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	white	
Odour	not available	
Melting point / freezing point	not available	
Initial boiling point	> 35 °C	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	< 23 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	
Kinematic viscosity	>20,5 mm ² /sec (40°C)	
Solubility	soluble in organic solvents	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1,12 ± 0,03 Kg/l	
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2004/42/EC) : 50,67 % - 567,48 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

TOLUENE

Avoid exposure to: light.

2-BUTOXYETHANOL

Decomposes under the effect of heat.

ACETONE

Decomposes under the effect of heat.

N-BUTYL ACETATE

Decomposes on contact with: water.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

TOLUENE

Risk of explosion on contact with: fuming sulphuric acid,nitric acid,silver perchlorate,nitrogen dioxide,non-metal halogenates,acetic acid,organic nitrocompounds.May form explosive mixtures with: air.May react dangerously with: strong oxidising agents,strong acids,sulphur.

2-BUTOXYETHANOL

May react dangerously with: aluminium,oxidising agents.Forms peroxides with: air.

ACETONE

Risk of explosion on contact with: bromine trifluoride,fluorine dioxide,hydrogen peroxide,nitrosyl chloride,2-methyl-1,3 butadiene,nitromethane,nitrosyl perchlorate.May react dangerously with: potassium tert-butoxide,alkaline hydroxides,bromine,bromoform,isoprene,sodium,sulphur dioxide,chromium trioxide,chromyl chloride,nitric acid,chloroform,peroxymonosulphuric acid,phosphoryl oxychloride,chromosulphuric acid,fluorine,strong oxidising agents,strong reducing agents.Develops flammable gas on contact with: nitrosyl perchlorate.

N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents.May react dangerously with: alkaline hydroxides,potassium tert-butoxide.Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

2-BUTOXYETHANOL

Avoid exposure to: sources of heat,naked flames.

ACETONE

Avoid exposure to: sources of heat,naked flames.

N-BUTYL ACETATE

Avoid exposure to: moisture,sources of heat,naked flames.

10.5. Incompatible materials

ACETONE

Incompatible with: acids,oxidising substances.

N-BUTYL ACETATE

Incompatible with: water,nitrates,strong oxidants,acids,alkalis,zinc.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

2-BUTOXYETHANOL

May develop: hydrogen.

ACETONE

May develop: ketenes,irritant substances.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

SECTION 11. Toxicological information ... / >>**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

TOLUENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

METHANOL

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

N-BUTYL ACETATE

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**TOLUENE**

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

METHANOL

The minimum lethal dose for humans by ingestion is considered to be in the range from 300 to 1000 mg/kg. Ingestion of 4-10 ml of the substance may cause permanent blindness in adult humans (IPCS).

N-BUTYL ACETATE

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

Interactive effects**TOLUENE**

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

N-BUTYL ACETATE

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	1000,00 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg

TITANIUM DIOXIDE [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

LD50 (Oral): > 10000 mg/kg Rat

ISO-BUTANOL

LD50 (Dermal): 2460 mg/kg Rabbit

LD50 (Oral): 2460 mg/kg Rat

LC50 (Inhalation vapours): 19,2 mg/l/4h Rat

TOLUENE

LD50 (Dermal): 12124 mg/kg Rabbit

LD50 (Oral): 5580 mg/kg Rat

LC50 (Inhalation vapours): 28,1 mg/l/4h Rat

SECTION 11. Toxicological information ... / >>

METHANOL	
STA (Dermal):	300 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
STA (Oral):	100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LC50 (Inhalation vapours):	> 87,6 mg/l/4h Rat
STA (Inhalation vapours):	3 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
2-BUTOXYETHANOL	
LD50 (Oral):	1200 mg/kg Guinea pig
LC50 (Inhalation vapours):	3 mg/l/4h Rat
PROPAN-2-OL	
LD50 (Dermal):	12800 mg/kg Rat
LD50 (Oral):	4710 mg/kg Rat
LC50 (Inhalation vapours):	72,6 mg/l/4h Rat
N-BUTYL ACETATE	
LD50 (Dermal):	> 5000 mg/kg Rabbit
LD50 (Oral):	> 6400 mg/kg Rat
LC50 (Inhalation vapours):	21,1 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

TITANIUM DIOXIDE [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1% or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

TOLUENE

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Suspected of damaging the unborn child

STOT - SINGLE EXPOSUREMay cause damage to organs
May cause drowsiness or dizziness**STOT - REPEATED EXPOSURE**

May cause damage to organs

ASPIRATION HAZARDDoes not meet the classification criteria for this hazard class Viscosity: >20,5 mm²/sec (40°C)

SECTION 11. Toxicological information ... / >>**11.2. Information on other hazards**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Information not available

12.2. Persistence and degradability

TITANIUM DIOXIDE [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

Solubility in water < 0,001 mg/l

Degradability: information not available

ISO-BUTANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

TOLUENE

Solubility in water 100 - 1000 mg/l

Rapidly degradable

METHANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

2-BUTOXYETHANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

PROPAN-2-OL

Rapidly degradable

ACETONE

Rapidly degradable

N-BUTYL ACETATE

Solubility in water 1000 - 10000 mg/l

12.3. Bioaccumulative potential

ISO-BUTANOL

Partition coefficient: n-octanol/water 1

TOLUENE

Partition coefficient: n-octanol/water 2,73

BCF 90

METHANOL

Partition coefficient: n-octanol/water -0,77

BCF 0,2

2-BUTOXYETHANOL

Partition coefficient: n-octanol/water 0,81

PROPAN-2-OL

Partition coefficient: n-octanol/water 0,05

ACETONE

Partition coefficient: n-octanol/water -0,23

BCF 3

SECTION 12. Ecological information ... / >>

N-BUTYL ACETATE
Partition coefficient: n-octanol/water 2,3
BCF 15,3

12.4. Mobility in soil

ISO-BUTANOL
Partition coefficient: soil/water 0,31

N-BUTYL ACETATE
Partition coefficient: soil/water < 3

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
Waste transportation may be subject to ADR restrictions.
CONTAMINATED PACKAGING
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number or ID number**

ADR / RID, IMDG, IATA: 1263

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL
IMDG: PAINT or PAINT RELATED MATERIAL
IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3

**14.4. Packing group**

ADR / RID, IMDG, IATA: II

SECTION 14. Transport information ... / >>**14.5. Environmental hazards**

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 33	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
	Special provision: 163, 367, 640D, 650		
IMDG:	EMS: F-E, S-E	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 60 L	Packaging instructions: 364
	Passengers:	Maximum quantity: 5 L	Packaging instructions: 353
	Special provision:	A3, A72, A192	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Point 69

Point 48

METHANOL

TOLUENE

REACH Reg.: 01-2119471310-51-XXXX

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Regulated explosives precursor

The acquisition, introduction, possession or use of that regulated explosives precursor by members of the general public is subject to reporting obligations as set out in Article 9.

All suspicious transactions and significant disappearances and thefts must be reported to the relevant national contact point.

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Carc. 2	Carcinogenicity, category 2
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
STOT SE 1	Specific target organ toxicity - single exposure, category 1
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
STOT SE 2	Specific target organ toxicity - single exposure, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H371	May cause damage to organs.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit

SECTION 16. Other information ... / >>

- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 10 / 11 / 12 / 14 / 15 / 16.



Sofia
6 "Andrey Germanov" str.
mobile: 089 666 3042 / 089 468 3880

Sofia, "Ovcha Kupel 1" quarter
33 "Promishlena" str., 429 bl., store 18,
mobile: 089 666 9071

Plovdiv
176 "Brezovsko shose" str.
mobile: 089 544 7503 / 089 666 3044

Varna
25 "Usta Kolyu Ficheto" str.
mobile: 089 666 9079 / 089 466 9023

Shumen, "Dobrudzhanski" quarter
Ind. zone, "Stroykomplekt" site
mobile: 089 455 1685 / 089 666 3043

Kardzhali
1 "Klokotnitsa" str.
mobile: 089 575 0749 / 089 666 3057

Troyan
49 "Makedoniya" str.
mobile: 089 666 9079 / 089 673 4489

Haskovo, 5 "Okolovrasten pat" str.
South Industrial zone
mobile: 089 666 3051 / 089 241 2833