

**REAL SLF 116 B - EPOXY SELF LEVELING B COMPONENT** 

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 1 / 13

Replaced revision:1 (Dated 12/05/2025)

# **Safety Data Sheet**

According to Annex II to REACH - Regulation (EU) 2020/878

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: REAL SLF 116 B

Product name EPOXY SELF LEVELING B COMPONENT

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use not available

# 1.3. Details of the supplier of the safety data sheet

Name REAL YAPI KIMYASALLARI A.S.

Full address Muratçeşme Mah. Sultan Murat Caddesi Efe 2 Sok. No:5

District and Country Büyükçekmece / İstanbul

Türkiye

Tel. +90(212)596 11 01

1.4. Emergency telephone number

For urgent inquiries refer to +90530 905 7125

# **SECTION 2. Hazards identification**

## 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Reproductive toxicity, category 16	H300F	May damage tertility.
Serious eye damage, category 1	H318	Causes serious eye damage.
Specific target organ toxicity - single exposure,	H335	May cause respiratory irritation.
category 3		
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, acute toxicity,	H400	Very toxic to aquatic life.
category 1		
Hazardous to the aquatic environment, chronic	H410	Very toxic to aquatic life with long lasting effects.
toxicity, category 1		

H360E

May damage fortility

### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger



**REAL SLF 116 B - EPOXY SELF LEVELING B COMPONENT** 

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 2 / 13

Replaced revision:1 (Dated 12/05/2025)

### **SECTION 2. Hazards identification** .../>>

Hazard statements:

H360FMay damage fertility.H318Causes serious eye damage.H335May cause respiratory irritation.H317May cause an allergic skin reaction.

**H410** Very toxic to aquatic life with long lasting effects.

Restricted to professional users.

Precautionary statements:

**P201** Obtain special instructions before use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do Continue rinsing

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

P310 Immediately call a POISON CENTER / doctor / . . .

**P273** Avoid release to the environment.

P391 Collect spillage.

Contains: 4,4'-ISOPROPYLIDENEDIPHENOL

The product is classified both in acute and long-term aquatic hazard categories: it is possible to use only hazard statement H410 on the label

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product contains substances with endocrine disrupting properties in concentration ≥ 0,1%: 4,4'-ISOPROPYLIDENEDIPHENOL

## **SECTION 3. Composition/information on ingredients**

### 3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

4,4'-ISOPROPYLIDENEDIPHENOL

INDEX 604-030-00-0 30 ≤ x < 32,5 Repr. 1B H360F, Eye Dam. 1 H318, STOT SE 3 H335, Skin Sens. 1 H317,

Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=10

EC 201-245-8 CAS 80-05-7

2-[2-[4-(1-feniletil)fenoksi]etoksi]etanol

INDEX  $9 \le x < 10.5$  Aquatic Chronic 2 H411

EC 608-713-4 CAS 32171-27-0

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms



**REAL SLF 116 B - EPOXY SELF LEVELING B COMPONENT** 

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 3 / 13

Replaced revision:1 (Dated 12/05/2025)

# **SECTION 4. First aid measures** .../>>

(coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

#### Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

## 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

# 4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER / doctor / . . .

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

# **SECTION 5. Firefighting measures**

## 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

# 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

# 5.3. Advice for firefighters

## **GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).



**REAL SLF 116 B - EPOXY SELF LEVELING B COMPONENT** 

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 4 / 13

Replaced revision:1 (Dated 12/05/2025)

## **SECTION 6. Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

# 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage**

## 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

## 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

# **SECTION 8. Exposure controls/personal protection**

#### 8.1. Control parameters

Regulatory references:

BGR България НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА

РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА

ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.28 от 2 Април 2024г.)

GBR United Kingdom EH40/2005 Workplace exposure limits (Fourth Edition 2020)

EU OEL EU Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130;

Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164;

Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.



**REAL SLF 116 B - EPOXY SELF LEVELING B COMPONENT** 

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 5 / 13

Replaced revision:1 (Dated 12/05/2025)

## SECTION 8. Exposure controls/personal protection .../>>

4.4'-ISOPROPYLIDENEDIPHENOL								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15n	nin	Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	2				INHAL		
WEL	GBR	2						
OEL	EU	2				INHAL		

#### Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

## 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

# **EYE PROTECTION**

Wear airtight protective goggles (see standard EN ISO 16321).

### RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

# **ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Information

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

# **SECTION 9. Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

**Properties** Value not available Appearance Colour transparent Odour amine Melting point / freezing point not available Initial boiling point not available °C Boiling range 230 Flammability not available Lower explosive limit not available Upper explosive limit not available

@ EPY 11.9.0 - SDS 1004.14

**REAL SLF 116 B - EPOXY SELF LEVELING B COMPONENT** 

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 6 / 13

Replaced revision:1 (Dated 12/05/2025)

## SECTION 9. Physical and chemical properties .../>

Flash point 60 °C Auto-ignition temperature not available not available Decomposition temperature not available Kinematic viscosity insoluble Solubility Partition coefficient: n-octanol/water not available not available Vapour pressure Density and/or relative density not available Relative vapour density Particle characteristics not applicable

# 9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

# **SECTION 10. Stability and reactivity**

# 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

## 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

## 10.5. Incompatible materials

Information not available

# 10.6. Hazardous decomposition products

Information not available

# **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008



**REAL SLF 116 B - EPOXY SELF LEVELING B COMPONENT** 

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 7 / 13

Replaced revision:1 (Dated 12/05/2025)

# **SECTION 11. Toxicological information** .../>>

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

## **ACUTE TOXICITY**

ATE (Inhalation) of the mixture:

ATE (Oral) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

Not classified (no significant component)

4,4'-ISOPROPYLIDENEDIPHENOL

LD50 (Dermal): 3000 mg/kg Rabbit

LD50 (Oral): 5000 mg/kg

## SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

#### **SERIOUS EYE DAMAGE / IRRITATION**

Causes serious eye damage

## RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

#### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

## **CARCINOGENICITY**

Does not meet the classification criteria for this hazard class

# REPRODUCTIVE TOXICITY

May damage fertility

# **STOT - SINGLE EXPOSURE**

May cause respiratory irritation

# **STOT - REPEATED EXPOSURE**



**REAL SLF 116 B - EPOXY SELF LEVELING B COMPONENT** 

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 8 / 13

Replaced revision:1 (Dated 12/05/2025)

# **SECTION 11. Toxicological information** .../>>

Does not meet the classification criteria for this hazard class

## **ASPIRATION HAZARD**

Does not meet the classification criteria for this hazard class

#### 11.2. Information on other hazards

Based on the available data, the product contains the following endocrine disruptors in concentrations of 0.1% or greater by weight that may have endocrine disrupting effects on humans and cause adverse effects on the exposed individual or his or her progeny:

4,4'-ISOPROPYLIDENEDIPHENOL

# **SECTION 12. Ecological information**

This product is dangerous for the environment and highly toxic for aquatic organisms. In the long term, it has negative effects on the aquatic environment.

# 12.1. Toxicity

4,4'-ISOPROPYLIDENEDIPHENOL

LC50 - for Fish 9,4 mg/l/96h Menidia menidia EC50 - for Crustacea 10,2 mg/l/48h Daphnia magna

#### 12.2. Persistence and degradability

4,4'-ISOPROPYLIDENEDIPHENOL

Solubility in water 301 mg/l

Rapidly degradable

## 12.3. Bioaccumulative potential

4,4'-ISOPROPYLIDENEDIPHENOL

Partition coefficient: n-octanol/water 3,4

#### 12.4. Mobility in soil

4.4'-ISOPROPYLIDENEDIPHENOL

Partition coefficient: soil/water 2,95

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

### 12.6. Endocrine disrupting properties

Based on the available data, the product contains the following endocrine disruptors in concentrations of 0.1% or greater by weight that may have endocrine disrupting effects on the environment and on animal species causing adverse effects on the exposed organisms or on their progeny: 4,4'-ISOPROPYLIDENEDIPHENOL

## 12.7. Other adverse effects

Information not available



**REAL SLF 116 B - EPOXY SELF LEVELING B COMPONENT** 

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025

#### Replaced revision:1 (Dated 12/05/2025)

# **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information**

#### 14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 3082

ADR / RID: In accordance with Special Provision 375, this product, when is packed in receptacles of a

capacity ≤ 5Kg or 5L, is not submitted to ADR provisions.

IMDG: In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in

receptacles of a capacity ≤ 5Kg or 5L, is not submitted to IMDG Code provisions.

In accordance with SP A197, this product, when is packed in receptacles of a capacity ≤ 5Kg IATA:

or 5L, is not submitted to IATA dangerous goods regulations.

## 14.2. UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ADR / RID:

(4,4'-ISOPROPYLIDENEDIPHENOL; 2-[2-[4-(1-feniletil)fenoksi]etoksi]etanol)

IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(4,4'-ISOPROPYLIDENEDIPHENOL; 2-[2-[4-(1-feniletil)fenoksi]etoksi]etanol)

IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(4,4'-ISOPROPYLIDENEDIPHENOL; 2-[2-[4-(1-feniletil)fenoksi]etoksi]etanol)



**REAL SLF 116 B - EPOXY SELF LEVELING B COMPONENT** 

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 10 / 13

Replaced revision:1 (Dated 12/05/2025)

# **SECTION 14. Transport information** .../>>

# 14.3. Transport hazard class(es)

ADR / RID: Class: 9 Label: 9

IMDG: Class: 9 Label: 9

IATA: Class: 9 Label: 9



## 14.4. Packing group

ADR / RID, IMDG, IATA: III

#### 14.5. Environmental hazards

ADR / RID: Environmentally Hazardous

IMDG: Marine Pollutant

IATA: Environmentally Hazardous



# 14.6. Special precautions for user

ADR / RID: HIN - Kemler: 90 Limited Quantities: 5 lt Tunnel restriction code: (-)

Special provision: 274, 335, 375, 601, 650

IMDG: EMS: F-A, S-F Limited Quantities: 5 lt

IATA: Cargo: Maximum quantity: 450 L

Passengers: Maximum quantity: 450 L

Special provision: A97, A158, A197, A215

Packaging instructions: 964 Packaging instructions: 964

# 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

# **SECTION 15. Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: E1

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

**Product** 

Point 3
Contained substance

Point 30-66-75 4,4'-ISOPROPYLIDENEDIPHENOL



**REAL SLF 116 B - EPOXY SELF LEVELING B COMPONENT** 

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 11 / 13

Replaced revision:1 (Dated 12/05/2025)

# **SECTION 15. Regulatory information** .../>>

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable

Substances in Candidate List (Art. 59 REACH) 4,4'-ISOPROPYLIDENEDIPHENOL

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

## Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

## 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

## **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

**Repr. 1B** Reproductive toxicity, category 1B **Eye Dam. 1** Serious eye damage, category 1

STOT SE 3 Specific target organ toxicity - single exposure, category 3

**Skin Sens. 1** Skin sensitization, category 1

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2

**H360F** May damage fertility.

H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H317 May cause an allergic skin reaction.

**H400** Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008



**REAL SLF 116 B - EPOXY SELF LEVELING B COMPONENT** 

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 12 / 13

Replaced revision:1 (Dated 12/05/2025)

## **SECTION 16. Other information** .../>>

- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

## **GENERAL BIBLIOGRAPHY**

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
- 25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)



**REAL SLF 116 B - EPOXY SELF LEVELING B COMPONENT** 

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 13 / 13

Replaced revision:1 (Dated 12/05/2025)

# **SECTION 16. Other information** .../>>

- 26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
- 27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

#### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

#### Changes to previous review:

The following sections were modified:

01.