

REAL GRN 785 A - TWO COMPONENT, EPOXY COATING FLOOR COATING IN RAL CATALOG COLORS - A COMPONENT

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 1 / 12

Replaced revision:1 (Dated 12/05/2025)

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: REAL GRN 785 A

Product name TWO COMPONENT, EPOXY COATING FLOOR COATING IN RAL

CATALOG COLORS - A COMPONENT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use not available

1.3. Details of the supplier of the safety data sheet

Name REAL YAPI KIMYASALLARI A.S.

Full address Muratçeşme Mah. Sultan Murat Caddesi Efe 2 Sok. No:5

District and Country

Büyükçekmece / İstanbul

Türkiye

Tel. +90(212)596 11 01

1.4. Emergency telephone number

For urgent inquiries refer to +90530 905 7125

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2 H319 Causes serious eye irritation.
Skin irritation, category 2 H315 Causes skin irritation.

Skin sensitization, category 1 H317 May cause an allergic skin reaction.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Warning

Hazard statements:

H319 Causes serious eye irritation.H315 Causes skin irritation.

H317 May cause an allergic skin reaction.



REAL GRN 785 A - TWO COMPONENT. EPOXY COATING FLOOR COATING IN RAL CATALOG COLORS - A COMPONENT

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 2 / 12

Replaced revision:1 (Dated 12/05/2025)

SECTION 2. Hazards identification .../>>

Precautionary statements:

P280 Wear protective gloves / eye protection / face protection.
P261 Avoid breathing dust / fume / gas / mist / vapours / spray.
P333+P313 If skin irritation or rash occurs: Get medical advice / attention.
P337+P313 If eye irritation persists: Get medical advice / attention.

P264 Wash . . . thoroughly after handling.

P362+P364 Take off contaminated clothing and wash it before reuse.

Contains: Bis[4(2,3-epoksipropoksi)fenil]-propan

Alkyl (C12-C14) Glycidyl Ether

BENZYL ALCOHOL

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

CAS

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

Bis[4(2,3-epoksipropoksi)fenil]-propan

INDEX 50 ≤ x < 54 Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317

EC 216-823-5 CAS 1675-54-3 Alkyl (C12-C14) Glycidyl Ether

INDEX $5 \le x < 6$ Skin Irrit. 2 H315, Skin Sens. 1 H317

EC 271-846-8 CAS 68609-97-2 BENZYL ALCOHOL

INDEX 603-057-00-5 5 ≤ x < 6 Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Sens. 1B H317

EC 202-859-9 LD50 Oral: 1200 mg/kg

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

100-51-6

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document. In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing. INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection



REAL GRN 785 A - TWO COMPONENT, EPOXY COATING FLOOR COATING IN RAL CATALOG COLORS - A COMPONENT

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 3 / 12

Replaced revision:1 (Dated 12/05/2025)

SECTION 4. First aid measures .../>>

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If skin irritation or rash occurs: Get medical advice / attention.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.



REAL GRN 785 A - TWO COMPONENT, EPOXY COATING FLOOR COATING IN RAL CATALOG COLORS - A COMPONENT

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 4 / 12

Replaced revision:1 (Dated 12/05/2025)

SECTION 6. Accidental release measures .../>>

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR България НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА

РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.28 от 2 Април 2024г.)

BENZYL ALCOHOL						
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
	-	mg/m3	ppm	mg/m3	ppm	
TLV	BGR	5				

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.



REAL GRN 785 A - TWO COMPONENT, EPOXY COATING FLOOR COATING IN RAL CATALOG COLORS - A COMPONENT

Revision nr 2 Dated 28/05/2025 Printed on 30/05/2025

Replaced revision:1 (Dated 12/05/2025)

SECTION 8. Exposure controls/personal protection .../>>

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties Appearance not available Colour RFNKI İ Odour characteristic Melting point / freezing point not available Initial boiling point not available Boiling range 200 °C Flammability not available Lower explosive limit not available Upper explosive limit not available Flash point °C Auto-ignition temperature not available not available Decomposition temperature not available 10000-15000 Kinematic viscosity Solubility insoluble Partition coefficient: n-octanol/water not available not available Vapour pressure Density and/or relative density 1.6 g/cm3 not available Relative vapour density Particle characteristics not applicable

Value

Information

9.2. Other information

9.2.1. Information with regard to physical hazard classes



REAL GRN 785 A - TWO COMPONENT. EPOXY COATING FLOOR COATING IN RAL CATALOG COLORS - A COMPONENT

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 6 / 12

Replaced revision:1 (Dated 12/05/2025)

SECTION 9. Physical and chemical properties .../>>

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

BENZYL ALCOHOL

Decomposes at temperatures above 870°C/1598°F.Possibility of explosion.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

BENZYL ALCOHOL

May react dangerously with: hydrobromic acid,iron,oxidising agents,sulphuric acid.Risk of explosion on contact with: phosphorus trichloride.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

BENZYL ALCOHOL

Avoid exposure to: air, sources of heat, naked flames.

10.5. Incompatible materials

BENZYL ALCOHOL

Incompatible with: sulphuric acid,oxidising substances,aluminium.

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure



REAL GRN 785 A - TWO COMPONENT, EPOXY COATING FLOOR COATING IN RAL CATALOG COLORS - A COMPONENT

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 7 / 12

Replaced revision:1 (Dated 12/05/2025)

SECTION 11. Toxicological information .../>>

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture: Not classified (no significant component)

ATE (Oral) of the mixture: >2000 mg/kg

ATE (Dermal) of the mixture: Not classified (no significant component)

BENZYL ALCOHOL

LD50 (Dermal): 2000 mg/kg Rabbit

LD50 (Oral): 1200 mg/kg

LC50 (Inhalation vapours): > 4,1 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of



REAL GRN 785 A - TWO COMPONENT. EPOXY COATING FLOOR COATING IN RAL CATALOG COLORS - A COMPONENT

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 8 / 12

Replaced revision:1 (Dated 12/05/2025)

potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Information not available

12.2. Persistence and degradability

BENZYL ALCOHOL Rapidly degradable

12.3. Bioaccumulative potential

BENZYL ALCOHOL

Partition coefficient: n-octanol/water

1,1

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.



REAL GRN 785 A - TWO COMPONENT, EPOXY COATING FLOOR COATING IN RAL CATALOG COLORS - A COMPONENT

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 9 / 12 Replaced revision:1 (Dated 12/05/2025)

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3
Contained substance
Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable



REAL GRN 785 A - TWO COMPONENT, EPOXY COATING FLOOR COATING IN RAL CATALOG COLORS - A COMPONENT

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 10 / 12

Replaced revision:1 (Dated 12/05/2025)

SECTION 15. Regulatory information .../>>

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4 Acute toxicity, category 4
Eye Irrit. 2 Eye irritation, category 2
Skin Irrit. 2 Skin irritation, category 2
Skin Sens. 1 Skin sensitization, category 1
Skin Sens. 1B Skin sensitization, category 1B

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP



REAL GRN 785 A - TWO COMPONENT, EPOXY COATING FLOOR COATING IN RAL CATALOG COLORS - A COMPONENT

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 11 / 12

Replaced revision:1 (Dated 12/05/2025)

SECTION 16. Other information .../>>

- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
- 25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
- 26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
- 27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition



REAL GRN 785 A - TWO COMPONENT, EPOXY COATING FLOOR COATING IN RAL CATALOG COLORS - A COMPONENT

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 12 / 12

Replaced revision:1 (Dated 12/05/2025)

SECTION 16. Other information .../>>

- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01.