

REAL DC 985 B - TWO-COMPONENT. POLYURETHANE SELF-LEVELING JOINT SEALANT (B COMPONENT)

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 1 / 12

Replaced revision:1 (Dated 12/05/2025)

# **Safety Data Sheet**

According to Annex II to REACH - Regulation (EU) 2020/878

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: REAL DC 985 B

Product name TWO-COMPONENT, POLYURETHANE SELF-LEVELING JOINT

**SEALANT (B COMPONENT)** 

INDEX number 615-005-00-9
EC number 202-966-0
CAS number 101-68-8

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use not available

#### 1.3. Details of the supplier of the safety data sheet

Name REAL YAPI KIMYASALLARI A.S.

Full address Muratçeşme Mah. Sultan Murat Caddesi Efe 2 Sok. No:5

District and Country

Büyükçekmece / İstanbul

Türkiye

Tel. +90(212)596 11 01

1.4. Emergency telephone number

For urgent inquiries refer to +90530 905 7125

## **SECTION 2. Hazards identification**

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Carcinogenicity, category 2	H351	Suspected of causing cancer.
Acute toxicity, category 4	H332	Harmful if inhaled.
Specific target organ toxicity - repeated exposure,	H373	May cause damage to organs through prolonged or
category 2		repeated exposure.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Respiratory sensitization, category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.

Classification note according to Annex VI to the CLP Regulation: 2 Classification note according to Annex VI to the CLP Regulation: C



REAL DC 985 B - TWO-COMPONENT, POLYURETHANE SELF-LEVELING JOINT SEALANT (B COMPONENT)

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 2 / 12

Replaced revision:1 (Dated 12/05/2025)

### **SECTION 2. Hazards identification** .../>>

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H351 Suspected of causing cancer.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H319 Causes serious eye irritation. Causes skin irritation. H315

H335 May cause respiratory irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled. H334

May cause an allergic skin reaction. H317

Precautionary statements:

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.

P280 Wear protective gloves/ protective clothing / eye protection / face protection. P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER / doctor / . . . P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Obtain special instructions before use. P201

P308+P313 IF exposed or concerned: Get medical advice / attention.

DIPHENYLMETHANE-4,4'-DIISOCYANATE INDEX 615-005-00-9

As from 24 August 2023 adequate training is required before industrial or professional use.

#### 2.3. Other hazards

The substance does not have persistence, bioaccumulation and toxicity (PBT) properties and is not very persistent and very bioaccumulative. (vPvB).

The substance does not have endocrine disrupting properties.

## **SECTION 3. Composition/information on ingredients**

#### 3.1. Substances

Contains:

Identification Conc. % Classification (EC) 1272/2008 (CLP)

**DIPHENYLMETHANE-4,4'-DIISOCYANATE** 

INDEX 615-005-00-9 Carc. 2 H351, Acute Tox. 4 H332, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 100

2 H315, STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317, Classification note according to Annex VI to the CLP Regulation: 2, C

EC 202-966-0

Skin Irrit. 2 H315: ≥ 5%, Eye Irrit. 2 H319: ≥ 5%, Resp. Sens. 1 H334: ≥ 0,1%,

STOT SE 3 H335: ≥ 5%

CAS 101-68-8

The full wording of hazard (H) phrases is given in section 16 of the sheet.



REAL DC 985 B - TWO-COMPONENT, POLYURETHANE SELF-LEVELING JOINT SEALANT (B COMPONENT)

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 3 / 12

Replaced revision:1 (Dated 12/05/2025)

## **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document. In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing. INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention

#### Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

#### 4.2. Most important symptoms and effects, both acute and delayed

Information not available

## 4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned: Get medical advice / attention.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

## **SECTION 5. Firefighting measures**

### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

## 5.3. Advice for firefighters

#### **GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances



REAL DC 985 B - TWO-COMPONENT, POLYURETHANE SELF-LEVELING JOINT SEALANT (B COMPONENT)

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 4 / 12 Replaced revision:1 (Dated 12/05/2025)

potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

#### **SECTION 6. Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

## 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available



REAL DC 985 B - TWO-COMPONENT, POLYURETHANE SELF-LEVELING JOINT SEALANT (B COMPONENT)

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 5 / 12

Replaced revision:1 (Dated 12/05/2025)

## **SECTION 8. Exposure controls/personal protection**

#### 8.1. Control parameters

Regulatory references:

TUR Türkiye Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında

Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345.

ΕU **OEL EU** Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130;

Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164;

Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.

DIPHENYLMETHANE-4,4'-DIISOCYANATE							
Threshold L	Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
ESD	TUR	0,05	0,005				
OEL	EU	0.01		0,02		SKIN As NCO	

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

## 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times). HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

### **EYE PROTECTION**

Wear airtight protective goggles (see standard EN ISO 16321).

#### RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

## **ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.



REAL DC 985 B - TWO-COMPONENT, POLYURETHANE SELF-LEVELING JOINT SEALANT (B COMPONENT)

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 6 / 12

Temperature: 20-60 cps (25°C) °C

Replaced revision:1 (Dated 12/05/2025)

## **SECTION 9. Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Properties Value Information

Appearance liquid hafifi şeffaf sıvı Colour Odour characteristic Melting point / freezing point 10 Initial boiling point 205,31 °C °C Boiling range 208 Flammability not available Lower explosive limit not available Upper explosive limit not available °C Flash point 200 Auto-ignition temperature not available not available Decomposition temperature

pH not available
Kinematic viscosity not available

Solubility soluble in water Partition coefficient: n-octanol/water not available

Vapour pressure 0.0003 mmHg@26nHg

Density and/or relative density not available Temperature: 1.195-1.230 g/cm3 (25°C) °C

Relative vapour density not available Particle characteristics not applicable

#### 9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

## **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Decomposes at 274°C/525°F.

With water it develops carbon dioxide and forms an insoluble solid polymer and consequently any wet material recovered must be stored in open containers.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

May react dangerously with: alcohols, amines, ammonia, sodium hydroxide, acids, water, strong acids, strong bases.

#### 10.4. Conditions to avoid



REAL DC 985 B - TWO-COMPONENT, POLYURETHANE SELF-LEVELING JOINT SEALANT (B COMPONENT)

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 7 / 12

Replaced revision:1 (Dated 12/05/2025)

### **SECTION 10. Stability and reactivity** .../>>

None in particular. However the usual precautions used for chemical products should be respected.

### 10.5. Incompatible materials

Information not available

### 10.6. Hazardous decomposition products

May develop: nitric oxide,carbon oxides,hydrogen cyanide.

## **SECTION 11. Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

#### Information on likely routes of exposure

WORKERS: inhalation; contact with the skin.

POPULATION: inhalation of ambient air; contact with the skin of products containing the substance.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Causes symptoms of irritation of the eye mucous membranes, upper respiratory and digestive tract and also to the skin; lung irritation of the bronchitis type (chest pains, cough, asthmatic wheezing), neurological symptoms (dizziness, balance disorders, headaches and consciousness disturbances). In severe cases, may give rise to delayed pulmonary edema (INRS, 2009). May cause hypersensitivity pneumonia which, in the event of continuous exposure, may progress to interstitial fibrosis (INRS, 2009).

## Interactive effects

Cross sensitisations with other isocyanates are possible, in particular with TDI (toluene diisocyanate).

### **ACUTE TOXICITY**

Acute toxicity, category 4. Harmful if inhaled.

#### SKIN CORROSION / IRRITATION

Causes skin irritation

#### **SERIOUS EYE DAMAGE / IRRITATION**

Causes serious eye irritation

#### RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin Sensitising for the respiratory system

#### **GERM CELL MUTAGENICITY**

Does not meet the classification criteria for this hazard class

#### **CARCINOGENICITY**



REAL DC 985 B - TWO-COMPONENT, POLYURETHANE SELF-LEVELING JOINT SEALANT (B COMPONENT)

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 8 / 12

Replaced revision:1 (Dated 12/05/2025)

### **SECTION 11. Toxicological information** .../>>

Suspected of causing cancer

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999).

## REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### STOT - SINGLE EXPOSURE

May cause respiratory irritation

#### **STOT - REPEATED EXPOSURE**

May cause damage to organs

#### **ASPIRATION HAZARD**

Does not meet the classification criteria for this hazard class

#### 11.2. Information on other hazards

Based on the available data, the substance is not listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

## **SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

### 12.1. Toxicity

Information not available

#### 12.2. Persistence and degradability

Solubility in water 0,1 - 100 mg/l

NOT rapidly degradable

#### 12.3. Bioaccumulative potential

Partition coefficient: n-octanol/water 4,51

#### 12.4. Mobility in soil

Information not available

## 12.5. Results of PBT and vPvB assessment

The substance does not have persistence, bioaccumulation and toxicity (PBT) properties and is not very persistent and very bioaccumulative. (vPvB).

#### 12.6. Endocrine disrupting properties

Based on the available data, the substance is not listed in the main European lists of potential or suspected



REAL DC 985 B - TWO-COMPONENT, POLYURETHANE SELF-LEVELING JOINT SEALANT (B COMPONENT)

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 9 / 12

Replaced revision:1 (Dated 12/05/2025)

### **SECTION 12. Ecological information** .../>>

endocrine disruptors with environmental effects under evaluation.

#### 12.7. Other adverse effects

Information not available

## **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

**CONTAMINATED PACKAGING** 

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## **SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

#### 14.1. UN number or ID number

not applicable

### 14.2. UN proper shipping name

not applicable

## 14.3. Transport hazard class(es)

not applicable

## 14.4. Packing group

not applicable

#### 14.5. Environmental hazards

not applicable

#### 14.6. Special precautions for user

not applicable



REAL DC 985 B - TWO-COMPONENT, POLYURETHANE SELF-LEVELING JOINT SEALANT (B COMPONENT)

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 10 / 12

Replaced revision:1 (Dated 12/05/2025)

## **SECTION 14. Transport information** .../>>

## 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

## **SECTION 15. Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>

Point 3 Contained substance

Point 56-75 DIPHENYLMETHANE-4.4'-DIISOCYANATE

Point 74 DIISOCYANATES

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

#### **Healthcare controls**

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

#### 15.2. Chemical safety assessment

Has not been performed / is not yet available a chemical safety assessment for the substance.

#### **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Carc. 2 Carcinogenicity, category 2
Acute Tox. 4 Acute toxicity, category 4

STOT RE 2 Specific target organ toxicity - repeated exposure, category 2

Eye Irrit. 2 Eye irritation, category 2 Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Resp. Sens. 1



REAL DC 985 B - TWO-COMPONENT, POLYURETHANE SELF-LEVELING JOINT SEALANT (B COMPONENT)

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 11 / 12

Replaced revision:1 (Dated 12/05/2025)

#### **SECTION 16. Other information** .../>>

Respiratory sensitization, category 1

Skin Sens. 1 Skin sensitization, category 1
H351 Suspected of causing cancer.

H332 Harmful if inhaled.

**H373** May cause damage to organs through prolonged or repeated exposure.

**H319** Causes serious eye irritation.

**H315** Causes skin irritation.

**H335** May cause respiratory irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**H317** May cause an allergic skin reaction.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

#### **GENERAL BIBLIOGRAPHY**

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament



REAL DC 985 B - TWO-COMPONENT, POLYURETHANE SELF-LEVELING JOINT SEALANT (B COMPONENT)

Revision nr.2 Dated 28/05/2025 Printed on 30/05/2025 Page n. 12 / 12

Replaced revision:1 (Dated 12/05/2025)

#### **SECTION 16. Other information** .../>>

- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
- 25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
- 26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
- 27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

## CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

#### Changes to previous review:

The following sections were modified:

01.