

KPB256VG10 - KEMILAC POL. BIANCO 256V G10 - OPV256BVG10

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: KPB256VG10
Product name: KEMILAC POL. BIANCO 256V G10 - OPV256BVG10
UFI : AWDA-H0CR-500G-H9MD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: KEMILAC WHITE POLYURETHANE

Identified Uses	Industrial	Professional	Consumer
Product for painting	✓	-	-

1.3. Details of the supplier of the safety data sheet

Name: KEMICAL SRL
Full address: Via Dell'Artigianato, 2
District and Country: 35010 Trebaseleghe (PD) Italia
Tel.: +390499385648
Fax: +390499385070
e-mail address of the competent person responsible for the Safety Data Sheet: laboratorio@kemichal.it

1.4. Emergency telephone number

For urgent inquiries refer to: National Poisons Information Service DIAL 111

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Reproductive toxicity, category 2	H361d	Suspected of damaging the unborn child.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Skin sensitization, category 1A	H317	May cause an allergic skin reaction.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



KEMICHAL SRL

KPB256VG10 - KEMILAC POL. BIANCO 256V G10 - OPV256BVG10

Revision nr.8
Dated 20/06/2024
Printed on 20/06/2024
Page n. 2 / 20
Replaced revision:7 (Dated 20/02/2024)

EN

SECTION 2. Hazards identification ... / >>

Signal words:

Danger

Hazard statements:

H225

Highly flammable liquid and vapour.

H361d

Suspected of damaging the unborn child.

H304

May be fatal if swallowed and enters airways.

H373

May cause damage to organs through prolonged or repeated exposure.

H315

Causes skin irritation.

H335

May cause respiratory irritation.

H317

May cause an allergic skin reaction.

Precautionary statements:

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P331

Do NOT induce vomiting.

P280

Wear protective gloves/ protective clothing / eye protection / face protection.

P301+P310

IF SWALLOWED: immediately call a POISON CENTER / doctor (show label if possible).

P370+P378

In case of fire: use carbon dioxide, foam, dry chemical, water spray to extinguish. Do not use water directly on the flames.

P261

Avoid breathing mist / vapours / spray.

Contains:

TOLUENE

XYLENE

MALEIC ANHYDRIDE

Miscela reattiva di etilbenzene ,m-xilene p-xilene (Benzene <0,01%)

prodotti della reazione di addizione di acidi grassi dell'olio girasole coniugati e acidi grassi di talloil con anidride acida dell'acido maleico

Product not intended for uses provided for by Directive 2004/42/EC.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<div><div>XYLENE</div><div>INDEX601-022-00-9</div></div>	17,5 ≤ x < 19	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l
<div><div>EC215-535-7</div><div>CAS1330-20-7</div><div>REACH Reg.01-2119488216-32</div><div>TOLUENE</div><div>INDEX601-021-00-3</div></div>	7 ≤ x < 8	Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 3 H412
<div><div>EC203-625-9</div><div>CAS108-88-3</div><div>REACH Reg.01-2119471310-51</div><div>Miscela reattiva di etilbenzene ,m-xilene p-xilene (Benzene <0,01%)</div><div>INDEX4,6 ≤ x < 4,8</div></div>		Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335 ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l
<div><div>EC905-562-9</div><div>CAS</div></div>		

EPY 11.7.1 - SDS 1004.14

KPB256VG10 - KEMILAC POL. BIANCO 256V G10 - OPV256BVG10

SECTION 3. Composition/information on ingredients ... / >>

REACH Reg. 01-2119555267-33-XXXX

ETHYL ACETATEINDEX 607-022-00-5 $2,2 \leq x < 2,3$ Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

EC 205-500-4

CAS 141-78-6

REACH Reg. 01-2119475103-46

prodotti della reazione di addizione di acidi grassi dell'olio girasole coniugati e acidi grassi di talloil con anidride acida dell'acido maleicoINDEX 701-043-4 $0,2425 \leq x < 0,2525$ Skin Irrit. 2 H315, Skin Sens. 1 H317

EC 701-043-4

CAS

ETHYLBENZENEINDEX 601-023-00-4 $0,076 \leq x < 0,078$ Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412

EC 202-849-4

CAS 100-41-4

METHANOLINDEX 603-001-00-X $0,066 \leq x < 0,068$ Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT SE 1 H370

EC 200-659-6

CAS 67-56-1

STOT SE 2 H371: $\geq 3\% - < 10\%$
ATE Oral: 100 mg/kg, ATE Dermal: 300 mg/kg, ATE Inhalation vapours: 3 mg/l

REACH Reg. 01-2119433307-44

2-METHOXY-1-METHYLETHYL ACETATEINDEX 607-195-00-7 $0,024 \leq x < 0,025$ Flam. Liq. 3 H226, STOT SE 3 H336

EC 203-603-9

CAS 108-65-6

REACH Reg. 01-2119475791-29

CUMENEINDEX 601-024-00-X $0,004 \leq x < 0,005$ Flam. Liq. 3 H226, Carc. 1B H350, Asp. Tox. 1 H304, STOT SE 3 H335, Aquatic Chronic 2 H411

EC 202-704-5

CAS 98-82-8

MALEIC ANHYDRIDEINDEX 607-096-00-9 $0,002 \leq x < 0,003$ Acute Tox. 4 H302, STOT RE 1 H372, Skin Corr. 1B H314, Eye Dam. 1 H318, Resp. Sens. 1 H334, Skin Sens. 1A H317, EUH071

EC 203-571-6

CAS 108-31-6

Skin Sens. 1A H317: $\geq 0,001\%$
ATE Oral: 500 mg/kg

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

KPB256VG10 - KEMILAC POL. BIANCO 256V G10 - OPV256BVG10

SECTION 4. First aid measures ... / >>

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned: Get medical advice / attention.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

KEMICHAL SRL		Revision nr.8 Dated 20/06/2024 Printed on 20/06/2024 Page n. 5 / 20 Replaced revision:7 (Dated 20/02/2024)	EN
KPB256VG10 - KEMILAC POL. BIANCO 256V G10 - OPV256BVG10			
SECTION 7. Handling and storage			
7.1. Precautions for safe handling			
Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.			
7.2. Conditions for safe storage, including any incompatibilities			
Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.			
2-METHOXY-1-METHYLETHYL ACETATE			
Store in an inert atmosphere, sheletered from moisture because it hydrolises easily.			
7.3. Specific end use(s)			
Information not available			
SECTION 8. Exposure controls/personal protection			
8.1. Control parameters			
Regulatory references:			
BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)	
ESP	España	Límites de exposición profesional para agentes químicos en España 2023	
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021	
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία"»	
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81	
LTU	Lietuva	Jsakymas dėl lietuvos higienos normos hn 23:2011 „cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai" patvirtinimo	
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos	
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy	
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006	
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345.	
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)	
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.	
	TLV-ACGIH	ACGIH 2023	

CEPY 11.7.1 - SDS 1004.14

KPB256VG10 - KEMILAC POL. BIANCO 256V G10 - OPV256BVG10

SECTION 8. Exposure controls/personal protection ... / >>

XYLENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	221	50	442	100	SKIN
VLA	ESP	221	50	442	100	SKIN
VLEP	FRA	221	50	442	100	SKIN
TLV	GRC	435	100	650	150	
VLEP	ITA	221	50	442	100	SKIN
RD	LTU	221	50	442	100	SKIN
VLE	PRT	221	50	442	100	SKIN
NDS/NDSch	POL	100		200		SKIN
TLV	ROU	221	50	442	100	SKIN
ESD	TUR	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH			20			

TITANIUM DIOXIDE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	10				RESP
VLA	ESP	10				
VLEP	FRA	10				
TLV	GRC		10			
RD	LTU	5				
NDS/NDSch	POL	10				INHAL
TLV	ROU	10		15		
WEL	GBR	10				INHAL
WEL	GBR	4				RESP
TLV-ACGIH		0,2				RESP

2-METHOXY-1-METHYLETHYL ACETATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	275	50	550	100	SKIN
VLA	ESP	275	50	550	100	SKIN
VLEP	FRA	275	50	550	100	SKIN
TLV	GRC	275	50	550	100	
VLEP	ITA	275	50	550	100	SKIN
RD	LTU	250	50	400	75	SKIN
VLE	PRT	275	50	550	100	SKIN
NDS/NDSch	POL	260		520		SKIN
TLV	ROU	275	50	550	100	SKIN
ESD	TUR	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

KPB256VG10 - KEMILAC POL. BIANCO 256V G10 - OPV256BVG10

SECTION 8. Exposure controls/personal protection ... / >>

TOLUENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	192	50	384	100	SKIN
VLA	ESP	192	50	384	100	SKIN
VLEP	FRA	76,8	20	384	100	SKIN
TLV	GRC	192	50	384	100	
VLEP	ITA	192	50			SKIN
RD	LTU	192	50	384	100	SKIN
VLE	PRT	192	50	384	100	SKIN
NDS/NDSch	POL	100		200		SKIN
TLV	ROU	192	50	384	100	SKIN
ESD	TUR	192	50	384	100	SKIN
WEL	GBR	191	50	384	100	SKIN
OEL	EU	192	50	384	100	SKIN
TLV-ACGIH			20			

ETHYLBENZENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	435		545		SKIN
VLA	ESP	441	100	884	200	SKIN
VLEP	FRA	88,4	20	442	100	SKIN
TLV	GRC	435	100	545	125	
VLEP	ITA	442	100	884	200	SKIN
RD	LTU	442	100	884	200	SKIN
VLE	PRT	442	100	884	200	SKIN
NDS/NDSch	POL	200		400		SKIN
TLV	ROU	442	100	884	200	SKIN
ESD	TUR	442	100	884	200	SKIN
WEL	GBR	441	100	552	125	SKIN
OEL	EU	442	100	884	200	SKIN
TLV-ACGIH		87	20			

CUMENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	100	20	250	50	SKIN
VLA	ESP	50	10	250	50	SKIN
VLEP	FRA	50	10	250	50	SKIN
TLV	GRC	245	50	370	75	
VLEP	ITA	100	20	250	50	SKIN
RD	LTU	50	10	170	35	SKIN
VLE	PRT	50	10	250	50	INHAL
VLE	PRT	50	10	250	50	SKIN
NDS/NDSch	POL	50		250		SKIN
TLV	ROU	50	10	250	50	SKIN
ESD	TUR	50	10	250	50	SKIN
WEL	GBR	125	25	250	50	SKIN
OEL	EU	50	10	250	50	SKIN
TLV-ACGIH			5			

KPB256VG10 - KEMILAC POL. BIANCO 256V G10 - OPV256BVG10

SECTION 8. Exposure controls/personal protection ... / >>

METHANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	260	200			SKIN
VLA	ESP	266	200			SKIN
VLEP	FRA	260	200	1300	1000	SKIN 11
TLV	GRC	260	200	325	250	
VLEP	ITA	260	200			SKIN
RD	LTU	260	200			SKIN
VLE	PRT	260	200			SKIN
NDS/NDSch	POL	100		300		SKIN
TLV	ROU	260	200			SKIN
ESD	TUR	260	200			SKIN
WEL	GBR	266	200	333	250	SKIN
OEL	EU	260	200			
TLV-ACGIH		262	200	328	250	SKIN

ETHANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	1000				
VLA	ESP			1910	1000	
VLEP	FRA	1900	1000	9500	5000	
TLV	GRC	1900	1000			
RD	LTU	1000	500	1900	1000	
NDS/NDSch	POL	1900				
TLV	ROU	1900	1000	9500	5000	
ESD	TUR	1900	1000			
WEL	GBR	1920	1000			
TLV-ACGIH				1884	1000	

PROPAN-2-OL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	980		1225		
VLA	ESP	500	200	1000	400	
VLEP	FRA			980	400	
TLV	GRC	980	400	1225	500	
RD	LTU	350	150	600	250	
NDS/NDSch	POL	900		1200		SKIN
TLV	ROU	200	81	500	203	
ESD	TUR	980	400			
WEL	GBR	999	400	1250	500	
TLV-ACGIH		492	200	983	400	

DI-ISOBUTYL KETONE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	148	25			
VLEP	FRA	250	25			
TLV	GRC	290	50			
NDS/NDSch	POL	150		300		
TLV	ROU	150	26	250	43	
ESD	TUR	290	50			
WEL	GBR	148	25			
TLV-ACGIH		145	25			

SECTION 8. Exposure controls/personal protection ... / >>

ETHYL ACETATE						
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	734	200	1468	400	
VLA	ESP	734	200	1468	400	
VLEP	FRA	734	200	1468	400	
TLV	GRC	734	200	1468	400	
VLEP	ITA	734	200	1468	400	
RD	LTU	500	150	1100 (C)	300 (C)	
VLE	PRT	734	200	1468	400	
NDS/NDSch	POL	734		1468		
TLV	ROU	734	200	1468	400	
ESD	TUR	734	200	1468	400	
WEL	GBR	734	200	1468	400	
OEL	EU	734	200	1468	400	
TLV-ACGIH		1441	400			

MALEIC ANHYDRIDE						
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	1				
VLA	ESP	0,4	0,1			
VLEP	FRA			1		
TLV	GRC	1				
RD	LTU	1,2	0,3	2,5	0,6	
NDS/NDSch	POL	0,5		1		SKIN
TLV	ROU	1	0,25	3	0,75	
ESD	TUR	1	0,25			
WEL	GBR	1		3		
TLV-ACGIH		0,01	0,0025			INHAL

octamethylcyclotetrasiloxane								
Predicted no-effect concentration - PNEC								
Normal value in fresh water					1,5	µg/L		
Normal value in marine water					0,00015	mg/l		
Normal value for fresh water sediment					3	mg/kg		
Normal value for marine water sediment					300	µg/kg		
Normal value for marine water, intermittent release					150	ng/L		
Normal value of STP microorganisms					10	mg/l		
Normal value for the food chain (secondary poisoning)					41	mg/kg		
Normal value for the terrestrial compartment					840	µg/kg		
Normal value for the atmosphere					NPI			
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		3,7 mg/kg				
Inhalation		NPI	13,0 mg/m³	13,0 mg/m³	NPI	NPI	73,0 mg/m³	73,0 mg/m³
Skin		NPI	NPI	NPI	NPI	NPI	NPI	NPI

KEMICHAL SRL

KPB256VG10 - KEMILAC POL. BIANCO 256V G10 - OPV256BVG10

Revision nr.8

Dated 20/06/2024

Printed on 20/06/2024

Page n. 10 / 20

Replaced revision:7 (Dated 20/02/2024)

EN

SECTION 8. Exposure controls/personal protection ... / >>

Miscela reattiva di etilbenzene ,m-xilene p-xilene (Benzene <0,01%)

Predicted no-effect concentration - PNEC

Normal value in fresh water	327	µg/L
Normal value in marine water	327	µg/L
Normal value for fresh water sediment	12,46	mg/kg/d
Normal value for marine water sediment	12,46	mg/kg/d
Normal value for water, intermittent release	327	µg/L
Normal value of STP microorganisms	6,58	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			Chronic systemic
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	
Oral				1,6 mg/kg bw/d				
Inhalation				14,8 mg/m3	289 mg/m3			77 mg/m3
Skin				108 mg/kg bw/d				180 mg/kg bw/d

Decamethylcyclopentasiloxane

Predicted no-effect concentration - PNEC

Normal value in fresh water	1,2	µg/L
Normal value in marine water	0,00012	mg/l
Normal value for fresh water sediment	11	mg/kg
Normal value for marine water sediment	1,1	mg/kg
Normal value for marine water, intermittent release	120	ng/L
Normal value of STP microorganisms	10	mg/l
Normal value for the food chain (secondary poisoning)	16	mg/kg
Normal value for the terrestrial compartment	2,54	mg/kg
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			Chronic systemic
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	
Oral		NPI		5,0 mg/kg				
Inhalation		NPI	4,3 mg/m³	17,3 mg/m³	NPI	NPI	24,2 mg/m³	97,3 mg/m³
Skin		NPI	NPI	NPI	NPI	NPI	NPI	NPI

Dodecamethylcyclohexasiloxane

Predicted no-effect concentration - PNEC

Normal value in fresh water	NPI	
Normal value in marine water	NPI	
Normal value for fresh water sediment	13,5	mg/kg
Normal value for marine water sediment	1,35	mg/kg
Normal value for water, intermittent release	NPI	
Normal value for marine water, intermittent release	NPI	
Normal value of STP microorganisms	NPI	
Normal value for the food chain (secondary poisoning)	66,7	mg/kg
Normal value for the terrestrial compartment	NPI	
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			Chronic systemic
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	
Oral		NPI		NPI		1,7 mg/kg bw/d	1,7 mg/kg bw/d	
Inhalation		NPI	300,0 µg/m³	NPI	6,1 mg/m³	NPI	1,22 mg/m³	NPI
Skin		NPI	NPI	NPI	NPI	NPI	NPI	NPI

EPY 11.7.1 - SDS 1004.14

Reazione di massa dell'etilbenzene e dello xilene

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg/d
Normal value for marine water sediment	12,46	mg/kg/d
Normal value for water, intermittent release	0,327	mg/l
Normal value of STP microorganisms	6,58	mg/l
Normal value for the terrestrial compartment	2,31	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers	Effects on workers
1. Product quality	<p>• Quality of goods: Firms may invest in better materials and technology to improve product quality and differentiate themselves from competitors.</p> <p>• Quality of services: Firms may invest in training and technology to improve service quality and customer satisfaction.</p>	<p>• Quality of work life: Firms may invest in better working conditions, safety, and employee benefits to attract and retain talent.</p> <p>• Quality of products: Firms may invest in better materials and technology to improve product quality and differentiate themselves from competitors.</p>
2. Product variety	<p>• Product differentiation: Firms may invest in research and development to create new products and services, leading to increased product variety.</p> <p>• Product innovation: Firms may invest in new technologies and processes to create innovative products and services.</p>	<p>• Product innovation: Firms may invest in new technologies and processes to create innovative products and services.</p> <p>• Product differentiation: Firms may invest in research and development to create new products and services, leading to increased product variety.</p>
3. Product price	<p>• Price competition: Firms may invest in cost-cutting measures to reduce production costs and compete on price.</p> <p>• Price differentiation: Firms may invest in premium branding and marketing to create high-end products and services, leading to higher prices.</p>	<p>• Price competition: Firms may invest in cost-cutting measures to reduce production costs and compete on price.</p> <p>• Price differentiation: Firms may invest in premium branding and marketing to create high-end products and services, leading to higher prices.</p>
4. Product availability	<p>• Product availability: Firms may invest in logistics and distribution networks to ensure that products are available to customers in a timely and efficient manner.</p> <p>• Product innovation: Firms may invest in new technologies and processes to create innovative products and services.</p>	<p>• Product availability: Firms may invest in logistics and distribution networks to ensure that products are available to customers in a timely and efficient manner.</p> <p>• Product innovation: Firms may invest in new technologies and processes to create innovative products and services.</p>

Predicted no-effect concentration - PNEC

Normal value for the food chain (secondary poisoning)	67	mg/kg
---	----	-------

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers	Effects on workers
1. Product quality	<p>• Quality of goods: Higher quality standards, improved safety, and better product reliability.</p> <p>• Product variety: Increased range of products and services.</p>	<p>• Job quality: Improved working conditions, safety, and job security.</p> <p>• Productivity: Increased productivity due to better equipment and training.</p>
2. Income and employment	<p>• Income: Higher income levels for consumers.</p> <p>• Employment: Increased employment opportunities.</p>	<p>• Income: Higher income levels for workers.</p> <p>• Employment: Increased employment opportunities.</p>
3. Health and safety	<p>• Health: Improved health and safety standards.</p> <p>• Safety: Reduced risk of accidents and injuries.</p>	<p>• Health: Improved health and safety standards.</p> <p>• Safety: Reduced risk of accidents and injuries.</p>
4. Environment	<p>• Environment: Improved environmental standards.</p> <p>• Waste: Reduced waste and pollution.</p>	<p>• Environment: Improved environmental standards.</p> <p>• Waste: Reduced waste and pollution.</p>

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low

hazard ; MED = medium hazard ; HIGH = high hazard.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as

to guarantee maximum protection (e.g. reduction in replacement times).

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability

time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash

body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the

threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourous or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing

KPB256VG10 - KEMILAC POL. BIANCO 256V G10 - OPV256BVG10

SECTION 8. Exposure controls/personal protection ... / >>

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	white	
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	77 °C	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	-4 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	
Kinematic viscosity	1100 mm ² /s	Temperature: 20 °C
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1,33 kg/l	Temperature: 20 °C
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F)	65,78 %		
VOC (Directive 2010/75/EU)	34,08 %	- 453,29	g/litre
VOC (volatile carbon)	29,97 %	- 398,65	g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-METHOXY-1-METHYLETHYL ACETATE

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

TOLUENE

Avoid exposure to: light.

ETHYL ACETATE

Decomposes slowly into acetic acid and ethanol under the effect of light, air and water.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

KPB256VG10 - KEMILAC POL. BIANCO 256V G10 - OPV256BVG10

SECTION 10. Stability and reactivity ... / >>

XYLENE

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

2-METHOXY-1-METHYLETHYL ACETATE

May react violently with: oxidising substances, strong acids, alkaline metals.

TOLUENE

Risk of explosion on contact with: fuming sulphuric acid, nitric acid, silver perchlorate, nitrogen dioxide, non-metal halogenates, acetic acid, organic nitrocompounds. May form explosive mixtures with: air. May react dangerously with: strong oxidising agents, strong acids, sulphur.

ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

ETHYL ACETATE

Risk of explosion on contact with: alkaline metals, hydrides, oleum. May react violently with: fluorine, strong oxidising agents, chlorosulphuric acid, potassium tert-butoxide. Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ETHYL ACETATE

Avoid exposure to: light, sources of heat, naked flames.

10.5. Incompatible materials

2-METHOXY-1-METHYLETHYL ACETATE

Incompatible with: oxidising substances, strong acids, alkaline metals.

ETHYL ACETATE

Incompatible with: acids, bases, strong oxidants, chlorosulphuric acid.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

2-METHOXY-1-METHYLETHYL ACETATE

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

XYLENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

2-METHOXY-1-METHYLETHYL ACETATE

WORKERS: inhalation; contact with the skin.

TOLUENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

METHANOL

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

KPB256VG10 - KEMILAC POL. BIANCO 256V G10 - OPV256BVG10

SECTION 11. Toxicological information ... / >>

XYLENE

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

2-METHOXY-1-METHYLETHYL ACETATE

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

TOLUENE

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispesl). Is irritating for skin, conjunctiva and respiratory tract.

METHANOL

The minimum lethal dose for humans by ingestion is considered to be in the range from 300 to 1000 mg/kg. Ingestion of 4-10 ml of the substance may cause permanent blindness in adult humans (IPCS).

Interactive effects

XYLENE

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

TOLUENE

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	>2000 mg/kg

XYLENE

LD50 (Dermal):	4350 mg/kg Rabbit
ATE (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	26 mg/l/4h Rat
ATE (Inhalation vapours):	11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

2-METHOXY-1-METHYLETHYL ACETATE

LD50 (Dermal):	> 5000 mg/kg Rat
LD50 (Oral):	8530 mg/kg Rat

TOLUENE

LD50 (Dermal):	12124 mg/kg Rabbit
LD50 (Oral):	5580 mg/kg Rat
LC50 (Inhalation vapours):	28,1 mg/l/4h Rat

ETHYLBENZENE

LD50 (Dermal):	15354 mg/kg Rabbit
LD50 (Oral):	3500 mg/kg Rat
LC50 (Inhalation vapours):	17,2 mg/l/4h Rat

CUMENE

LD50 (Dermal):	> 3160 mg/kg Rabbit
LD50 (Oral):	1400 mg/kg Rat
LC50 (Inhalation vapours):	> 17,6 mg/l/6h Rat

KPB256VG10 - KEMILAC POL. BIANCO 256V G10 - OPV256BVG10

SECTION 11. Toxicological information ... / >>

METHANOL
LC50 (Inhalation vapours): > 87,6 mg/l/4h Rat

MALEIC ANHYDRIDE
LD50 (Dermal): 610 mg/kg Rat
LD50 (Oral): 400 mg/kg Rat

Miscela reattiva di etilbenzene ,m-xilene p-xilene (Benzene <0,01%)
LD50 (Dermal): 12126 mg/kg
ATE (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral): 3500 mg/kg
LC50 (Inhalation vapours): 27,124 mg/l/4h
ATE (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

prodotti della reazione di addizione di acidi grassi dell'olio girasole coniugati e acidi grassi di talloil con anidride acida dell'acido maleico
LD50 (Oral): > 2000 mg/kg ratto (femmina) - OECD 423

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

XYLENE
Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

TOLUENE
Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

ETHYLBENZENE
Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).
Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

REPRODUCTIVE TOXICITY

Suspected of damaging the unborn child

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

KPB256VG10 - KEMILAC POL. BIANCO 256V G10 - OPV256BVG10

SECTION 11. Toxicological information ... / >>

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Miscela reattiva di etilbenzene ,m-xilene p-xilene (Benzene <0,01%)

LC50 - for Fish	2,6 mg/l/96h
EC50 - for Algae / Aquatic Plants	4,36 mg/l/72h
EC10 for Algae / Aquatic Plants	1900 µg/L/72h
Chronic NOEC for Fish	1,3 mg/l
Chronic NOEC for Crustacea	1065 µg/L
Chronic NOEC for Algae / Aquatic Plants	440 µg/L/72

prodotti della reazione di addizione di acidi grassi dell'olio girasole coniugati e acidi grassi di talloil con anidride acida dell'acido maleico

LC50 - for Fish	> 150 mg/l/96h Leuciscus idus
EC50 - for Crustacea	> 100 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h Pseudokirchneriella subcapitata

12.2. Persistence and degradability

XYLENE

Solubility in water	100 - 1000 mg/l
Rapidly degradable	

TOLUENE

Solubility in water	100 - 1000 mg/l
Rapidly degradable	

METHANOL

Solubility in water	1000 - 10000 mg/l
Rapidly degradable	

ETHYL ACETATE

Solubility in water	> 10000 mg/l
Rapidly degradable	

12.3. Bioaccumulative potential

XYLENE

Partition coefficient: n-octanol/water	3,12
BCF	25,9

TOLUENE

Partition coefficient: n-octanol/water	2,73
BCF	90

METHANOL




Partition coefficient: n-octanol/water	-0,77
BCF	0,2

ETHYL ACETATE

Partition coefficient: n-octanol/water	0,68
BCF	30

12.4. Mobility in soil

Information not available

KEMICHAL SRL		Revision nr.8 Dated 20/06/2024 Printed on 20/06/2024 Page n. 17 / 20 Replaced revision:7 (Dated 20/02/2024)		EN
KPB256VG10 - KEMILAC POL. BIANCO 256V G10 - OPV256BVG10				
SECTION 12. Ecological information ... / >>				
12.5. Results of PBT and vPvB assessment				
On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.				
12.6. Endocrine disrupting properties				
Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.				
12.7. Other adverse effects				
Information not available				
SECTION 13. Disposal considerations				
13.1. Waste treatment methods				
Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. Waste transportation may be subject to ADR restrictions. CONTAMINATED PACKAGING Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.				
SECTION 14. Transport information				
14.1. UN number or ID number				
ADR / RID, IMDG, IATA: UN 1263				
14.2. UN proper shipping name				
ADR / RID: PAINT RELATED MATERIAL IMDG: PAINT RELATED MATERIAL IATA: PAINT RELATED MATERIAL				
14.3. Transport hazard class(es)				
ADR / RID:		Class: 3	Label: 3	
IMDG:		Class: 3	Label: 3	
IATA:		Class: 3	Label: 3	
14.4. Packing group				
ADR / RID, IMDG, IATA: II				
14.5. Environmental hazards				
ADR / RID: NO IMDG: not marine pollutant IATA: NO				
14.6. Special precautions for user				
ADR / RID:		HIN - Kemler: 33 Special provision: 163, 367, 640D, 650	Limited Quantities: 5 lt	Tunnel restriction code: (D/E)
IMDG:		EMS: F-E, S-E	Limited Quantities: 5 lt	
IATA:		Cargo: Passengers: Special provision:	Maximum quantity: 60 L Maximum quantity: 5 L A3, A72, A192	Packaging instructions: 364 Packaging instructions: 353

<div>KEMICHAL SRL</div> <div>KPB256VG10 - KEMILAC POL. BIANCO 256V G10 - OPV256BVG10</div>		<div>Revision nr.8</div> <div>Dated 20/06/2024</div> <div>Printed on 20/06/2024</div> <div>Page n. 18 / 20</div> <div>Replaced revision:7 (Dated 20/02/2024)</div> <div>EN</div>
SECTION 14. Transport information ... / >>		
14.7. Maritime transport in bulk according to IMO instruments		
Information not relevant		
SECTION 15. Regulatory information		
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture		
Seveso Category - Directive 2012/18/EU: P5c		
Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006		
Product		
Point 3 - 40		
Contained substance		
Point 75		
Point 48 TOLUENE		
REACH Reg.: 01-2119471310-51		
Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors		
not applicable		
Substances in Candidate List (Art. 59 REACH)		
On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.		
Substances subject to authorisation (Annex XIV REACH)		
None		
Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:		
None		
Substances subject to the Rotterdam Convention:		
None		
Substances subject to the Stockholm Convention:		
None		
Healthcare controls		
Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.		
15.2. Chemical safety assessment		
A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.		
SECTION 16. Other information		
Text of hazard (H) indications mentioned in section 2-3 of the sheet:		
Flam. Liq. 2	Flammable liquid, category 2	
Flam. Liq. 3	Flammable liquid, category 3	
Carc. 1B	Carcinogenicity, category 1B	
Repr. 2	Reproductive toxicity, category 2	
Acute Tox. 3	Acute toxicity, category 3	
STOT SE 1	Specific target organ toxicity - single exposure, category 1	
Acute Tox. 4	Acute toxicity, category 4	
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1	
Asp. Tox. 1	Aspiration hazard, category 1	
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2	
Skin Corr. 1B	Skin corrosion, category 1B	
Eye Irrit. 2	Eye irritation, category 2	
Skin Irrit. 2	Skin irritation, category 2	
STOT SE 3	Specific target organ toxicity - single exposure, category 3	
Resp. Sens. 1	Respiratory sensitization, category 1	
Skin Sens. 1	Skin sensitization, category 1	
Skin Sens. 1A	Skin sensitization, category 1A	

EPY 11.7.1 - SDS 1004.14

KPB256VG10 - KEMILAC POL. BIANCO 256V G10 - OPV256BVG10

SECTION 16. Other information ... / >>

STOT SE 2	Specific target organ toxicity - single exposure, category 2
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H350	May cause cancer.
H361d	Suspected of damaging the unborn child.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H371	May cause damage to organs.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)

KPB256VG10 - KEMILAC POL. BIANCO 256V G10 - OPV256BVG10

SECTION 16. Other information ... / >>

4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
24. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

03 / 04 / 08 / 14 / 16.