

Polaron®

TECHNICAL DATA SHEET

P-UHS Hardener for 2K Acrylic UHS varnish - scratch resistant

Field of application	Car-refinish and commercial vehicles
Chemical bases	Non-yellowing highly durable aliphatic isocyanate resin
General qualities	P UHS Hardener is the hardener of P-Acryl / C2 UHS Scratch Resistant Clear Coat. It is a non-yellowing, high strength, ultra high solid hardener. It should be used upper 8 °C
Recommended Products	2K Acrylic UHS varnish - Scratch resistant - P-Acryl/C2 Polaron Thinners T 8-18 , 18-25 or 25-35
Gloss	See info, P-Acryl/C2 UHS Scratch Resistant Clear Coat
Cleaning the equipment	Polaron Thinners T 8-18, 18-25 or 25-35
Colour	Clear
Storage life	Under normal storage conditions and unopened tins for up to 1-1.5 years. If the tin is opened, it can be kept for no longer than one week. The tin should be closed immediately after use. Stable approximately one week, depending on temperatures and humidity.
Safety	Use suitable respiratory protection (fresh air supply respirator is strongly recommended).

For more detailed information please see Safety Data Sheet.

**ADA COLOR LTD**
• Life In Colors •
www.adacolor-bg.com

Sofia 6 "Andrey Germanov" str. mobile: 089 666 3042 / 089 468 3880	Sofia, "Ovcha Kupel 1" quarter 33 "Promishlena" str., 429 bl., store 18, mobile: 089 666 9071	Plovdiv 176 "Brezovsko shose" str. mobile: 089 544 7503 / 089 666 3044	Varna 25 "Usta Kolyu Ficheto" str. mobile: 089 666 9079 / 089 466 9023
Shumen, "Dobrudzhanski" quarter Ind. zone, "Stroykomplekt" site mobile: 089 455 1685 / 089 666 3043	Kardzhali 1 "Klokotnitsa" str. mobile: 089 575 0749 / 089 666 3057	Troyan 49 "Makedoniya" str. mobile: 089 666 9079 / 089 673 4489	Haskovo, 5 "Okolovrasten pat" str. South Industrial zone mobile: 089 666 3051 / 089 241 2833