

P-HS Hardener for 2K Acrylic HS varnish - P-Acryl/C2

Field of application	Car-refinish and commercial vehicles
Chemical bases	Non-yellowing highly durable aliphatic isocyanate resin
General qualities	P HS Hardener is the hardener for the HS varnish P-Acryl/C2 Clear Coat. It is a non-yellowing, high strength, ultra high solid hardener. It should be used upper 8 °C
Recommended Products	<u>2K Acrylic HS varnish - P-Acryl/C2</u> Polaron Thinners <u>T 8-18</u> , <u>18-25</u> or <u>25-35</u>
Gloss	See info, P-Acryl/C2 HS vamsih
Equipment Cleaning	Polaron Thinners T 8-18, 18-25 or 25-35
Color	Clear
Storage life	Under normal storage conditions and unopened tins for up to 1-1.5 years. If the tin is opened, it can be kept for no longer than one week. The tin should be closed immediately after use. Stable approximately one week, depending on temperatures and humidity.
Safety	Use appropriate respiratory protection (the use of a painter's full face mask $-\underline{3M^{M} 6900}$ is recommended).
	For more detailed information please see Safety Data Sheet.



For professional use only. The technical information in this document has been carefully selected and prepared by us based on the current information. However, these data represent symbolic values. Since application variables are an important factor in product performance, this information should only be presented as a general guide. Polaron assumes no liability or responsibility for the use of this information. Due to any defect / error in this product, only the options of replacing the defective product or refunding the sales price are available, and the right to choose among them belongs to Polaron. See SDS for safety information.