

Polaron®

TECHNICAL DATA SHEET

e-Hardener for 2K Acrylic varnish - Polaron a-Acryl/C2

Field of application	Car-refinish and commercial vehicles
Chemical bases	Non-yellowing highly durable aliphatic isocyanate resin
General qualities	e-Hardener is Hardener for 2K Acrylic varnish a-Acryl/c2. Standard for use at normal temperatures on small and medium sized objects/areas and for partial and spot-repair. Recommended temperature for use is between 18 oC and 30 oC
Recommended Products	2K Acrylic varnish - a-Acryl/C2 Polaron Thinners T 8-18 , 18-25 or 25-35
Gloss	See the information in the TDS of a-Acryl/C2 varnish
Equipment Cleaning	Polaron Thinners T 8-18, 18-25 or 25-35
Color	Clear
Storage life	Under normal storage conditions and unopened tins for up to 1-1.5 years. If the tin is opened, it can be kept for no longer than one week. The tin should be closed immediately after use. Stable approximately one week, depending on temperatures and humidity.
Safety	Use appropriate respiratory protection (the use of a painter's full face mask - 3M™ 6900 is recommended).

For more detailed information please see Safety Data Sheet.

**ADA COLOR LTD**
• Life In Colors •
www.adacolor-bg.com

Sofia 6 "Andrey Germanov" str. mobile: 089 666 3042 / 089 468 3880	Sofia, "Ovcha Kupel 1" quarter 33 "Promishlena" str., 429 bl., store 18, mobile: 089 666 9071	Plovdiv 176 "Brezovsko shose" str. mobile: 089 544 7503 / 089 666 3044	Varna 25 "Usta Kolyu Ficheto" str. mobile: 089 666 9079 / 089 466 9023
Shumen, "Dobrudzhanski" quarter Ind. zone, "Stroykomplekt" site mobile: 089 455 1685 / 089 666 3043	Kardzhali 1 "Klokotnitsa" str. mobile: 089 575 0749 / 089 666 3057	Troyan 49 "Makedoniya" str. mobile: 089 666 9079 / 089 673 4489	Haskovo, 5 "Okolovrasten pat" str. South Industrial zone mobile: 089 666 3051 / 089 241 2833