

Polaron®

TECHNICAL DATA SHEET

Acrylic thinner - FAST - Polaron T 8-18

Field of application	Thinners for all Polaron products
Chemical bases	Organic solvent blend
General qualities	Do not use in combination with synthetic products. Universal Polaron thinners should be used according to the following temperature ranges: T 8-18 Universal Thinner Fast for: use in cold weather conditions or partial spot repair. It should be used at between 8-18 °C. T 18-25 Universal Thinner Standard for: use in normal weather conditions. It should be used at between 18-25 °C. T 25-35 Universal Thinner Slow for: use in hot weather conditions. It should be used at between 25-35 °C. T 35+ Universal Thinner Very Slow for: use in very hot weather conditions. It should be used above 35 °C
Applicability	All Polaron products except synthetic products
Mixing ratio (volume)	See TDSs for other Polaron products.
Color	Clear
Storage life	Under normal storage conditions and unopened tins up to 2 years.
Safety	Use appropriate respiratory protection (the use of a painter's full face mask - 3M™ 6900 is recommended). For more detailed information please see Safety Data Sheet.

**ADA COLOR LTD**
• Life In Colors •
www.adacolor-bg.com

Sofia 6 "Andrey Germanov" str. mobile: 089 666 3042 / 089 468 3880	Sofia, "Ovcha Kupel 1" quarter 33 "Promishlena" str., 429 bl., store 18, mobile: 089 666 9071	Plovdiv 176 "Brezovsko shose" str. mobile: 089 544 7503 / 089 666 3044	Varna 25 "Usta Kolyu Ficheto" str. mobile: 089 666 9079 / 089 466 9023
Shumen, "Dobrudzhanski" quarter Ind. zone, "Stroykomplekt" site mobile: 089 455 1685 / 089 666 3043	Kardzhali 1 "Klokotnitsa" str. mobile: 089 575 0749 / 089 666 3057	Troyan 49 "Makedoniya" str. mobile: 089 666 9079 / 089 673 4489	Haskovo, 5 "Okolovrasten pat" str. South Industrial zone mobile: 089 666 3051 / 089 241 2833