

Polaron®

TECHNICAL DATA SHEET

Acrylic thinner - SLOW - Polaron T 8-18

Field of application	Thinners for all Polaron products
Chemical bases	Organic solvent blend
General qualities	<p>Do not use in combination with synthetic products.</p> <p>Universal Polaron thinners should be used according to the following temperature ranges:</p> <p>T 8-18 Universal Thinner Fast for: use in cold weather conditions or partial spot repair. It should be used at between 8-18 °C.</p> <p>T 18-25 Universal Thinner Standard for: use in normal weather conditions. It should be used at between 18-25 °C.</p> <p>T 25-35 Universal Thinner Slow for: use in hot weather conditions. It should be used at between 25-35 °C.</p>
Applicability	All Polaron products except synthetic products
Mixing ratio (volume)	See TDSs for other Polaron products.
Color	Clear
Storage life	Under normal storage conditions and unopened tins up to 2 years.
Safety	<p>Use appropriate respiratory protection (the use of a painter's full face mask - 3M™ 6900 is recommended).</p> <p>For more detailed information please see Safety Data Sheet.</p>

**ADA COLOR LTD**
• Life In Colors •
www.adacolor-bg.com

Sofia 6 "Andrey Germanov" str. mobile: 089 666 3042 / 089 468 3880	Sofia, "Ovcha Kupel 1" quarter 33 "Promishlena" str., 429 bl., store 18, mobile: 089 666 9071	Plovdiv 176 "Brezovsko shose" str. mobile: 089 544 7503 / 089 666 3044	Varna 25 "Usta Kolyu Ficheto" str. mobile: 089 666 9079 / 089 466 9023
Shumen, "Dobrudzhanski" quarter Ind. zone, "Stroykomplekt" site mobile: 089 455 1685 / 089 666 3043	Kardzhali 1 "Klokotnitsa" str. mobile: 089 575 0749 / 089 666 3057	Troyan 49 "Makedoniya" str. mobile: 089 666 9079 / 089 673 4489	Haskovo, 5 "Okolovrasten pat" str. South Industrial zone mobile: 089 666 3051 / 089 241 2833