TECHNICAL DATA SHEET



CODE	Art. 1601
TRADE NAME	ACETONE PURO
PRODUCT TYPE	ACETONE

Technical characteristics

Solvent for paints, lacquers, adhesives, and especially for acetyl and ethyl cellulose resins, colophony and its esters, natural and synthetic resins, etc. Also used in the celluloid industry, in wool degreasing, but above all in the furniture industry as a solvent for dyes, polyester and nitro paints, and for cleaning manufactured items and painting equipment. It is used as a solvent for cellulose acetate, oils, waxes, resins, rubber, and plastics.

Applications

To diluite:

Use to thin enamels/primers to bring the coating product to the desired fluidity, with an optimal dilution that enhances gloss and flow.

To clean:

Thanks to its high solvent power, it can also be used to clean spray guns, brushes, and tools stained with paint.

Important

Always conduct a preliminary test before using. Use according to good working practices, however, dispose of the product or packaging environment.

Safety data

Refer to the Material Safety Data Sheet

Chemical and Physical Property				
Physical State	Liquid			
Colour	Colourless			
Odour	Characteristic			
Flash point	< 21°C			
Relative density	0,79 ± 0,02 g/cm3			
Boiling point	60°C ca.			

- -

• Life In Colors • www.adacolor-bg.com							
Sofia 6 "Andrey Germanov"str. mobile: 089 666 3042 / 089 468 3880	Sofia, "Ovcha Kupel 1" quarter 33 "Promishlena" str., 429 bl., store 18, mobile: 089 666 9071	Plovdiv 176 "Brezovsko shose" str. mobile: 089 544 7503 / 089 666 3044	Varna 25 "Usta Kolyu Ficheto" str. mobile: 089 666 9079 / 089 466 9023				
Shumen, "Dobrudzhanski" quarter Ind.zone, "Stroykomplekt" site mobile: 089 455 1685 / 089 666 3043	Ind.zone, "Stroykomplekt" site 1 "Klokotnitsa" str.		Haskovo, 5 "Okolovrasten pat" str. South Industrial zone mobile: 089 666 3051 / 089 241 2833				