

ANTI-CORROSION SPRAY PRIMER - ETCH PRIMER PROFESSIONAL SPRAY

ETCH PRIMER SPRAY is a one-component primer for priming metal surfaces before painting. Thanks to the aerosol formula, it is easy to apply and dries very quickly. Perfect for small-area repairs or partial painting. It can be applied as a first coat directly to bare metal. It is a suitable base for other paints: acrylic, alkyd, cellulose and epoxy.

Thanks to the content of zinc phosphate, it has very good anti-corrosion properties.

ONLY FOR PROFESSIONAL USE!

PRODUCT COLOUR

Grey, mat.

USE

- ✓ Priming metal surfaces before painting.
- ✓ Protection against corrosion.

SUBSTRATE

- ✓ Steel.
- ✓ Aluminium.
- ✓ Iron.

PROPERTIES

- ✓ Quickly drying reactive primer.
- ✓ Perfect adhesion.
- ✓ Perfect for small-area repairs or partial painting.
- ✓ No sanding required.
- ✓ Perfect protection of ferrous and steel parts against corrosion.
- ✓ It can be covered with a wide range of other paints: acrylic, alkyd, cellulose and epoxy.
- ✓ Petrol resistant.

TECHNICAL PROPERTIES

Density 20°C: 0.82 g/ml

Viscosity: not applicable (aerosol ready to use)

DRYING TIME

Drying time depends on layer thickness, temperature and ventilation.

Dust free: after approx.	10- 15 min.
Touch dry:	After approx. 30 minutes.

Sanding:	After approx. 1 hour.
Over-coating:	After approx. 1 hour.

DIRECTIONS FOR USE

The best results can be achieved by using the primer at room temperature.

Air temperature:	15°C - 30°C
Surface temperature:	15°C - 30°C
Container temperature:	18°C - 25°C
Relative humidity:	max 80%

TECHNICAL DATA SHEET**INSTRUCTION FOR USE**

- ✓ Shake the container thoroughly before use (2-3 minutes).
- ✓ The surface should be dry and clean, free from dirt, rust, grease etc., it can be lightly sanded beforehand.
- ✓ Spray an even layer from a distance of approx. 25 cm onto the surface prepared for painting.
- ✓ Allow to evaporate/dry.
- ✓ Clean the nozzle after use to prevent clogging: Hold the can upside down and spray until only gas is released.

ATTENTION: To obtain the best adhesion of the next layer, the primer should be lightly sanded with sandpaper.

CONTENT OF VOLATILE ORGANIC COMPOUNDS

II/B/e limit=840 g/l, VOC = 727,4 g/l

STORAGE CONDITIONS

Store in a cool (10- 20°C) and dry place.

Shelf live: 36 months.

ADDITIONAL INFORMATION

- ✓ Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- ✓ Pressurized container: Do not pierce or burn, even after use.
- ✓ Do not spray on an open flame or other ignition source.
- ✓ Avoid breathing spray.
- ✓ Wear eye/face protection and hand protection.
- ✓ Use only outdoors or in a well-ventilated area.

PACKAGING

ITEM NO	TYPE	CAPACITY (ML)	PACKAGING (PCS)	PACKAGING (KG)
80666-1	ETCH PRIMER SPRAY	500	12	6,36

The information given is based on careful laboratory research and many years of experience. Strong market position does not absolve us from constant control of the quality of our products. However, we are not responsible for the final results after incorrect use of the product.



www.adacolor-bg.com

Sofia
6 "Andrey Germanov" str.
mobile: 089 666 3042 / 089 468 3880

Sofia, "Ovcha Kupel 1" quarter
33 "Promishlena" str., 429 bl., store 18,
mobile: 089 666 9071

Plovdiv
176 "Brezovsko shose" str.
mobile: 089 544 7503 / 089 666 3044

Varna
25 "Usta Kolyu Ficheto" str.
mobile: 089 666 9079 / 089 466 9023

Shumen, "Dobrudzhanski" quarter
Ind. zone, "Stroykomplekt" site
mobile: 089 455 1685 / 089 666 3043

Kardzhali
1 "Klokotnitsa" str.
mobile: 089 575 0749 / 089 666 3057

Troyan
49 "Makedoniya" str.
mobile: 089 666 9079 / 089 673 4489

Haskovo, 5 "Okolovrasten pat" str.
South Industrial zone
mobile: 089 666 3051 / 089 241 2833