

TECHNICAL DATA SHEET**CONTROL BLACK COATING SPRAY**

Control Black Coating Spray is a black paint used to control the surface after repairing damages of the car body. It is easy to apply and dries quickly. After sanding it reveals surface imperfections and places that require further processing. Control Black is compatible with all types of primers and fillers, including epoxy, acrylic, polyester and alkyd products.

PRODUCT FOR PROFESSIONAL USE!

PRODUCT COLOUR

Black.

PROPERTIES

- ✓ Easy application.
- ✓ Quick drying.
- ✓ Good sandability.
- ✓ Silicone free.
- ✓ Compatible with various types of primers and fillers.

TECHNICAL INFORMATION

Basis:	Nitro-combi binder, black pigment, sandable fillers, flow improving additives.
Solvents:	Esters and ketones.
Odour:	Acetone and esters.
Appearance:	Matt black coating layer.
Density:	0.84
Drying times:	Depends on layer thickness, temperature and ventilation.
Indication:	Sanding: approx. 3-5 minutes Overcoating: not applicable, product is sanded off.

WAY OF USE

Use at room temperature.
Shake before use to mix the product well in the container (approx. 3 minutes).
The surface must be dry and clean, free from dirt, rust, grease etc.

- ✓ Apply a very thin layer of the product on the prepared surface.
- ✓ Leave to evaporate/dry.
- ✓ Sand with sandpaper.
- ✓ Clean the nozzle after use to prevent clogging. To do it - hold the can upside down and spray until only gas is released.

ATTENTION! To obtain the "mist" effect, apply from a distance of 15-20 cm from the controlled surface. Difference in colour indicate surface imperfections.

WORKING CONDATIONS

- ✓ Application temperature: 15°C-30°C.
- ✓ Air temperature: 15°C-30°C.
- ✓ Surface temperature: 15°C-30°C, but above the dew point.
- ✓ Can temperature: 18°C-25°C.
- ✓ Relative humidity: max 80%.

TECHNICAL DATA SHEET**CONTENT OF VOLATILE ORGANIC COMPOUNDS**

II/B/e limit=840 g/l, VOC = 659,9 g/l

STORAGE CONDITIONS

- ✓ Shelf life in originally sealed container at a temperature of 10°C - 20°C is 60 months.
- ✓ Store in a cool place, away from heat/sparks/open flames/hot surfaces. No smoking.
- ✓ Pressurized container: Do not pierce or burn, even after use.
- ✓ Do not spray on an open flame or other ignition source.
- ✓ Avoid breathing spray.
- ✓ Wear protective gloves / eye protection.
- ✓ Use only outdoors or in a well-ventilated area.

HEALTH AND SAFETY REGULATIONS

According to the Material Safety Data Sheet for particular product.

PACKAGING

ITEM NO	TYPE	CAPACITY	PACKAGING (PCS)	PACKAGING (KG)
80663	Control Black	400 ml		

The information given is based on careful laboratory research and many years of experience. Strong market position does not absolve us from constant control of the quality of our products. However, we are not responsible for the final results after incorrect use of the product.



Sofia 6 "Andrey Germanov" str. mobile: 089 666 3042 / 089 468 3880	Sofia, "Ovcha Kupel 1" quarter 33 "Promishlena" str., 429 bl., store 18, mobile: 089 666 9071	Plovdiv 176 "Brezovsko shose" str. mobile: 089 544 7503 / 089 666 3044	Varna 25 "Usta Kolyu Ficheto" str. mobile: 089 666 9079 / 089 466 9023
Shumen, "Dobrudzhanski" quarter Ind. zone, "Stroykomplekt" site mobile: 089 455 1685 / 089 666 3043	Kardzhali 1 "Klokotnitsa" str. mobile: 089 575 0749 / 089 666 3057	Troyan 49 "Makedoniya" str. mobile: 089 666 9079 / 089 673 4489	Haskovo, 5 "Okolovrasten pat" str. South Industrial zone mobile: 089 666 3051 / 089 241 2833