

TECHNICAL DATA SHEET



Spray adhesive - Contact adhesive klej spray

Transparent adhesive spray, based on styrene butadiene rubber, resins and hydrocarbon solvents.

Bonds a wide range of materials such as: wood, stone, rubber, canvas, cardboard, metal, paper, cork, foam, etc.

FOR PROFESSIONAL USE!

PRODUCT CHARACTERISTICS

- Easy and clean in use.
- ♦ Strong binding.
- ♦ Quick adhesion.
- Moisture resistant.
- Low viscosity adhesive.

ATTENTION: Safe to use on most surfaces and materials. However, the adhesive can damage some materials, so surfaces must always be checked first in an invisible place.

GROUND PREPARATION

- ♦ Clean and degrease the ground
- For a better effect, the ground can be sanded with p400 paper.

INSTRUCTION FOR USE

- ♦ Shake before use for about 1 minute.
- ♦ Spray the surface / object to be glued.
- ♦ Leave to evaporate for ca. 5 minutes.
- Stick the surfaces firmly together.
- Remove the excess of the adhesive with white spirit.
- ♦ Clean the sprayer after painting by puting the container upside down and pressing the valve for approx. 5 seconds.
- ♦ Application temperature (10°C 35°C)



TECHNICAL DATA SHEET

Ρ	E	R	F	O	R	M	Α	N	CE

400 ml, ± 1.1 m²

CONTENT OF VOLATILE ORGANIC COMPOUNDS

VOC II/B/e limit = 840 g/l, VOC = 587.7 g/l

STORAGE CONDITIIONS

Store in a cool (10°C-20°C) and dry place, away from the sources of fire and heat. The shelf life of the product in originally sealed container at 20°C is 60 months.

HEALTH AND SAFETY REGULATIONS

According to Material Safety Data Sheet of Dangerous Substance for particular product.

PACKAGING

Art. No: Capacity, ml: Package, psc.: Weight of carton, kg: 80606 400 12 5.20

The information provided is based on careful laboratory research and many years of experience. A strong market position does not absolve us from constant quality control of our products. However, we are not responsible for the final effects if used incorrectly.

