

Page: 1 of 10

Print date: 24.02.2025 Update:24.02.2025

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Trade Name: Hardener for light polyester putty LIGHT

1.2. Identified relevant uses of the substance or mixture and non-recommended uses

Formulation and packaging in small containers. Industrial application as a polymerization initiator for polymer production, as well as a crosslinking agent for the production of resins. Professional as a means of mesh bonding of roofing resins

[F; ERC2; PROC1, PROC2, PROC3, PROC5, PROC8a, PROC8b, PROC9, PROC15; PC32] [F; ERC3; PROC5, PROC8b, PROC14; PC32] [IS; SU11, SU12; ERC6d; PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15; PC32]

[PW; ERC8b; PROC5, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC19, PROC21; PC32] [PW; ERC8e; PROC5, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC19, PROC21; PC32]

Application of the substance/preparation

Dibenzoyl peroxide, paste Hardener

Catalyst for polymerization

1.3. Details of the safety data sheet provider

RAICHEM S.p.A.

Via Don Grazioli, 53 - Località Gavassa 42122 Reggio Emilia (Italy)

Tel. +39 0522 511182 - Fax +39 0522 920616

Information cell: RAICHEM S.p.A. - E-mail: laboratorio@raichem.it

Producer: RANAL Sp. z o.o.

Łódzka 3

42-240 Rudniki k. Częstochowy, PL

Tel.: +48 34 329 45 03 Fax: +48 34 320 12 16

Registration number: 000029202

Distributor: Ada Color Ltd 176 Brezovsko Shose, str. 4003 Plovdiv, Bulgaria Mobile: +359896663052 Phone: +35932940456 Fax: +35932940457 Web: adacolor-bg.com

1.4. Emergency phone number

Chemicals Bureau +48 42 2538 400

RAICHEM S.p.A. - Technical support: Tel. +39 0522 511182 (Monday-Friday: 8.30 (AM) -12.30 (PM), 2.00-4.30 PM)

Additional information: Bulgaria:

Toxicology Clinic at the Hospital for Active Treatment of Sick

Patients "N.I. Pirogov" Emergency phone number:

+359 02 9154 409 (during standard working hours except Saturdays and Sundays)

+359 02 9154 346 (continuous service)

SECTION 2: DESCRIPTION OF HAZARDS

2.1. Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Org. Perox. E H242 Heating may cause a fire. Eye Irrit. 2 H319

Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic reaction to the skin.

Aquatic Acute 1 H400 Highly toxic to aquatic organisms.

Aquatic Chronic 1 H410 Highly toxic to aquatic organisms, with a long-lasting effect.

2.2. Label elements

Labelling in accordance with Regulation (EC) No 1272/2008

The product is classified and labeled in accordance with CLP regulations.

Pictograms identifying the type of threat:







GHS02

GHS07

GHS09



Page: 1 of 10

Print date: 24.02.2025 Update:24.02.2025

Signal word: Attention.

Labelling hazard ingredients

dibenzoyl peroxide

Hazard Warnings:

H242 Heating may cause a fire. H319 Causes

serious eye irritation.

H317 May cause an allergic reaction to the skin.

H410 Highly toxic to aquatic organisms, with a long-lasting effect.

Safety recommendations:

P101 If medical attention is needed, carry the packaging or label of the product. P102 Keep out of

the reach of children.

P280 Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 IN

CASE OF SKIN CONTACT: Wash with plenty of soap and water.

P305+P351+P338 IN CASE OF CONTACT WITH EYES: Gently rinse with water for several minutes. Remove contact lenses, if any, and as much as possible. Keep rinsing.

P403+P235 Store in a well-ventilated area. Store in a cool place.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other dangers

Results of the assessment of PBT and vPvB values

PBT: The mixture does not contain substances which, in concentrations of >0.1%, present such a hazard. vPvB: The mixture does not contain substances which, in concentrations of >0.1%, present such a hazard.

Determination of endocrine disrupting properties:

The mixture does not contain substances that in concentrations >0.1% create such a hazard.

SECTION 3: COMPOSITION/INGREDIENT INFORMATION

3.2. Mixtures

Description: A mixture of the ingredients listed below with safe impurities

Dangerous ingredients:		
CAS: 94-36-0	dibenzoyl peroxide	45-52%
EINECS: 202-327-6	Org. Perox. B, H241; Aquatic Acute 1, H400	
Zip code number: 617-008-00-0	(M=10); Aquatic, Chronic 1, H410 (M=10);	
Reg. №.: 01-2119511472-50-XXXX	Eye Irritates. 2, H319; Skin Sens. 1, H317	
CAS: 107-21-1	ethane-1,2-diol	0,1-9,9%
EINECS: 203-473-3	STOT RE 2, H373; Acute Tox. 4, H302	
Postal code number: 603-027-00-1		
Reg. №.: 01-2119456816-28-XXXX		

Additional instructions:

If the ATE value is not specified, you should familiarize yourself with the LD/LC50 values in section 11. The full text of the cited hazard guidelines is found in Chapter 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Summary: Dirty, soaked clothing should be removed immediately.

After inhalation: Provide plenty of fresh air and call a doctor for safety.

In case of loss of consciousness, placement and transport in a stable lateral position.

In case of skin contact: In case of prolonged skin irritation, seek medical attention. Wash immediately with soap

and water and rinse thoroughly.

After contact with the eye: Rinse the eyes with the eyelid open for a few minutes under running

water. If symptoms persist, consult a doctor.

After ingestion: Do not induce vomiting and call a doctor.

4.2. The most significant acute symptoms and effects occurring after a certain period of time

No additional material data available

4.3. Indication of the need for any emergency medical care and special treatment

No additional material data available

SECTION 5: FIRE MEASURES

5.1. Fire extinguishing agents Suitable extinguishing agents:

CO2, fire extinguishing powder or water jet. A large fire should be extinguished with a water jet or with foam resistant to alcohol. Fire extinguishing procedures should be adapted to the situation.



Page: 1 of 10

Print date: 24.02.2025 Update:24.02.2025

5.2. Particular hazards arising from the substance or mixture

During a fire, the following can be released:

Carbon dioxide (CO₂) Carbon monoxide (CO) Benzoic acid Benzene Biphenyl

Phenyl benzoate

Under some fire conditions, the presence of traces of other poisonous substances cannot be ruled out.

5.3. Tips for firefighters Special

protective equipment:

Do not inhale the gases that are formed during explosions and fires. Protect the airways with a suitable device.

Wear appropriate firefighting equipment.

Other data

Cool endangered tanks with a water jet.

Contaminated water must be collected separately, it cannot get into the sewer.

SECTION 6: EMERGENCY DISCHARGE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Keep ignition sources at a safe distance.

Wear protective clothing. Persons who are not protected should be moved to a safe place. Ensure sufficient ventilation.

In case of aerosol dust (steam) action, use respiratory protection.

6.2. Precautions to protect the environment

In case of falling into water bodies or sewers, notify the relevant authorities.

Do not allow penetration into sewage / surface water / groundwater.

6.3. Methods and materials for restraint and cleaning

Download mechanically. Do not allow it to dry out. Ensure sufficient ventilation.

6.4. Reference to other sections

For information on safe operation, see Section 7. For information on personal protective equipment, see Sections 8. For information on disposal, see section 13.

SECTION 7: OPERATION AND STORAGE

7.1. Precautions for safe operation

Use only in well-ventilated areas.

Ensure good ventilation/suction in the workplace. Keep away

from heat and direct sunlight.

Prepare measures against electrostatic charges.

Fire and explosion safety guidelines:

The material/product in a dry state keeps combustion. Keep

ignition sources away - do not smoke tobacco.

7.2. Conditions for safe storage, including incompatibilities Storage:

Requirements for storage rooms and tanks:

Store in a cool place. Store only in the original

harrels.

Guidelines on co-storage:

Do not store together with gearboxes, heavy metal compounds, acids and alkalis.

Additional instructions on storage conditions:

Store the tank in a well-ventilated area. Avoid drying.

Keep the tank tightly closed. Keep away from

heat and direct sunlight.

The material stored in the original packaging, away from the sun's rays, retains its properties for a period of 12 months from the date of manufacture.

Recommended storage temperature: +5°C / +25°C.

7.3. Specific end-use(s)

No other relevant data is available.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTIVE EQUIPMENT

8.1. Control parameters

National occupational exposure limit values and biological limit values*:



Page: 1 of 10

Print date: 24.02.2025 Update:24.02.2025

Ingredients with controlled limit values depending on the workplace:			
94-36-0 Dibenzoyl Peroxide			
NDS (PL)	NDSCh: 10 mg/m ³		
	NDS: 5 mg/m ³		
FOR THE	NDS: 5 mg/m ³		
(US) REL	NDS: 5 mg/m ³		
(US) TLV	NDS: 5 mg/m ³		
(US)	A4		
107-21-1 ethane-1,2-diol			
NDS (PL)	NDSCh: 50 mg/m ³		
	NDS: 15 mg/m ³		
	Skóra		
IOELV (EU)	NDSCh: 104 mg/m ³ , 40 ppm		
	NDS: 52 mg/m³, 20 ppm		
	Skin		
TLV (US)	NDSCh:10** mg/m³, 50* ppm		
	NDS: 25* ppm		
	*vapor fraction:**inh.fraction, aerosol only, A4		
WEEL (US)	I (2)		

Information on legal provisions

NDS (PL): OJ 2024 item 1017, 10.07.24

PEL (US): Guide to Occupational Exposure Values (OSHA PELs) REL (US): Guide to Occupational Exposure Values (NIOSH RELs) TLV

(US): Guide to Occupational Exposure Values (TLV)

IOELV (EU): (EU) 2019/1831

WEEL (US): Guide to Occupational Exposure Values (AIHA WEELs)

DNEL Rates		
94-36-0 Diben	zoyl Peroxide	
Oral	DNEL / Long term exposure - Systemic effects	2 mg/kg bw/d (general population) Repeated dose toxicity
Koženi	DNEL / Long term exposure - Systemic effects	17 mg/kg bw/d (general population) Repeated dose toxicity 34,3 mg/kg bw/d (workers) Repeated dose toxicity
	DNEL / Long term exposure - Local effects	0,034 mg/kg (workers) skin irritation/corrosion
Inhalable	DNEL / Long term exposure - Systemic effects	3,5 mg/m3 (general population) Repeated dose toxicity 39 mg/m3 (workers) Repeated dose toxicity
107-21-1 ethane	e-1,2-diol	
Kozheni	DNEL / Long term exposure - Systemic effects	53 mg/kg bw/d (general population) Repeated dose toxicity 106 mg/kg bw/d (workers) Repeated dose toxicity
Inhalable	DNEL / Long term exposure - Local effects	7 mg/m3 (general population) Skin irritation/corrosion 35 mg/m3 (workers) Skin irritation/corrosion
PNEC values		
94-36-0 Diben	zoyl Peroxide	
PNEC/aqua	0,00002 mg/l (freshwater	
	0,000602 mg/l (intermittent	
	releases) 0,000002 mg/l (marine	
PNEC/sediment	water) 0,0127 mg/kg dw	
	(freshwater) 0,00127 mg/kg dw	
PNEC/soil	(marine water) 0,0025 mg/kg dw	
PNEC/STP	0,35 mg/l (sewage treatment plant)	
107-21-1 etha	· · · · · · · · · · · · · · · · · · ·	
PNEC/aqua	10 mg/l (freshwater)	
	10 mg/l (intermittent releases)	
	1 mg/l (marine water)	
PNEC/sediment	37 mg/kg DO (freshwater)	
DNEG/ II	3,7 mg/kg DO (marine	
PNEC/soil PNEC/STP	water) 1,53 mg/kg DU 199,5 mg/l (sewage treatment plant)	

Additional tips: The basis was the lists currently in force.

8.2. Exposure control

Appropriate technical means of control No further data, see paragraph 7. Individual protective equipment as individual protective equipment

General protection and hygiene measures:

During work, do not eat, drink, smoke, do not use tobacco. The usual precautions must be observed when working with chemicals. Keep away from food,

beverages and feed.

Contaminated, soaked clothing should be removed

immediately. Wash your hands before rest and before the

end of work.

Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.

Respiratory protection

In case of insufficient ventilation, protection of the respiratory tract.

Hand protection:



Page: 1 of 10

Print date: 24.02.2025 Update:24.02.2025



Protective gloves

The material from which the gloves are made must be impermeable and resistant to the action of the product / substance

Selection of material for protective gloves with regard to penetration time, penetration rate and degradation.

The material from which the gloves are made

Nitrile rubber

Recommended material thickness: ≥ 0.4 mm

The choice of suitable gloves depends not only on the material, but also on other quality characteristics and varies from manufacturer to manufacturer. Since the product is a preparation consisting of several substances, the resistance of the materials from which the gloves are made cannot be calculated in advance and must therefore be checked before use.

Penetration time for the material from which the gloves are made

The manufacturer of the gloves must be informed about the exact time of the breakdown and observed.

For the mixture of the following chemicals, the breakout time must be at least 480 minutes (penetration in accordance with EN 16523-1:2015: Level 6).

Eye or face protection

Personal Protective Equipment Symbols*:



Tightly closed safety glasses

Body protection: Light protective equipment

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties *

General data

State of concentration Permanent material

Colour Different, depending on the coloration Smell Characteristic Not applicable

Odor threshold Melting/freezing temperature 0 °C

Boiling point or initial temperature points

of boiling and boiling temperature range Not applicable Decay occurs before or during boiling

Flammability of materials

Lower and upper explosiveness limits

Lower: Not applicable Upper: Not applicable Flash point Not applicable Above the SADT value

Decomposition temperature SADT=50°

SADT: Self-Accelerating Decomposition Temperature pH at 20 °C

Indissoluble

Not applicable

May cause fire

Viscosity Kinematic viscosity 172000-754000 m2/s (Brookfield, 20°C) **Dynamic** 215000-867000 mPa·s

Solubility

Water

Partition coefficient n-octanol/water

(Value Log Ratio) Not applicable Steam pressure Not applicable

Density or relative density

Density at 20 °C 1.15-1.25 g/cm3 Relative Steam Density Not applicable **Characteristics of molecules** Hard pastes

9.2. Other Information

Appearance

Form In the form of paste

Important data for health and environmental protection and safety Ignition

temperature

Explosive properties The product does not pose an explosion hazard Change of state

Evaporation rate

Information on physical hazard classes **Organic peroxides** Heating may cause a fire



Page: 1 of 10

Print date: 24.02.2025 Update:24.02.2025

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No additional material data available

10.2. Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition during storage and handling in accordance with the intended purpose. Exothermic thermal decomposition.

When heated, visible decomposition by spontaneous ignition. SADT = 50°C

SADT (Self accelerating decomposition temperature) represents the lowest temperature at which the self-accelerating decomposition of the substances contained in the traditional packaging used to transport the product will be triggered.

A dangerous self-accelerating decomposition reaction and, under certain conditions, an explosion or fire may be caused by thermal decomposition in the SADT specified herein or better than it.

Contact with incompatible materials may cause decomposition of the SADT temperature or temperature below it.

10.3. Possibility of dangerous reactions

Reactions with reducing agents.

Reactions with heavy metals.

Reactions with bases, amines and strong acids.

10.4. Conditions to avoid

No additional essential data is available.

10.5. Incompatible materials

No additional essential data is available.

10.6. Hazardous decay products

Benzoic acid Benzene Biphenyl Phenyl Benzoate

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes set out in Regulation (EC) No 1272/2008*

Acute toxicity

Based on the available data, the classification criteria are not met.

Correspondi	Corresponding classified values of LD/LC50:					
94-36-0 Dibe	enzoyl Peroxide					
Oral	LD0	>2.000 mg/kg (mouse) (OECD TG 401: Acute Oral Toxicity)				
inhalation	LC0	24,3 mg/l (rat) (OECD TG 403: Acute Inhalation Toxicity)				
107-21-1 eth	nane-1,2-diol					
Oral Skin	LD50	7.712 mg/kg (rat)				
Inhalation	LD50	>3.500 mg/kg (mouse)				
	LC50/6h	>2,5 mg/l (rat)				

Initial Irritating Action: Action Type Method:

Skin corrosion / irritation Based on the available data, the classification criteria are not met.

Serious eye damage/eye irritation Irritates the eyes.

Sensitization of the respiratory tract or skin May cause an allergic reaction of the skin.

Germ cell mutagenicity Based on the available data, the classification criteria are not met.

Carcinogenicity Based on the available data, the classification criteria are not met.

Toxicity for reproduction			
94-36-0	Dibenzoyl Peroxide		
Oral	Effect on fertility - NOAEL	500 mg/kg bw/day (rat) (OECD TG 422: Combined Repeated Dose	
		Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)	
	Effect on developmental toxicity - NOAEL	300 mg/kg bw/day (rat) (OECD TG 414: Prenatal development toxicity study)	

Specific Organ Toxicity (Specific Toxicity) - Single Exposure Based on the available data, the classification criteria are not met.

Specific	Specific Organ Toxicity (Specific Organ Toxicity) - Repeated Exposure			
94-36-0	94-36-0 Dibenzoyl Peroxide			
Oral	Repeated dose toxicity – NOAEL	200 mg/kg bw/day (rat)		
		Chronic toxicity – systemic effects		
Leather	Repeated dose toxicity – NOEAL	833 mg/kg bw/day (rat)		
		Chronic toxicity – systemic effects		
	Repeated dose toxicity - NOAEL	0,17 mg/cm2 (mouse)		
		Repeated dose toxicity – local effects		

Inhalation hazard Based on available data, classification criteria are not met



Page: 1 of 10

Print date: 24.02.2025 Update:24.02.2025

11.2. Information on other hazards Endocrinedisrupting properties None of the ingredients are

on the list.

SECTION 12: ENVIRONMENTAL INFORMATION

12.1. Toxicity

Aquatic toxicity	
94-36-0 Dibenzoyl	Peroxide
LC50 / 96h	0,0602 mg/l (fish - Oncorhynchus mykiss) (OECD TG 203: Fish, Acute Toxicity Test)
EC50 / 48h	0,11 mg/l (crustacea - Daphnia magna) (OECD TG 202: Daphnia sp. Acute Immobilisation Test)
ErC50 / 72h	0,0711 mg/l (algae - Pseudokirchneriella subcapitata) (OECD TG 201: Alga, Growth Inhibition Test)
NOEC / 96h	0,0316 mg/l (fish - Oncorhynchus mykiss) (OECD TG 203: Fish, Acute Toxicity Test)
EC10 / 21d	0,001 mg/l (crustacea - Daphnia magna) (OECD TG 211: Daphnia magna Reproduction Test)
NOEC / 72 h	0,02 mg/l (algae - Pseudokirchneriella subcapitata) (OECD TG 201: Alga, Growth Inhibition Test)
107-21-1 ethane-1	,2-diol
LC50 / 96h	72.860 mg/l (fish - Pimephales promelas)
EC50 / 48h	>100 mg/l (crustacea - Daphnia magna) (OECD TG 202: Daphnia sp. Acute Immobilisation Test)
ErC50 / 96h	6.500-13.000 mg/l (algae - Pseudokirchneriella subcapitata)
NOEC / 72 h	>100 mg/l (algae - Pseudokirchneriella subcapitata) (OECD TG 201: Alga, Growth Inhibition Test)
NOEC / 7d	8.590 mg/l (crustacea - Ceriodaphnia dubia)

12.2. Durability and degradability

94-36-	O	D	ib	enz	ov	ΙP	е	ro	χiα	de	•

94-36-0 Dibenzoyi Peroxide	
Ready Biodegradability in water / 28d	71 % (OECD TG 301 D: Ready Biodegradability: Closed Bottle Test)
107-21-1 ethane-1,2-diol	
Ready Biodegradability in water / 10d	90-100 % (OECD TG 301A: Ready Biodegradability: DOC Die Away Test)

12.3. Bioaccumulative capacity

94-36-	O Dil	enzovi	Pero	ride

94-36-0 Di	Denzoyi Peroxide
Log Kow	3,2 /(22°C) (OECD TG 117: Partition Coefficient (n-octanol / water), HPLC Method))
BCF	306,3 /l/kg (fish) (QSAR calculation)

12.4. Soil Portability

94-36-0	Dibenzoyl	Peroxide

1			
	Log Koc	3,8 /(22°C) (OECD TG 121: (Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High	
	Log Noc	1 3,0 /(22 C) (OLCD TO 121: (Estimation of the Masorption Coefficient (Noc) on son and on sewage studge asing right	
		Dorformance Liquid Chromatography (HDLC)	
		Performance Liquid Chromatography (HPLC))	

12.5. PBT and vPvB PBT Assessment

Results: Not applicable vPvB: Not applicable

12.6. Endocrine disrupting properties *

The product does not contain substances with properties that disrupt hormonal balance.

12.7. Other adverse effects Caution:

Very toxic to fish. Additional

environmental guidelines:

General instructions:

In water bodies, it is also poisonous to fish and plankton.

very toxic to aquatic organisms

Water hazard class 2 *(self-determination): harmful to water.

Do not allow penetration into groundwater, surface water or sewage. Harmful to drinking water even with penetration of minimal amounts into the soil.

SECTION 13: WASTE DISPOSAL

13.1. Waste treatment methods

Recommendations:

It cannot be processed together with household waste. Do not allow penetration into the sewer. Removal in accordance with applicable regulations.

Uncleaned packaging:

Recommendations:

Removal in accordance with applicable regulations.

Packaging that cannot be cleaned must be disposed of as material.

SECTION 14: INFORMATION ON TRANSPORTATION

14.1. UN List Number or Identification Number ADR/RID/ADN, IMDG, IATA

UN3108

14.2. Exact name of the consignment on the UN list



Page: 1 of 10

Print date: 24.02.2025

ADR/RID/ADN

IMDG

IATA

Update:24.02.2025 ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE), HAZARDOUS

TO THE ENVIRONMENT

ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide), MARINE POLLUTANT

ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide)

14.3. Transport hazard class(s)

ADR/RID/DNA, IMDG



Class Label 5.2 Organic peroxides

5.2

IATA



Class 5.2 Organic peroxides

Label 5.2

14.4. Packaging Group

ADR/RID/ADN, IMDG, IATA

N/a

14.5. Environmental hazards

Marine pollution:

Yes Symbol (fish and trees)

Special markings (ADR/RID/ADN):

Symbol (fish and trees)

14.6. Special precautions for consumers

Attention: Hazard identification number (Kemler number):

EMS Number:

Storage category

Storage code

Code for segregation

Organic peroxides

F-J,S-R

D

SW1 Protected from heat sources.

SG35 Charging "separately" SGG1-acids SG36 Charging "separately from" SGG18-bases.

SG72 See 7.2.6.3.2.

14.7. Maritime transport of bulk cargo according to International Maritime Organization instruments

IMDG

Limited quantities (LQ)

UN 3108 ORGANIC PEROXIDE TYPE E, STAY (DIBENZOYL PEROXIDE), 5.2, **UN Model Regulation:**

ENVIRONMENTALLY HAZARDOUS

SECTION 15: INFORMATION ON THE REGULATORY FRAMEWORK

15.1. Substance- or mixture-specific safety, health and environmental legislation/legislation

Regulation (EC) No 1907/2006 (REACH - Registration, evaluation, authorisation and restriction of chemicals)

Regulation (EC) No 1272/2008 (CLP - Classification, labelling and packaging of substances and mixtures) Safety data sheet: Regulation (EU) No 878/2020 (amending Regulation (EC) No 1907/2006, Annex II)

Directive 2012/18/EC (Seveso)

List of hazardous substances - ANNEX I, none of the ingredients are on the list **Seveso Category**

P6b SELF-ACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

E1 Hazardous to the aquatic environment

Threshold value (in tonnes) related to the application of the requirements for high-risk enterprises 50 t Threshold

value (in tonnes) related to the application of the requirements for high-risk enterprises 200 t

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II - none of the ingredients is on the list

REGULATION (EC) No 273/2004 on drug precursors - none of the ingredients are on the list

REGULATION (EC) No 111/2005 laying down rules for monitoring trade in drug precursors between the Community and third countries none of the ingredients is on the list

REGULATION (EU) 2019/1148:

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit limit for the purposes of granting permits pursuant to Article 5 (3)) - none of the ingredients is listed



Page: 1 of 10

Print date: 24.02.2025 Update:24.02.2025

Annex II - NOTIFIABLE EXPLOSIVES PRECURSORS - none of the ingredients is listed

15.2. Safety assessment of the chemical substance or mixture

A Chemical Safety Assessment was carried out:

Dibenzoyl Peroxide - CAS 94-36-0

SECTION 16: FRIEND INFORMATION

The data is based on the current state of our knowledge, but does not definitively determine the production properties and cannot be the basis for legitimate contracts.

Relevant phrases

H241 May cause fire or explosion when heated. H302 Harmful if

swallowed.

H317 May cause an allergic skin reaction. H319 Causes

serious eye irritation.

H373 May cause organ damage with prolonged or repeated exposure. H400 Highly toxic to aquatic

organisms.

H410 Highly toxic to aquatic organisms, with a long-lasting effect.

Classification according to Regulation (EC) No 1272/2008

elaboritation according to Regulation (10) No 117 1/ 1000			
Organic peroxides	Expert assessment		
Serious eye damage/eye irritation Sensitizing effect on the skin Posing a threat to the aquatic environment - Short-term (acute) threat to the aquatic environment Posing a threat to the aquatic environment - Long-term (chronic) threat to the aquatic environment	In accordance with Directive 1272/2008 (EC), the classification of a mixture is based on a calculation method using material data.		

(1.2) Essential identified uses of the substance or mixture and recommended uses to be avoided

No additional material data available

Life cycle stage

F Formulation or repackaging

IS Application in industrial sites

PW General Application by Professional Employees

Application Sector

SU11 Manufacture of rubber products

SU12 Manufacture of plastic articles, including preparation of mixtures and conversion

Product Category

PC32 Detergents and polymer compounds

Process category

PROC1 Production of chemicals or refining in a closed process with no likelihood of exposure or processes with equivalent protection conditions.

PROC2 Manufacture of chemical or refined products in closed continuous processes with episodic, controlled exposure or processes with equivalent protection conditions.

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with episodic, controlled exposure or processes with equivalent protection conditions.

PROC4 Chemical manufacturing where exposure opportunity arises PROC5 Mixing

or combining in batch processes

PROC6 Calendering Operations PROC7 Industrial Dusting Application

PROC8a Carriage of substances or mixtures (loading/unloading) in spaces not intended for this purpose. PROC8b Carriage of substances or mixtures (loading and unloading) in spaces intended for this purpose

PROC9 Transfer of substances or mixtures into small containers (filling line intended for this purpose together with weighing)

PROC10 Brush or roller application

PROC11 Non-industrial spraying

PROC13 Handling of articles by immersion and pouring

 ${\sf PROC14\ Tableting,\ pressing,\ squeezing,\ granulating,\ granulating\ PROC15\ Use\ as}$

laboratory reagents

PROC19 Manual actions with close contact with the substance

PROC21 Low Energy Handling and Transfer of Substances Related to/to Materials or Articles

Category of release of substances into the environment

ERC2 Formulation in Mixture

ERC3 Formulation in Rigid Matrix

ERC6d Use of Reactive Process Regulators in Polymerization Processes in an Industrial Site (Inclusion in or on the Surface of the Article) ERC8b General application of reactive excipient (not included in or on the surface of the device, indoors) ERC8e General application of reactive excipient (not included in or on the surface of the device, outdoors)

Contact Partner: Raichem S.p.A. Previous Version Date: 25.11.2022 Previous Version

Number: 3



Page: 1 of 10

Print date: 24.02.2025 Update:24.02.2025

Abbreviations and acronyms:

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals GHS: Globally Harmonised System of Classification and Labelling of Chemicals

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

CLP: Classification, Labelling and Packaging TLV: Threshold Limit Value

TLV-TWA: Threshold Limit Value - Time Weighted Average TLV-STEL: Threshold Limit Value - Short Term Exposure Limit

PEL: Permissible Exposure Limits

REL: Recommended Exposure Limits (Limiti di esposizione raccomandati)

IOELV: Indicative Occupational Exposure Limit Value

WEELs: Workplace Environmental Exposure Limits (BEI): Biological Exposure Indices

LD50: Lethal dose, 50 percent

LC50: Lethal Concentration, 50 percent LC0: Lethal Concentration 0 - no effect LD0: Maximum tested dose with no mortality. NOAEL: No Observed Adverse Effect Level Kow: Octanol-Water partition coefficient Koc: Organic Carbon partition Coefficient

BCF: BioConcentration Factor

LC50: LC50: Lethal Concentration, 50 percent EC50: Effective Concentration, 50 percent EC10: Effective Concentration, 10 percent

ErC50: Effective Concentration, 50 percent, growth rate

NOEC: No-Observed Effect Concentration.

WGK: Wassergefährdungsklasse - Water hazard class [Germany]

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Org. Perox. B: Organic Peroxides - Type B Org. Perox. E: Organic Peroxides - Type E/F Acute Tox.

4: Acute toxicity - Category 4

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

STOT RE 2: STOT (Specific Organ Toxicity) - Repeated Exposure - Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - Acute to the aquatic environment - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term danger to the aquatic environment - Category 1

^{*} Data has changed compared to the previous version