

# TECHNICAL DATA SHEET

**LUCENZA**  
*Stucchi Decorativi*

BAGLIORE PERLATO  
Декоративна мазилка ПЕРЛА



## DESCRIPTION

Interior decorative plaster with pearlescent beads, based on an acrylic copolymer binder, designed for use as a final decorative interior finish. It is easy to apply with a brush, allowing the creation of various decorative textures and effects.

## CHARACTERISTICS

Water-based decorative plaster with high vapor permeability, allowing the surface to breathe. Provides a bright, pearlescent, and textured appearance.

## APPLICATION AREAS

After cleaning and preparing the substrate, the PEARL decorative plaster can be applied over previously painted surfaces, concrete, gypsum, cement plaster, cement boards, and wooden surfaces.

## SURFACE PREPARATION

**Preparation and application on uneven or old, flaking substrates:**

1. The surface must be thoroughly cleaned from dust, grease, or other contaminants. All old, flaking, or unstable coatings must be completely removed.
2. Apply a concrete-contact primer to strengthen the substrate, ensure better adhesion, and provide a stable base for subsequent coatings.
3. Level with a fine polymer filler, if necessary. After priming, any irregularities, cracks, or defects must be filled and smoothed to achieve an even and uniform surface.
4. Sand the filler to obtain a smooth finish. Once the filler is completely dry, sand the surface with suitable sandpaper or a sanding machine. Remove all sanding dust.
5. Apply a primer for decorative plaster. On the sanded and cleaned surface, apply a white or pre-tinted decorative plaster primer to improve adhesion and provide a strong base. Tinting the primer in the same color as the plaster is recommended for better coverage and results.
6. Apply the decorative plaster. Once the primer is dry and the surface is smooth and defect-free, the PEARL decorative plaster can be applied.

## Preparation and application on a sound and smooth substrate:

1. Apply a white or pre-tinted decorative plaster primer, depending on the desired final color and covering capacity. Tinting the primer in the same color as the plaster is recommended for optimal results.
2. After the primer dries, proceed with the final application of the PEARL decorative plaster.

## APPLICATION

The decorative plaster is applied onto the prepared surface with a brush. The desired decorative effect is created using the brush before the material dries.

## IMPORTANT INSTRUCTIONS

Stir well before use until a homogeneous mixture is obtained.

Apply at temperatures from +5°C to +35°C.

Surfaces must be dry and clean. Application should follow the instructions provided on the product label.

Treated surfaces must be protected from mechanical impact for 3 days and from rain, snow, freezing, or high temperatures for 24 hours.

Clean brushes, rollers, and tools with water after each application.

## TECHNICAL DATA

**Density (g/cm<sup>3</sup>):** 1.10 ± 0.02

**pH:** 8.5-9

**Solids content (%):** 50 ± 2

**Dilution:** Ready to use (can be diluted with up to 5% water if necessary)

**Color:** Gold, Silver, Copper, Bronze can be tinted using a tinting system

**Coverage:** 7-9 m<sup>2</sup>/L

**Drying time:** Touch dry: 4–5 hours / Fully dry: 24 hours

**Shelf life:** 2 years

**Packaging:** 1 l / 2.5 l



Sofia  
6 "Andrey Germanov" str.  
mobile: 089 666 3042 / 089 468 3880

Sofia, "Ovcha Kupel 1" quarter  
33 "Promishlena" str., 429 bl., store 18,  
mobile: 089 666 9071

Plovdiv  
176 "Brezovsko shose" str.  
mobile: 089 544 7503 / 089 666 3044

Varna  
25 "Usta Kolyu Ficheto" str.  
mobile: 089 666 9079 / 089 466 9023

Shumen, "Dobrudzhanski" quarter  
Ind. zone, "Stroykomplekt" site  
mobile: 089 455 1685 / 089 666 3043

Kardzhali  
1 "Klokotnitsa" str.  
mobile: 089 575 0749 / 089 666 3057

Troyan  
49 "Makedoniya" str.  
mobile: 089 666 9079 / 089 673 4489

Haskovo, 5 "Okolovrasten pat" str.  
South Industrial zone  
mobile: 089 666 3051 / 089 241 2833