

## TECHNICAL DATA SHEET



### DESCRIPTION

Venetian plaster for interior and exterior based on acrylic copolymer binder. Paste-like, contains special additives and pigments such as quartz, marble powder, etc. Applied with a trowel or spatula. Forms a marble effect on the surface.

### CHARACTERISTICS

Venetian plaster with a marble effect, glossy, with high coverage. Thanks to its elastic structure, it does not crack. Ecological plaster with high vapor permeability, easy to clean, water-based.

### APPLICATION AREA

After cleaning and preparing the surface, Venetian plaster can be applied to old painted surfaces, concrete, gypsum, lime-cement plaster and wooden surfaces.

### SURFACE PREPARATION

#### Preparation and application for uneven or old crumbling coatings:

1. The surface must be dry, well cleaned of dust, grease or other dirt. All old crumbling or unstable coatings must be completely removed.
2. Application of a concrete contact type primer to strengthen the base, for better adhesion and to provide a more stable surface for subsequent coatings.
3. Leveling with a fine polymer putty, if necessary. In case of irregularities, cracks or other defects on the surface after priming, they must be filled and leveled to achieve an even and smooth surface.
4. Sanding the putty to obtain a smooth coating. After the putty has completely dried, the surface is sanded with a grinder or with sandpaper of a coarseness depending on the roughness. The dust formed by sanding must be cleaned.
5. Application of a primer for decorative plasters. On the sanded and cleaned surface, for a stronger base and good adhesion, a primer for decorative plaster is applied, white or pre-colored, depending on the requirements for the final color and coverage. It is recommended to color the primer in the same color as the plaster to achieve better results.
6. Application of the decorative plaster. After the primer has dried on a smooth surface without defects, the Venetian plaster can be applied.
7. After applying and polishing the Venetian plaster, apply wax for Venetian plaster.

#### Preparation and application on a solid and flat surface:

1. Application of a primer for decorative plaster, white or pre-colored, depending on the requirements for the final color and coverage. It is recommended to color the primer in the same color as the plaster to achieve better results.
2. After the primer has dried, the final application of the Venetian plaster is performed.
3. After applying and polishing the Venetian plaster, apply wax for Venetian plaster.

#### APPLICATION

Before use, the Venetian plaster is mixed well until a homogeneous mixture.

Ready to use, it is applied without thinning on a pre-primed surface. The application is carried out with a trowel or spatula in at least two layers. After applying the second layer, different colors can be added and combined

The interval between layers is 4-6 hours. The material is applied by forming an even and smooth surface by means of crosswise, horizontal and vertical movements with a spatula or trowel. In the final stage, by applying pressure on the trowel, the surface is polished, working left-right, up-down and in circular movements.

#### IMPORTANT INSTRUCTIONS

Before use, the plaster must be mixed well until a homogeneous mixture is obtained.

It is applied at a temperature of +5°C to +35°C.

The surfaces must be dry and clean. The application is carried out according to the application information on the label.

The treated surfaces must be protected from mechanical impacts for 3 days, and from rain, snow, frost or high temperatures for 24 hours.

After each application, clean the brushes, rollers and tools with water.

#### TECHNICAL DATA

**Density (g/cm<sup>3</sup>):** 1.60 ± 0.02

**pH:** 7.5-9

**Dry matter (%):** 68 ± 2

**Dilution:** Ready to use (do not dilute).

**Color:** Can be tinted using a tinting system.

**Coverage:** 7-8 m<sup>2</sup>/l

**Drying time:** Dry to the touch: 3-4 hours / Completely dry: 24 hours

**Shelf life:** 18 months

**Packages:** 1 kg / 4 kg / 20 kg



# АДА КОЛОР

• Ж И В О Т В Ц В Е Т О В Е •

[www.adacolor-bg.com](http://www.adacolor-bg.com)

гр. София  
ул. „Андрей Германов“ 6  
GSM: 089 666 3042 / 089 468 3880

гр. София, кв. Овча Купел 1,  
ул. „Промислена“ 33, бл.429, мар. №18  
GSM: 089 666 9071

гр. Пловдив  
ул. „Брезовско шосе“ 176  
GSM: 089 544 7503 / 089 666 3044

гр. Варна  
ул. „Уста Кольо Фичето“ 25  
GSM: 089 666 9079 / 089 466 9023

гр. Шумен, кв. Добруджански,  
инд. зона: база на Стройкомплект  
GSM: 089 455 1685 / 089 666 3043

гр. Кърджали  
ул. „Клокотница“ 1  
GSM: 089 575 0749 / 089 666 3057

гр. Троян  
ул. „Македония“ 49  
GSM: 089 666 9079 / 089 673 4489

гр. Хасково, Южна индустриална  
зона, ул. „Околовръстен път“ 5  
GSM: 089 666 3051 / 089 241 2833