

TECHNICAL DATA SHEET



DESCRIPTION

Sand plaster for interior based on acrylic copolymer binder, with pearl pigment and dense sand texture. Applied with a brush.

CHARACTERISTICS

Interior decorative sand plaster, ecological, water-based, with high vapor permeability. Gives a shiny, pearly and textured look to the applied surface.

APPLICATION AREA

After cleaning and preparing the surface, the decorative sand plaster - SAHARA, can be applied to old painted surfaces, concrete, gypsum, black plaster and wooden surfaces.

SURFACE PREPARATION

Preparation and application for uneven or old crumbling coatings:

1. The surface must be thoroughly cleaned of dust, grease or other dirt. All old crumbling or unstable coatings must be completely removed.
2. Application of concrete contact primer to strengthen the base, for better adhesion and to provide a more stable surface for subsequent coatings.
3. Leveling with fine polymer putty, if necessary. In case of irregularities, cracks or other defects on the surface after priming, they must be filled and leveled to achieve an even and smooth surface.
4. Sanding the putty to obtain a smooth coating. After the putty is completely dry, the surface is sanded with suitable sandpaper or a grinder. The sanding dust must be removed.
5. Application of a primer for decorative plasters. On the sanded and cleaned surface for a stronger base and good adhesion, a primer for decorative plasters is applied, white or pre-colored, depending on the requirements for the final color and coverage. It is recommended to color the primer the same color as the plaster to achieve better results.
6. Application of the decorative plaster. After the primer has dried and the surface is smooth and free of defects, the decorative plaster - SAHARA can be applied.

Preparation and application on a solid and flat surface:

1. Application of a primer for decorative plasters, white or pre-colored, depending on the requirements for the final color and coverage. It is recommended to color the primer in the same color as the plaster to achieve better results.
2. After the primer has dried, the final application of the decorative plaster - SAHARA is carried out.

APPLICATION

The decorative sand plaster is applied undiluted to the primed surface with a brush. The desired decorative effect is also formed with a brush before the decorative plaster dries.

IMPORTANT INSTRUCTIONS

Before use, the decorative plaster must be mixed well until a homogeneous mixture is obtained.

It is applied at a temperature of +5°C to +35°C.

The surfaces must be dry and clean.

The application is carried out according to the application information on the label.

Treated surfaces must be protected from mechanical impacts for 3 days, and from rain, snow, frost or high temperatures for 24 hours.

After each application, clean brushes, rollers and tools with water.

TECHNICAL DATA

Density (g/cc): 1.15 ± 0.02

pH: 8.5-9

Dry matter (%): 50 ± 2

Dilution: Ready to use (can be diluted up to 5% with water if necessary)

Color: Gold, Silver, Copper, Bronze - can be tinted using a tinting system.

Consumption: 6-8 sq.m/l

Drying time: Dry to touch: 4-5 hours / **Completely dry:** 24 hours

Shelf life: 2 years

Packages: 1 l / 2.5 l



гр. София
ул. „Андрей Германов“ 6
GSM: 089 666 3042 / 089 468 3880

гр. София, кв. Овча Купел 1,
ул. „Промислена“ 33, бл.429, мар. №18
GSM: 089 666 9071

гр. Пловдив
ул. „Брезовско шосе“ 176
GSM: 089 544 7503 / 089 666 3044

гр. Варна
ул. „Уста Кольо Фичето“ 25
GSM: 089 666 9079 / 089 466 9023

гр. Шумен, кв. Добруджански,
инд. зона: база на Стройкомплект
GSM: 089 455 1685 / 089 666 3043

гр. Кърджали
ул. „Клокотница“ 1
GSM: 089 575 0749 / 089 666 3057

гр. Троян
ул. „Македония“ 49
GSM: 089 666 9079 / 089 673 4489

гр. Хасково, Южна индустриална
зона, ул. „Околовръстен път“ 5
GSM: 089 666 3051 / 089 241 2833