



THE BEST FOR YOUR WOOD.

Koralan[®] Holzlasur MATT

Lasur wood varnish for exterior - Matt

1. Product description

Product type	Wood scumble, acrylic-based for coating wooden elements outdoors. Ideal for the decorative design of, for example, board goods, wooden façades or façade profiles.
Protective effect	Protects wooden surfaces from the effects of weather (sun, rain). Reduces water absorption and therefore the risk of wood discolouration caused by fungi. The coating film is protected against blue stain and mould infestations (protection provided by the film).
Properties	<ul style="list-style-type: none">• Water-repellent• Glazing• Moisture regulating• Easy to sand• Low upridging of wood grains• Good filling of the wood pores
Scope of application	For decorative surface design of exterior wood without ground contact. Particularly suitable for products made of softwood.
Colour shades	Colour shades on request.
Container sizes	0.75 l 2.5 l

Cleaning the tools

After use with water and detergent. Do not allow material and cleaning residues to enter the sewage system. Do not wash painting tools in sinks or drains.

4. Special instructions

Labelling according to Regulation (EG) No. 1272/2008 [CLP]

Hazard warnings:

H412 Harmful to aquatic organisms, with long-term effects.

Safety instructions:

P273 Avoid release into the environment.

P501 Dispose of contents/containers in accordance with local/regional/national/international regulations.

Hazardous components for labelling:

EUH208 Contains mixture of 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazolin-3-one, 3-iodo-2-propinylbutylcarbamate. May cause allergic reactions.

Instructions for use and warnings

Misuse may cause health problems and lead to environmental damage. Contains biocidal product: IPBC. Keep out of reach of children. Avoid skin and eye contact; wear suitable protective clothing (e.g. protective gloves, goggles). Keep away from food, drinks and animal feed stuffs. If medical advice is required, have the packaging or label at hand. After working, wash your face and hands thoroughly with soap and water.

Storage and environmental protection

Store only in original containers!

Use opened containers as soon as possible.

Close the container tightly after use.

Do not discharge into surface water or the sewage system.

Do not store at temperatures below +5 °C or above +30 °C.

Shelf life

If stored in a cool, dry place protected from frost in the unopened original packaging.

At least 36 months.

Disposal

Dispose of cleaning residues properly as well as containers that are not empty (collection point for hazardous waste). Place emptied (drip-free) containers in recycling material containers.

EWC/ German Waste catalogue regulation [AVV]

08 01 20 – Aqueous suspensions containing paint or varnish, apart from those covered by 08 01 19.

VOC content

The maximum value (VOC content cat. A/e) for this product is, as per Directive 2004/42/EC: 130 g/l. The VOC content of this product in the ready-to-use condition is <130 g/l.

The above details are based on the latest technological developments and application methods and contain general advice. They describe our products, and provide information on the application and processing thereof.

Because application and processing are beyond our control, we are liable only for the consistent quality of our products as per our general terms and conditions. In the event of doubt, please contact our technical advisory team.