

TECHNICAL DATA SHEET



DESCRIPTION

Decorative pearl plaster with pearl beads and fine sand texture based on acrylic copolymer binder, intended for finishing decorative coating in interiors. It is easily applied with a brush, which allows the formation of various decorative textures and patterns.

CHARACTERISTICS

Gives a glossy, pearly and textured appearance to the treated surface. Water-based decorative plaster and an environmentally friendly product. It is characterized by high vapor permeability and easy cleaning by wiping.

APPLICATION AREA

After cleaning and priming the surface, the decorative plaster can be applied to old painted surfaces, concrete, gypsum, cement plaster, cement boards and wooden surfaces.

SURFACE PREPARATION

Preparation and application for uneven or old crumbling coatings:

1. Preparation and application for uneven or old crumbling coatings:
2. The surface must be thoroughly cleaned of dust, grease or other contaminants. All old crumbling or unstable coatings must be completely removed.
3. Application of a concrete contact type primer to strengthen the base, for better adhesion and to provide a more stable surface for subsequent coatings.
4. Leveling with a fine polymer putty, if necessary. In case of irregularities, cracks or other defects on the surface after priming, they must be filled and leveled to achieve an even and smooth surface.
5. Sanding the putty to obtain a smooth coating. After the putty has completely dried, the surface is sanded with suitable sandpaper or a grinder. Sanding dust must be removed.
6. Application of a primer for decorative plaster. On the sanded and cleaned surface, for a stronger base and good adhesion, a primer for decorative plaster is applied, white or pre-colored, depending on the requirements for the final color and coverage. It is recommended to color the primer in the same color as the plaster to achieve better results.
7. Application of the decorative plaster. After the primer has dried on a smooth surface without defects, the decorative pearl plaster can be applied.

Preparation and application on a solid and flat surface:

1. Application of a primer for decorative plaster, white or pre-colored, depending on the requirements for the final color and coverage. It is recommended to color the primer in the same color as the plaster to achieve better results.
2. After the primer has dried, the final application of the decorative pearl plaster is carried out.

APPLICATION

Apply to the primed surface without dilution with a brush. The desired structure/pattern is formed using a brush before the decorative plaster dries.

IMPORTANT INSTRUCTIONS

Before use, the plaster must be mixed well until a homogeneous mixture is obtained.

Apply at a temperature of +5°C to +35°C.

The surfaces must be dry and clean.

Application is carried out according to the application information on the label.

TECHNICAL DATA

Dry matter (%): 50 ± 2

Dilution: Ready to use (can be diluted up to 5% with water if necessary)

Color: Gold, Silver, Copper, Bronze - can be colored using a tinting system.

Consumption: 6-8 sq.m/l

Drying time: Dry to the touch: 4-5 hours / Completely dry: 24 hours

Shelf life: 2 years

Packages: 1 l / 2.5 l



www.adacolor-bg.com

гр. София
ул. „Андрей Германов“ 6
GSM: 089 666 3042 / 089 468 3880

гр. София, кв. Овча Кулел 1,
ул. „Промислена“ 33, бл.429, мар. №18
GSM: 089 666 9071

гр. Пловдив
ул. „Брезовско шосе“ 176
GSM: 089 544 7503 / 089 666 3044

гр. Варна
ул. „Уста Кольо Фичето“ 25
GSM: 089 666 9079 / 089 466 9023

гр. Шумен, кв. Добруджански,
инд. зона: база на Стройкомплект
GSM: 089 455 1685 / 089 666 3043

гр. Кърджали
ул. „Клокотница“ 1
GSM: 089 575 0749 / 089 666 3057

гр. Троян
ул. „Македония“ 49
GSM: 089 666 9079 / 089 673 4489

гр. Хасково, Южна индустриална
зона, ул. „Околовръстен път“ 5
GSM: 089 666 3051 / 089 241 2833