PRODUCT DATA SHEET

10808 ASBOYA ACRYLIC FLOOR PAINT SEMIGLOSS

Product description:
Special Acrylic resin based, one component, fast drying top coat paint on concrete and asphalt surfaces. It can also be used as a stone protector and stone varnish when taken as transparent.
It has the convenience of being produced in the desired color as semi-gloss.

General use
It can be easily applied on any asphalt or concrete floor with a roller, brush or airbrush. This product, which has high flexibility and excellent abrasion resistance, also has a very fast drying feature. It provides high resistance against salt water and chemicals, and the illumination factor facilitating night vision is at the upper limits. It can be used as reflective. It has the ability to be stored for many years.

Technicial Specifications

Density : 1.10-1.20 g/ml
Solids % : Weight : 40-50
: Volume : 35-45
Viscosity : 60 sec
Application viscosity: 60 sec (20oC, ready to use with roller)
Application viscosity: 18-20 sec (20oC, 5-10% thinner for the pistol)
Gloss : semi-gloss(60-70 G)

Drying Time

DRY TIME 20oC	DUST DRY	TOUCH DRY	DRY TO OPEN TO PEDESTRIAN TRAFFIC
	10-20 min.	60 min.	6 hours

CONSUMPTION	DRY FILM	WET FILM	THEORETICAL SPREAD
APPLICABLE (MICRON)	80-120	200-300	0,200-0,500 g/m^2
RECOMMENDED (MICRON)	100	250	0,250 g/m^2

Application
It can be applied by roller, brush or spray. In roller or brush applications, 2 coats of paint are applied. In airbrush applications, it can be applied as one or two coats according to the air or airless system. However, before applying 2 coats, the powder should be allowed to dry for 10 minutes. Since it has a very fine particle size, it does not cause blockage in the nozzles during application.
We can use varnish or own paint as a primer. It should be applied in 2 or 3 layers depending on absorbency.
Shelf life: 2 years in unopened package